

Turkish Universal Conceptual Cognitive Annotation

Necva Bölücü, Burcu Can

Hacettepe University, University of Wolverhampton

Department of Computer Engineering, Research Group in Computational Linguistics (RGCL)

Ankara Turkey, Wolverhampton UK

necvaa@gmail.com, b.can@wlv.ac.uk

Abstract

Universal Conceptual Cognitive Annotation (UCCA) is a cross-lingual semantic annotation framework that provides an easy annotation without any requirement for linguistic background. UCCA-annotated datasets have been already released in English, French, and German. In this paper, we introduce the first UCCA-annotated Turkish dataset that currently involves 50 sentences obtained from the METU-Sabancı Turkish Treebank. We followed a semi-automatic annotation approach, where an external semantic parser is utilised for an initial annotation of the dataset, which is partially accurate and requires refinement. We manually revised the annotations obtained from the semantic parser that are not in line with the UCCA rules that we defined for Turkish. We used the same external semantic parser for evaluation purposes and conducted experiments with both zero-shot and few-shot learning. This is the initial version of the annotated dataset and we are currently extending the dataset. We are releasing the current Turkish UCCA annotation guideline along with the annotated dataset.

Keywords: UCCA, semantic parsing, semantic annotation, Turkish, low-resource languages

1. Introduction

Semantics is concerned with anything related to meaning and explores answers to such questions (Vigliocco and Vinson, 2007): 1) How do we represent the meaning of each word? 2) How do the meanings of words form a semantic structure? 3) How are words related to each other in a semantic structure? Word embeddings allow the meaning of a word to be represented in a compact low-dimensional space. It is a learned representation where words with a similar meaning have similar representations. The first breakthrough in neural word representation is word2vec (Mikolov et al., 2013), a statistical-based method (built on a shallow neural architecture) for learning word embeddings via their contextual information obtained from a preferably large corpus. Learning high-quality word embeddings using neural methods rather than statistical methods such as co-occurrence matrices has improved the performance of all natural language processing (NLP) tasks such as text classification (Wensen et al., 2016; Li et al., 2018) and machine translation (Jansen, 2017; Qi et al., 2018), which applies to all languages with available large resources. Contextualised word embeddings such as BERT (Devlin et al., 2018) and its variations (Sanh et al., 2019; Yang et al., 2019) have recently been introduced, and have shown even better performance in almost any NLP task.

Better word representation techniques have paved the way for semantic representation for compositional semantics for bigger text units, such as phrases and sentences. Semantic representation is the process of mapping a given text into a formal or abstract form that can be understood by machines. Semantic representation is widely dominated by graph and tree-structured representations. Since graphs have the flexibility and

ability to express and generate adequate and variable target structures, they have been used for semantic representation schemes such as Abstract Meaning Representation (AMR) (Banarescu et al., 2013), Universal Conceptual Cognitive Annotation (UCCA) (Abend and Rappoport, 2013a), bilexical Semantic Dependencies (SDP) (Oepen et al., 2016), Universal Compositional Semantics (UDS) (White et al., 2016), and Parallel Meaning Bank (PMB) (Abzianidze et al., 2017). Graph-based semantic representation frameworks have been used in various NLP applications such as text summarisation (Liao et al., 2018; Zhang et al., 2020; Liu et al., 2018), question answering (Xu et al., 2021; Kapanipathi et al., 2020; Naseem et al., 2021), and machine translation (Song et al., 2019; Sulem et al., 2020; Nguyen et al., 2021), which have shown promising performance.

UCCA (Abend and Rappoport, 2013a) is a recently proposed semantic representation for depicting the “meaning” of a sentence within a multilayer framework in which each layer corresponds to a semantic module. The ultimate goal of UCCA is to provide a semantic representation that is applicable across languages and domains. It also allows rapid annotation by non-experts in linguistics. With all these benefits, UCCA representation has recently gained attention in the field and it has been already part of some shared tasks (SemEval 2019; (Herscovich et al., 2019), MRP 2019; (Oepen et al., 2019), MRP 2020; (Oepen et al., 2020)). According to the UCCA specification, the annotation framework is designed as cross-lingual. For example, the French corpus is extracted by implementing cross-lingual methods on an English-French parallel corpus obtained from *Twenty Thousand Leagues Under the Sea* by Jules Verne (Sulem et al., 2015). Apart

from French, there are also available UCCA-annotated datasets in English and German. However, there is not any available UCCA-annotated dataset for Turkish, which is a morphologically rich and low-resource language.

For Turkish, there is only one available annotated dataset based on graph-based AMR semantic representation (Azin and Eryiğit, 2019). The goal of this study is to build a UCCA-annotated dataset for Turkish. One of the main challenges in developing language models for morphologically rich languages with productive derivational morphology such as Hungarian, Finnish, or Turkish is the number of different word forms derived from a root. Here, we analyse the meaning of words without considering the morphological information. We leave morphological semantic annotation as a future goal. We initially annotated 50 sentences obtained from METU-Sabancı Turkish Treebank (Atalay et al., 2003; Oflazer et al., 2003). The annotation was performed in a semi-automatic pipeline in two steps.

1. In the first step, we train an external semantic parsing model on a dataset that is a combination of English, German, and French UCCA-annotated datasets to parse Turkish sentences using a zero-shot learning method, where the results are partially correct. 2. In the second step, we revised and corrected the annotations obtained from the semantic parsing model and defined new UCCA annotation rules in line with the Turkish syntax, if required. We also performed experiments on zero-shot and few-shot learning settings using the annotated dataset for training and evaluation purposes to better analyse the errors caused by the parsing model. This is the first UCCA-annotated dataset for Turkish and we introduce a set of UCCA annotation rules that are followed during the annotation along with our initial findings about the differences between the Turkish and other languages that have UCCA-annotated datasets available. The next step will be to extend the current Turkish UCCA annotation guideline that covers all types of sentence structures and grammatical phenomena, which will be based upon the differences in Turkish and English morphology and grammar.

The paper is organised as follows: Section 2 discusses the related work on UCCA parsing, Section 3 describes the UCCA representation, Section 4 explains the semantic parser model used in the first step of the semi-automatic annotation. Section 5 defines the rules that are defined while revising the output of the semantic parser. Section 6 presents the results obtained using the semantic parser model in zero-shot and few-shot settings on the new Turkish dataset, and finally Section 7 concludes the paper with some future goals.

2. Related Work

The approaches that are followed for UCCA-based semantic parsing can be categorised in 3 classes: transition-based, graph-based, end-to-end.

Transition-based approaches employ new features of

the UCCA framework such as discontinuity and reentrancy. The first parser model introduced for UCCA-based semantic representation is a transition-based model called TUPA parser. The TUPA parser defines new transition operations (e.g. `NODE`, `LEFT-EDGE`, `RIGHT-EDGE`, `LEFT-REMOTE`, `RIGHT-REMOTE`, `SWAP`) (Hershcovich et al., 2017) in addition to the standard operations (e.g. `SHIFT` and `REDUCE`). The second model introduced for UCCA parsing is based on the TUPA parser, which extends the TUPA parser for other graph-based semantic representation frameworks (i.e. UCCA, AMR, DM, and UD) (Hershcovich et al., 2018). With the shared tasks conducted at SemEval (Hershcovich et al., 2019) and MRP (Oepen et al., 2019; Oepen et al., 2020), new transition-based methods are introduced, and many of them are an extension of the TUPA parser (Lai et al., 2019; Arviv et al., 2020).

Graph-based approaches (Cao et al., 2019; Koreeda et al., 2019; Drostanova et al., 2019) aim to generate a graph with the highest score among all possible graphs in the graph space. The proposed methods are generally utilised for all graph-based frameworks. One of the graph-based approaches is to tackle the parsing task as a constituency parsing problem (Jiang et al., 2019; Li et al., 2019; Bölücü and Can, 2021). End-to-end neural models are usually complex systems based on deep learning models that parse the input by passing through intermediate layers (Chen et al., 2018; Wang et al., 2019a) that eventually generate the semantic parsing of the given input sequence.

3. Universal Conceptual Cognitive Annotation (UCCA)

UCCA (Abend and Rappoport, 2013a; Abend and Rappoport, 2013b) is a cross-lingual semantic annotation scheme influenced by the basic linguistic theory (Dixon, 2005; Dixon, 2010a; Dixon, 2010b; Dixon, 2012) and the cognitive linguistic theory (Langacker, 2008). It is a multi-layered framework, where each layer corresponds to a “module” of semantic distinctions of a sentence or a paragraph. The foundational layer of UCCA focuses on grammatically relevant information. It covers predicate-argument relations for predicates of grammatical categories (verbal, nominal, adjectival, and others). It is depicted by a directed acyclic graph (DAG) with leaves corresponding to tokens and multi-tokens in the text. The nodes of the graph are called units that can be either a terminal or multiple tokens considered together as a single entity according to some semantic or cognitive consideration. The edges of the graph indicate the role of a child in the relation (i.e. semantic categories) such as scene elements (Process (P), State (S), Participant (A), Adverbial (D)), elements of non-scene units (Center (C), Elaborator (E), Connector (N), Relator (R)), inter-scene relations (Parallel Scene (H), Linker (L), Ground (G)), and other roles (Function (F)).




Figure 1: The UCCA annotation graph of the Turkish sentence “Ama hiçbir şey söylemedim ki sizlere.” (in English, “*But I did not say anything to you.*”)

Initially, an English UCCA-annotated dataset was released (Abend and Rappoport, 2013a) that follows other UCCA-annotated datasets in several languages. For English, the *Wikipedia* corpus and the English-French parallel corpus obtained from the first five chapters of *Twenty Thousand Leagues Under the Sea* were annotated. The extension of the UCCA dataset into other languages has been implemented initially starting with the English-French parallel corpus, which is used to annotate the French dataset (Sulem et al., 2015). German dataset (Herscovich et al., 2019) consists of the entire book, *Twenty Thousand Leagues Under the Sea*. All of these datasets are annotated according to v2.1 of the UCCA guideline (Abend et al., 2020) and we followed the same version in our annotation¹.

An example of an UCCA annotation graph of a Turkish sentence is given in Figure 1. In the example, there is a **Linker** (L) “Ama” (meaning “*but*”) that links the event to the previous events (i.e. scenes) and a Scene “hiçbir şey söylemedim ki ben sizlere” (in English, “*I did not say anything to you*”), which corresponds to the main clause in the sentence. The Scene has a relation called **Process** (P) that corresponds to the main action in the scene: “söylemedim” (in English, “*I did not tell*”), three **Participants** (A) “hiçbir şey” (in English, “*anything*”), “ben” (in English, “*I*”) and “sizlere” (in English, “*to you*”) which are the arguments of the action and finally an **Adverbial** (D) “ki” that modifies the Scene.

4. Neural Semantic Parser for UCCA

We followed a semi-automatic annotation approach that involves two steps. First, we parsed the dataset using a neural UCCA semantic parser (Bölcü and Can, 2021) that is based on self-attention mechanism (Vaswani et al., 2017). The adopted neural semantic parser model follows a chart-based constituency parsing approach. The neural model is based on an encoder/decoder architecture. Self-attention layers are used within the encoder along with a multilayer perceptron (MLP) classifier with two fully-connected layers and Rectified Linear Unit (ReLU) non-linear activation function in the output layer. The final output of

¹bit.ly/semEval2019task1guidelines

the encoder gives the per-span scores where spans correspond to constituents in the constituency tree. The decoder adopts CYK (Cocke-Younger-Kasami) algorithm (Chappelier and Rajman, 1998) that generates the tree with the maximum score using the scores obtained from the encoder.

Zero-shot learning allows learning without using any training data on a particular domain or language by transferring information from another domain or language. By means of the large pre-trained models made available especially using transformer networks (Devlin et al., 2018; Sanh et al., 2019), the popularity of zero-shot learning has increased due to its outstanding success in various NLP tasks such as dependency parsing (Wang et al., 2019b; Tran and Bisazza, 2019) and text classification (Pushp and Srivastava, 2017; Chalkidis et al., 2020). Since there is not any UCCA-annotated dataset available for Turkish, we utilised the encoder/decoder model with zero-shot learning by transferring information from the UCCA-datasets available in other languages. We initially trained the parser on merged datasets (in English, German, and French) and then we parsed the Turkish UCCA dataset using the trained model. Once the partial parsing results were obtained from zero-shot learning, we manually revised the Turkish parsing results by concurrently defining our Turkish-specific rule set for UCCA annotation in Turkish. Eventually, we obtained 50 Turkish sentences that are annotated using UCCA representation. Example outputs of the parser are shown in Figure 2 and 3. As seen, most of the relations and their labels are identified correctly apart from the adverbial (“ki”) that is confused with a Relator² in Figure 2, and the participant and ground (‘oğlum’, meaning “my son”) that is confused with a static scene in Figure 3.

Data annotation might be a burden particularly when started from zero-resource. However, beginning with a semi-automatic annotation with only a small number of annotated sentences does not only speed the annotation process, but also helps understanding the general discrepancies between the annotated sentences in different languages. Thus, we designed more experiments using the annotated Turkish dataset as part of the training set for few-shot learning.

5. A UCCA-Annotated Dataset for Turkish

We annotated 50 sentences obtained from METU-Sabancı Turkish Treebank (Atalay et al., 2003; Oflazer et al., 2003). Here, we explain the annotation process, annotation rules that are specific to Turkish, and the statistical distribution of the labels in the dataset.

5.1. Turkish UCCA Annotation Rules

Once we analysed the output of the semantic parsing model manually, we either applied the rules already defined in UCCA guideline (Abend et al., 2020) or de-

²This is further explained in Section 5




Figure 2: The output of the parsing for sentence “Ama hiçbir şey söylemedim ki sizlere.” (in English, “*But I did not say anything to you.*”)





Figure 3: The output of the parsing for sentence “Kurtulmak istiyor musun oğlum? diye sordu Şakir.” (in English, “*Do you want to be saved, son? asked Şakir.*”)

defined new annotation rules for syntactic components in Turkish, which are not covered by any of the available rules in the official UCCA guideline. We do not re-describe the existing UCCA annotation rules here, but we only describe the new UCCA annotation rules with example sentences in Turkish that have been all encountered during the annotation of the dataset³:

- **Pronoun-dropping (Göçmen et al., 1995):** Pronoun subjects are usually omitted in Turkish, since it is a pro-drop language. In UCCA annotation, omitted pronoun subjects are identified with the label *A-IMPLICIT*:


Example 5.1

(Ben)_{A-IMPLICIT} özgür kalmak istemiyorum (in English, “*I don’t want to stay free*”)



Example 5.2


(O)_{A-IMPLICIT} soluk soluğaydı (in English, “*S/he was out of breath*”)



- **Genitive case:** To express possession in Turkish, the genitive suffix is added to the possessor and the possessive suffix is added to the possessed noun. Pronominal possessors of possessive nouns are also usually omitted since possessive suffix already bears the possession meaning. Omitted pronominal possessors of possessive nouns are identified with the label *E-IMPLICIT*:

Example 5.3


(Onun)_{E-IMPLICIT} gözleri kor gibi yanıyordu (in English, “*Her/his eyes were burning like embers*”)



- **Postpositions:** Unlike English, Turkish has no prepositions (Göksel and Kerslake, 2004). While some English prepositions correspond to the case suffixes in English, other prepositions are formed by postpositions that follow their complement phrases. Such postpositions are identified with the label *Relator (R)*:


Example 5.4

Göğsü körük gibi_R inip kalkıyordu (in English, “*Her/his chest was going up and down like a bellows*”)



Example 5.5


Şimdi ikimiz yan yana koşar adım gecenin içinde_R ilerliyorduk (in English, “*Now the two of us were running side by side stepping forward through the night*”)



³Please note that punctuation is not specified in the example sentences for simplicity purposes.

Example 5.6


*Nasıl bir kadın o diye_R sordum (in English, “I asked (that) what kind of a woman she is”)*⁴



- **Negation** In Turkish, negation is formed by adding a suffix to the end of the verb. However, “değil” (in English, “not”) is used to negate a nominal sentence. The negation word is marked as an Adverbial (D) as defined in the English guideline since it does not refer to a participant or a relation:

Example 5.7

Onlar önemli değil_D ki (in English, “They just don’t matter”)




- **Clitics:** Clitics are free morphemes in Turkish (e.g. “mi”, “ki”) that are meaning-bearing units, but their meaning may change from one context to another. Therefore, the meaning of a clitic can only be determined within a particular context:

1. “mi”⁵ can be used in 3 different meanings depending on its context:

- (a) Yes/No condition: It is identified with the label Function (F) since it does not refer to a participant or a relation:

Example 5.8

Nereye gittiğimi biliyor musunuz_F (in English, “Do you know where I’m going”)



- (b) Adverbial clause marker: It is labeled with Linker (L) that also corresponds to the same category in the UCCA


⁴Auxiliary verb “is” does not correspond to any word in Turkish.

⁵The clitic also involves the other forms of “mi”, such as “mı”, “mısın”, “mısınız” etc depending on the vowel harmony and the person type.

guideline.⁶

Example 5.9


Pazara gittin mi_L bütün ihtiyaçlarını alırsın (in English, “When you go to market you buy all your needs”)



- (c) Intensifier in doubled forms: We combine the doubled forms for a more concise annotation. (e.g. sıcak_mı_sıcak)⁶

Example 5.10

Sıcak_mı_sıcak bir çay verdiler (in English, “They gave me a very hot tea”)




2. “ki” can be used in 4 different meanings depending on its context:

- (a) Subordinator connecting: Since it is part of a larger construction that connects the subordinator to the main Scene, it is labelled with Relator (R), as defined in the English guideline.

Example 5.11


Anlıyorum ki_R o gelmeyecek (in English, “I understand that s/he will not come”)



- (b) Repudiative discourse connective: It means “just”, and therefore it is identified with the label Adverbial (D)⁶.

Example 5.12

Onlar önemli değil ki_D (in English, “They just don’t matter”)




⁶During the annotation, we did not come across any example of this type of marker. Therefore, the example does not exist in the annotated dataset.

- (c) Exclamations: It is identified with the label Ground (G) since it expresses the speaker’s attitude towards the event. It usually appears at the end of a sentence and usually used along with “*o kadar (that much)*” or “*öyle(sine) (so)*”. The exclamations do not correspond to a participant or relation⁶:

Example 5.13


Onun yemekleri o kadar lezzetli olur ki_G
(in English, *Her/his food is so delicious*)⁷



- (d) Relative clause marker: A relative clause modifies a noun and relative clause marker connects the clause to the top-level clause. It is identified with the label Relator (R)⁶ as defined in the English guideline.

Example 5.14

Ahmet ki_R ekşiyi sevmez o bile beğendi
(in English, *Even Ahmet who doesn't like sour liked the food*)



5.2. Inter-annotator Agreement

We employed 2 annotators who are native speakers of Turkish and both from a computational linguistics background. The annotators were initially trained for the UCCA annotation based on the official UCCA guideline (Abend and Rappoport, 2013a). They annotated the sentences independently, and then all annotated sentences were compared with each other at the end. The percentage of the agreement between the two annotators during the annotation is 90.69%⁸. Using Cohen’s Kappa (Cohen, 1960) (*100), we calculated the Inter-annotator Agreement (IAA) for the UCCA annotation to be 89.05. In case of disagreement, the sentence was labeled following a discussion, and if required, new rules were defined for a particular syntactic rule.

The general disagreement that recurs in the training procedure is mainly about the annotation of the clitics.

⁷Clitics “**ki**” does not correspond to any word in English.

⁸There was disagreement in 38 out of 408 tokens in 50 sentences between the two annotators during annotation.

Since the morphology is out of scope in the current version of the annotation, we only consider clitics that are seen as a free morpheme. Consider the example “*Onlar önemli değil ki*” (in English, “*They just don’t matter*”). The clitic “*ki*” gives repudiative meaning to the main Scene (*Onlar_A önemli_S değil_D ki_D*). We refer to the Turkish grammar rules defined by (Göksel and Kerslake, 2004) to identify the clitics in the dataset.

5.3. Comparison of the Parses in Automatic and Manual Annotation

We analyse the common errors of the semantic parser model which were manually corrected once the automatic parsing was performed. Two example sentences that are parsed by the semantic parser model are given in Figure 4 and 5 along with their gold standard annotations. While in Figure 4, we added only the IMPLICIT edge, the Parallel Scene (H) and Relator (R) were not correctly labeled by the model in the second sentence in Figure 5.

While correcting the parses that are obtained from the semantic parser model, we did not make any additional corrections to short sentences (having less than 5 words). The labels of the terminal nodes were also mostly correct. We corrected most of the annotations for the Parallel Scene (H), which also affect the entire annotation of the sentence.

5.4. Annotation Statistics


The overall proportions of the UCCA edges and labels in the final annotation of the dataset along with the English datasets are given in Table 1⁹. In the Turkish dataset, the number of Participants (A) is the highest and the frequency of Adverbial (D) label is higher than that of Elaborator (E) and Center (C). We have not come across any Connectors (N) in the dataset. The distribution of the other labels is similar in the English and Turkish datasets, with the exception of the Elaborator (E). The reason for the low frequency of Elaborator (E) is the short length of the sentences in the Turkish dataset.

6. Experiments and Results


We used the annotated dataset for training and testing UCCA-based semantic parsing on Turkish. For this purpose, we conducted experiments with zero-shot and few-shot learning to understand the impact of the size of the training set for UCCA parsing.

We used the UCCA-annotated datasets provided by SemEval 2019 (Hershcovich et al., 2019) in English, German, and French for training the aforementioned neural semantic parser model. The details of the datasets are given in Table 2. We used the official evaluation metrics used in SemEval 2019, that are precision, recall, and the F_1 score in all experiments.

⁹The dataset is publicly available at <https://github.com/necvabolucu/semantic-dataset>.




(a) The output of the semantic parsing model




(b) The correct annotation of the sentence

Figure 4: The semantic parse tree obtained from the semantic parsing model and the gold standard annotation obtained from the manual annotation of the sentence, *Yerinden kalkmıştı.* (in English, “*S/he had gotten up.*”)



(a) The output of the semantic parsing model



(b) The correct annotation of the sentence

Figure 5: The semantic parse tree obtained from the semantic parsing model and the gold standard annotation obtained from the manual annotation of the sentence, *Kurtulmak istiyor musun oğlum? diye sordu Şakir.* (in English, “*Do you want to be saved, son? asked Shakir.*”)

	Turkish	En-Wiki	En-20K
# edges	407	208,937	16,803
% primary	96.57	97.40	96.79
% remote	3.43	2.60	3.21
% Participant (A)	28.19	17.17	18.1
% Center (C)	8.09	18.74	16.31
% Adverbial (D)	8.82	3.65	5.25
% Elaborator (E)	4.41	18.98	18.06
% Function (F)	3.19	3.38	3.58
% Ground (G)	0.98	0.03	0.56
% Parallel Scene (H)	7.11	6.02	6.3
% Linker (L)	1.23	2.19	2.66
% Connector (N)	0.00	1.26	0.93
% Process (P)	15.44	7.1	7.51
% Relator (R)	2.70	8.58	8.09
% State (S)	4.17	1.62	2.1
% Punctuation (U)	15.69	11.28	10.55

Table 1: Statistics of the UCCA datasets in Turkish and English. Proportions of the edges and labels of each dataset are given.

In zero shot learning, we trained the semantic parser model on the combined datasets in English, German, and French. The trained model is used to parse the 50 sentences in Turkish, which is used as the test set. In

few shot learning, we performed cross validation with 5-fold by adding 40 sentences to the combined training set and using 10 sentences only for testing. We report the average scores obtained from each fold. The results show that few-shot learning improves the results substantially. In particular, remote edges cannot be learned during zero-shot learning, but they are learned during few-shot learning even with a small number of annotated sentences.

The experimental results obtained from both zero-shot and few shot learning are given in Table 3. The results show that using even a small size of training set significantly improves the accuracy of the parser on Turkish. The results obtained from few-shot learning according to different sentence lengths are given in Table 4. Since the sentences from the METU dataset are shorter than the sentences in English, German and French datasets, the model performs well at parsing shorter sentences.

7. Conclusion and Future Work

In this study, we started annotating the first Turkish UCCA dataset with the first 50 sentences obtained from the METU-Sabancı Turkish Treebank. While we adopted the official UCCA guideline particularly defined for English, we either utilised the current specifications by describing how each linguistic construction should be annotated to ensure consistent annotation or

	English-Wiki	English-20K	German-20K	French-20K
Train	4,113	0	5,211	15
Validation	514	0	651	238
Test	515	492	652	239

Table 2: The number of sentences in each UCCA-annotated dataset provided by SemEval 2019 (Hershcovich et al., 2019)

		Primary			Remote			Average		
		P	R	F_1	P	R	F_1	P	R	F_1
Zero-shot	Labeled	73.55	80.25	76.76	0.00	0.00	0.00	73.04	77.89	75.39
	Unlabeled	76.80	83.80	80.15	0.00	0.00	0.00	76.80	81.33	79.00
Few-shot	Labeled	78.72	84.30	81.42	30.00	25.00	27.28	78.75	83.78	81.11
	Unlabeled	87.71	93.92	90.71	50.00	41.67	45.45	87.53	93.12	90.24

Table 3: Precision (P), Recall (R) and F-measure (F_1) results obtained from zero-shot and few-shot learning on the Turkish UCCA dataset

		Labeled			Unlabeled		
Sent. Len.	# of sentences	Primary	Remote	All	Primary	Remote	All
≤ 5	30	87.73	0.00	86.93	93.25	66.67	93.00
≤ 10	19	80.53	0.30	75.20	89.38	50.00	85.37
≤ 20	1	68.42	-	66.67	84.21	-	82.05

Table 4: F_1 Results obtained from few-shot learning according to their sentence length

we defined new rules that would cover syntactic rules that are peculiar to the Turkish language. Our annotation approach is semi-automatic, where we adopted a semantic parser model using zero-shot learning by training on other languages, and testing on Turkish to have partially correct UCCA representations for Turkish. Then we analysed the discrepancies between the annotated sentences and the English guideline to define new rules compatible with the Turkish grammar.

We also performed experiments with zero-shot and few shot learning using the annotated Turkish dataset. For this purpose, we again used the same neural semantic parser model. The results show that even a small amount of training data improves the accuracy of the semantic parsing substantially in few-shot learning.

Our future goal is to extend the dataset using a similar semi-automatic approach and create a more comprehensive Turkish UCCA annotation guideline for a larger Turkish UCCA-annotated dataset.

8. Bibliographical References

- Abend, O. and Rappoport, A. (2013a). UCCA: A semantics-based grammatical annotation scheme. In *Proceedings of the 10th International Conference on Computational Semantics (IWCS 2013)–Long Papers*, pages 1–12.
- Abend, O. and Rappoport, A. (2013b). Universal conceptual cognitive annotation (UCCA). In *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 228–238.
- Abend, O., Schneider, N., Dvir, D., Prange, J., and Rappoport, A. (2020). UCCA’s Foundational Layer: Annotation Guidelines v2. 1. *arXiv preprint arXiv:2012.15810*.
- Abzianidze, L., Bjerva, J., Evang, K., Haagsma, H., van Noord, R., Ludmann, P., Nguyen, D.-D., and Bos, J. (2017). The Parallel Meaning Bank: Towards a Multilingual Corpus of Translations Annotated with Compositional Meaning Representations. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pages 242–247.
- Arviv, O., Cui, R., and Hershcovich, D. (2020). HUI-KU at MRP 2020: Two Transition-based Neural Parsers. In *Proceedings of the CoNLL 2020 Shared Task: Cross-Framework Meaning Representation Parsing*, pages 73–82.
- Atalay, N. B., Oflazer, K., and Say, B. (2003). The annotation process in the Turkish treebank. In *Proceedings of 4th International Workshop on Linguistically Interpreted Corpora (LINC-03) at EACL 2003*.
- Azin, Z. and Eryigit, G. (2019). Towards Turkish Abstract Meaning Representation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics: Student Research Workshop*, pages 43–47.
- Banarescu, L., Bonial, C., Cai, S., Georgescu, M.,

- Griffitt, K., Hermjakob, U., Knight, K., Koehn, P., Palmer, M., and Schneider, N. (2013). Abstract meaning representation for sembanking. In *Proceedings of the 7th linguistic annotation workshop and interoperability with discourse*, pages 178–186.
- Bölicü, N. and Can, B. (2021). Self-Attentive Constituency Parsing for UCCA-based Semantic Parsing. *arXiv preprint arXiv:2110.00621*.
- Cao, J., Zhang, Y., Youssef, A., and Srikumar, V. (2019). Amazon at MRP 2019: Parsing Meaning Representations with Lexical and Phrasal Anchoring. In *Proceedings of the Shared Task on Cross-Framework Meaning Representation Parsing at the 2019 Conference on Natural Language Learning*, pages 138–148.
- Chalkidis, I., Fergadiotis, M., Kotitsas, S., Malakasiotis, P., Aletras, N., and Androutsopoulos, I. (2020). An empirical study on large-scale multi-label text classification including few and zero-shot labels. *arXiv preprint arXiv:2010.01653*.
- Chappelier, J.-C. and Rajman, M. (1998). A generalized CYK algorithm for parsing stochastic CFG. In *Proc. of 1st Workshop on Tabulation in Parsing and Deduction (TAPD'98)*, number CONF, pages 133–137.
- Chen, B., Sun, L., and Han, X. (2018). Sequence-to-Action: End-to-End Semantic Graph Generation for Semantic Parsing. *arXiv preprint arXiv:1809.00773*.
- Cohen, J. (1960). A coefficient of agreement for nominal scales. *Educational and psychological measurement*, 20(1):37–46.
- Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2018). BERT: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.
- Dixon, R. M. (2005). *A semantic approach to English grammar*. Oxford University Press.
- Dixon, R. M. (2010a). *Basic linguistic theory volume 1: Methodology*, volume 1. Oxford University Press.
- Dixon, R. M. (2010b). *Basic linguistic theory volume 2: Grammatical topics*, volume 2. Oxford University Press on Demand.
- Dixon, R. M. (2012). *Basic linguistic theory. vol. 3: Further grammatical topics*.
- Droganova, K., Kutuzov, A., Mediantkin, N., and Zeman, D. (2019). ÚFAL-Oslo at MRP 2019: Garage Sale Semantic Parsing. In *Proceedings of the Shared Task on Cross-Framework Meaning Representation Parsing at the 2019 Conference on Natural Language Learning*, pages 158–165.
- Göksel, A. and Kerslake, C. (2004). *Turkish: A comprehensive grammar*. Routledge.
- Göçmen, E., Sehitoglu, O., and Bozsahin, C. (1995). An outline of Turkish syntax.
- Hershcovich, D., Abend, O., and Rappoport, A. (2017). A Transition-Based Directed Acyclic Graph Parser for UCCA. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1127–1138.
- Hershcovich, D., Abend, O., and Rappoport, A. (2018). Multitask Parsing Across Semantic Representations. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 373–385.
- Hershcovich, D., Aizenbud, Z., Choshen, L., Sulem, E., Rappoport, A., and Abend, O. (2019). SemEval-2019 Task 1: Cross-lingual Semantic Parsing with UCCA. In *Proceedings of the 13th International Workshop on Semantic Evaluation*, pages 1–10.
- Jansen, S. (2017). Word and phrase translation with word2vec. *arXiv preprint arXiv:1705.03127*.
- Jiang, W., Li, Z., Zhang, Y., and Zhang, M. (2019). HLT@SUDA at SemEval 2019 Task 1: UCCA Graph Parsing as Constituent Tree Parsing. *arXiv preprint arXiv:1903.04153*.
- Kapanipathi, P., Abdelaziz, I., Ravishankar, S., Roukos, S., Gray, A., Astudillo, R., Chang, M., Cornelio, C., Dana, S., Fokoue, A., et al. (2020). Leveraging Abstract Meaning Representation for Knowledge Base Question Answering. *arXiv preprint arXiv:2012.01707*.
- Koreeda, Y., Morio, G., Morishita, T., Ozaki, H., and Yanai, K. (2019). Hitachi at MRP 2019: Unified Encoder-to-BiAffine Network for Cross-Framework Meaning Representation Parsing. In *Proceedings of the Shared Task on Cross-Framework Meaning Representation Parsing at the 2019 Conference on Natural Language Learning*, pages 114–126.
- Lai, S., Lo, C. H., Leung, K. S., and Leung, Y. (2019). CHUK at MRP 2019: Transition-Based Parser with Cross-Framework Variable-Arity Resolve Action. In *Proceedings of the Shared Task on Cross-Framework Meaning Representation Parsing at the 2019 Conference on Natural Language Learning*, pages 104–113.
- Langacker, R. (2008). *Cognitive Grammar: A Basic Introduction*. Oxford: Oxford University Press.
- Li, L., Xiao, L., Jin, W., Zhu, H., and Yang, G. (2018). Text Classification Based on Word2vec and Convolutional Neural Network. In *International Conference on Neural Information Processing*, pages 450–460. Springer.
- Li, Z., Zhao, H., Zhang, Z., Wang, R., Utiyama, M., and Sumita, E. (2019). SJTU-NICT at MRP 2019: Multi-task Learning for End-to-End Uniform Semantic Graph Parsing. In *Proceedings of the Shared Task on Cross-Framework Meaning Representation Parsing at the 2019 Conference on Natural Language Learning*, pages 45–54.
- Liao, K., Lebanoff, L., and Liu, F. (2018). Abstract meaning representation for multi-document summarization. *arXiv preprint arXiv:1806.05655*.
- Liu, F., Flanagan, J., Thomson, S., Sadeh, N., and

- Smith, N. A. (2018). Toward abstractive summarization using semantic representations. *arXiv preprint arXiv:1805.10399*.
- Mikolov, T., Sutskever, I., Chen, K., Corrado, G. S., and Dean, J. (2013). Distributed Representations of Words and Phrases and Their Compositionality. In *Advances in neural information processing systems*, pages 3111–3119.
- Naseem, T., Ravishankar, S., Mihindukulasooriya, N., Abdelaziz, I., Lee, Y.-S., Kapanipathi, P., Roukos, S., Gliozzo, A., and Gray, A. (2021). A semantics-aware transformer model of relation linking for knowledge base question answering. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pages 256–262.
- Nguyen, L. H., Pham, V. H., and Dinh, D. (2021). Improving Neural Machine Translation with AMR Semantic Graphs. *Mathematical Problems in Engineering*, 2021.
- Oepen, S., Kuhlmann, M., Miyao, Y., Zeman, D., Cinková, S., Flickinger, D., Hajic, J., Ivanova, A., and Uresova, Z. (2016). Towards comparability of linguistic graph banks for semantic parsing. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC’16)*, pages 3991–3995.
- Oepen, S., Abend, O., Hajic, J., Hershovich, D., Kuhlmann, M., O’Gorman, T., Xue, N., Chun, J., Straka, M., and Urešová, Z. (2019). MRP 2019: Cross-framework Meaning Representation Parsing. In *Proceedings of the Shared Task on Cross-Framework Meaning Representation Parsing at the 2019 Conference on Natural Language Learning*, pages 1–27.
- Oepen, S., Abend, O., Abzianidze, L., Bos, J., Hajic, J., Hershovich, D., Li, B., O’Gorman, T., Xue, N., and Zeman, D. (2020). MRP 2020: The Second Shared Task on Cross-Framework and Cross-Lingual Meaning Representation Parsing. In *Proceedings of the CoNLL 2020 Shared Task: Cross-Framework Meaning Representation Parsing*, pages 1–22.
- Oflazer, K., Say, B., Hakkani-Tür, D. Z., and Tür, G. (2003). Building a Turkish treebank. In *Treebanks*, pages 261–277. Springer.
- Pushp, P. K. and Srivastava, M. M. (2017). Train once, test anywhere: Zero-shot learning for text classification. *arXiv preprint arXiv:1712.05972*.
- Qi, Y., Sachan, D. S., Felix, M., Padmanabhan, S. J., and Neubig, G. (2018). When and why are pre-trained word embeddings useful for neural machine translation? *arXiv preprint arXiv:1804.06323*.
- Sanh, V., Debut, L., Chaumond, J., and Wolf, T. (2019). DistilBERT, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*.
- Song, L., Gildea, D., Zhang, Y., Wang, Z., and Su, J. (2019). Semantic neural machine translation using AMR. *Transactions of the Association for Computational Linguistics*, 7:19–31.
- Sulem, E., Abend, O., and Rappoport, A. (2015). Conceptual Annotations Preserve Structure Across Translations: A French-English Case Study. In *Proceedings of the 1st Workshop on Semantics-Driven Statistical Machine Translation (S2MT 2015)*, pages 11–22.
- Sulem, E., Abend, O., and Rappoport, A. (2020). Semantic structural decomposition for neural machine translation. In *Proceedings of the Ninth Joint Conference on Lexical and Computational Semantics*, pages 50–57.
- Tran, K. M. and Bisazza, A. (2019). Zero-shot Dependency Parsing with Pre-trained Multilingual Sentence Representations. In *Proceedings of the 2nd Workshop on Deep Learning Approaches for Low-Resource NLP (DeepLo 2019)*, pages 281–288.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.
- Vigliocco, G. and Vinson, D. P. (2007). Semantic representation. *The Oxford handbook of psycholinguistics*, pages 195–215.
- Wang, X., Huang, J., and Tu, K. (2019a). Second-order semantic dependency parsing with end-to-end neural networks. *arXiv preprint arXiv:1906.07880*.
- Wang, Y., Che, W., Guo, J., Liu, Y., and Liu, T. (2019b). Cross-Lingual BERT Transformation for Zero-Shot Dependency Parsing. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5721–5727.
- Wensen, L., Zewen, C., Jun, W., and Xiaoyi, W. (2016). Short text classification based on Wikipedia and Word2vec. In *2016 2nd IEEE International Conference on Computer and Communications (ICCC)*, pages 1195–1200. IEEE.
- White, A. S., Reisinger, D., Sakaguchi, K., Vieira, T., Zhang, S., Rudinger, R., Rawlins, K., and Van Durme, B. (2016). Universal decompositional semantics on universal dependencies. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 1713–1723.
- Xu, W., Zhang, H., Cai, D., and Lam, W. (2021). Dynamic Semantic Graph Construction and Reasoning for Explainable Multi-hop Science Question Answering. *arXiv preprint arXiv:2105.11776*.
- Yang, Z., Dai, Z., Yang, Y., Carbonell, J., Salakhutdinov, R. R., and Le, Q. V. (2019). Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in neural information processing systems*, 32.
- Zhang, X., Zhao, H., Zhang, K., and Zhang, Y. (2020).

SEMA: Text Simplification Evaluation through Semantic Alignment. In *Proceedings of the 6th Workshop on Natural Language Processing Techniques for Educational Applications*, pages 121–128.