

MulZDG: Multilingual Code-Switching Framework for Zero-shot Dialogue Generation

Yongkang Liu, Shi Feng, Daling Wang*, Yifei Zhang

Northeastern University, Shenyang, China

misonsky@163.com

{fengshi, wangdaling, zhangyifei}@cse.neu.edu.cn

Abstract

Building dialogue generation systems in a zero-shot scenario remains a huge challenge, since the typical zero-shot approaches in dialogue generation rely heavily on large-scale pre-trained language generation models such as GPT-3 and T5. The research on zero-shot dialogue generation without cumbersome language models is limited due to lacking corresponding parallel dialogue corpora. In this paper, we propose a simple but effective **Multilingual learning framework for Zero-shot Dialogue Generation** (dubbed as MulZDG) that can effectively transfer knowledge from an English corpus with large-scale training samples to a non-English corpus with zero samples. Besides, MulZDG can be viewed as a multilingual data augmentation method to improve the performance of the resource-rich language. First, we construct multilingual code-switching dialogue datasets via translation utterances randomly selected from monolingual English datasets. Then we employ MulZDG to train a unified multilingual dialogue model based on the code-switching datasets. The MulZDG can conduct implicit semantic alignment between different languages. Experiments on DailyDialog and DSTC7 datasets demonstrate that MulZDG not only achieve competitive performance under zero-shot case compared to training with sufficient examples but also greatly improve the performance of the source language.

1 Introduction

The success of neural models and the emergence of large-scale dialogue datasets have greatly advanced the research of dialog generation (Serban et al., 2016, 2017; Huang et al., 2020; Meng et al., 2020). The open-domain dialogue systems aim to generate more informative and fluent responses (Ke et al., 2018; Zhang et al., 2020b; Bao et al., 2020;

Meng et al., 2021), which are widely used in various applications such as emotional companionship, mental health support, and social chatbots.




Figure 1: Multilingual semantic alignment map in zero-shot case. One color represents one language. English is the source language and other languages are target languages. u_i represents the i -th utterance in the conversation history and r represents the responses. Black arrows represent translating utterances from English into other languages. Solid brown lines represent implicit semantic alignments between different languages.

Although achieving promising performance, most existing dialogue generation systems (Zhang et al., 2020b; Bao et al., 2020; Li et al., 2020; Floridi and Chiriatti, 2020) rely on a considerable amount of data resource, such as DialoGPT (Zhang et al., 2020b). In practice, the dialogue corpus for many languages is unavailable, which limits the usefulness of dialogue systems for low-resource or even zero-resource languages. Hence it is important to design approaches that can effectively transfer knowledge from the source language with sufficient resources to a target language with zero training samples.

The pre-trained language models have been proved to be very effective in dialogue generations including zero-shot scenarios. Most existing zero-shot dialogue generation approaches usually directly employ large-scale pre-trained generative language models such as GPT-3 (Brown et al., 2020), T5 (Raffel et al., 2020), or conduct secondary pre-training on target language based

Corresponding author

on language models (Ebrahimi and Kann, 2021; Kim et al., 2021). Although these methods can handle the issue of zero-shot generation, the cost of pre-training is unaffordable.

In the similar task of NMT (neural machine translation), zero-shot generation methods are mainly introducing one additional language between source and target language (Johnson et al., 2017; Zheng et al., 2017; Artetxe et al., 2018; Cheng, 2019; Liu et al., 2020a), which can achieve indirect semantic mapping between the source and target language through the additional intermediate language. The nature of translation is the semantic mapping between source and target languages while there is no similar semantic mapping between dialogue history and response. Therefore, directly transferring the zero-shot approaches in NMT to the dialogue generation task is infeasible.

The zero-shot multilingual understanding tasks usually employ code-switching approach to achieve semantic alignment between different languages (Liu et al., 2020b; Chapuis et al., 2021; Qin et al., 2021). The way of code-switching can conduct implicit semantic alignment without relying on parallel corpus pairs. Inspired by these studies, we employ the code-switching method to transfer the knowledge of dialogue history in English to other target languages which have no training examples. We follow previous work (Chapuis et al., 2021) on multilingual representation to employ code-switching at the utterance level, although code-switching at the word or span level is more common (Banerjee et al., 2018; Bawa et al., 2020; Dođruöz et al., 2021).

Based on the code-switching method, we propose a simple but effective **Multilingual learning framework for Zero-shot Dialogue Generation** (dubbed as MulZDG) that can effectively transfer knowledge from English corpus with large-scale training samples to non-English corpus with zero samples. Specifically, we first construct code-switch languages using the NMT system and bilingual dictionary (Pan et al., 2021). As shown by the black arrows in Figure 1, we randomly select utterances from dialogue history to translate into other target languages. For each target language, we construct code-switching corpus containing source and target languages, respectively. Then we employ MulZDG based on an encoder-decoder structure to train a unified multilingual dialogue generation system, which can be applied in the source language

and other target languages with no training samples. MulZDG with a multi-task structure can generate responses with different languages according to specific input prompts. MulZDG can conduct implicit semantic alignments through task sharing mechanism between different languages, as shown by solid brown lines in Figure 1. To summarize, we make the following contributions:

- We propose a simple but effective multilingual framework, MulZDG, which can effectively transfer the knowledge from the source language with large-scale training samples to target languages with zero samples.
- We present a data augmentation method for multilingual code-switching, which can enhance the performance of source language.
- We construct multilingual code-switching dialogue datasets from English dialogue datasets DailyDialog and DSTC7, and release the multilingual versions datasets¹.

2 RELATED WORK

2.1 Dialogue Generation

Dialogue generation systems aim to produce informative and fluent responses and have attracted great attention in academia. Early studies usually adopt the methods of NMT based on an Encoder-Decoder network to generate responses (Sordani et al., 2015; Serban et al., 2016). However, these methods often generate dull and generic responses. To tackle this problem, memory mechanism (Wu et al., 2018; Zhang et al., 2020a; Tian et al., 2020) and attention mechanism (Zhang et al., 2019) are introduced into dialogue modeling successively. Although many approaches have been proposed, there are still remarkable gaps between responses generated by neural models and those from humans (Holtzman et al., 2019). Large-scale pre-trained generative models (Zhang et al., 2021; Ling et al., 2021; Wang et al., 2020) have greatly facilitated the development of dialogue generation task. Although achieving promising performance, these methods rely on a large number of training examples, which greatly limits the usability of dialogue systems. In this paper, we propose a multilingual framework that can work in zero-shot case.

2.2 Zero-shot Learning

Zero-shot Learning for dialogue generation tasks refers to building a dialogue generation sys-

¹<https://github.com/misonosky/MultilingualDatasets>

tem without available training samples (Floridi and Chiriatti, 2020). Most existing zero-shot methods of dialogue generation rely on large-scale pre-trained generative models (Lewis et al., 2020; Zhang et al., 2020b; Floridi and Chiriatti, 2020), such as GPT-3 (Floridi and Chiriatti, 2020). These methods require huge computing resources, which hinders the usability of dialogue systems. On similar machine translation tasks, zero-shot methods mainly include triangular and multilingual NMT systems. The triangular NMT systems (Zheng et al., 2017; Cheng, 2019) build a triangular translation case by adding an intermediate language and multilingual systems (Johnson et al., 2017; Liu et al., 2020a) mix multiple different language pairs to achieve semantic alignment between different languages under zero-shot case by building implicit triangular systems. The nature of these methods is the semantic mapping between different languages, which is consistent with the translation task. However, there is no similar semantic mapping between dialogue history and response. In this paper, we propose a simple but effective multilingual dialogue generation framework based on code-switching languages.

3 METHODOLOGY

3.1 Problem Formalization

Given a source language (S), the goal is to build a unified dialogue generation system based on the source language that can be applied to target languages (T). In this paper, the source language S is English. The T include: Zh (Chinese), De (German), Ru (Russian), Es (Spanish), Fr (French) and It (Italian). An instance in dialogue dataset can be represented as (C, R) where $C = \{u_1, u_2, \dots, u_n\}$ with n utterance represents the context of dialogue. u_i represents the i -th utterance. And R represents the corresponding response. Based on the S , we automatically build code-switching languages that include T through random translations. The construction process of code-switching languages are shown in Algorithm 1, where $D_T = \{D_{en_{zh}}, D_{en_{de}}, D_{en_{ru}}, D_{en_{es}}, D_{en_{fr}}, D_{en_{it}}\}$. The $D_{en_{tar}}$ represents code-switching languages composed of English and tar .

3.2 Multi-task MulZDG Framework

As shown in Figure 2, MulZDG mainly contains three layers: (i) Embedding Layer; (ii) Encoder Layer; (iii) Decoder Layer. The embedding layer

Algorithm 1: Code-Switching Languages.

Input: Corpus of S : D_S ; The target language set T ; Bilingual Dictionary: Dic ;

Output: Code-switching languages: D_T .

Initialize $D_T = \emptyset$;

foreach (C, R) in D_S **do**

 random sample utterances:

$U \sim P(C, R)$;

foreach target language t_i in T **do**

 Replace tokens for each utterance in

U by dictionary $Dic(S \rightarrow t_i)$: \tilde{U} ;

 Translate \tilde{U} by NMT system: \hat{U} ;

 Add updated (C, R) by \hat{U} to D_T ;

is responsible for mapping each word in D_T to a vector space using a pre-trained Glove (Pennington et al., 2014) embedding model. The encoder layer is responsible for capturing the semantic representation of the dialogue context. And the decoder layer is responsible for generating the probability distribution of response for the dialogue context. The decoder in MulZDG can generate responses in different languages through different prompt tokens. The code-switching languages in D_T share the same encoder and decoder, which can conduct semantic alignment between different languages through task sharing mechanism. In the training phase, we employ code-switching languages to train MulZDG. In the testing phase, MulZDG takes monolingual dialogue samples as input and generates responses in the corresponding target language.

MulZDG is a multi-task framework, which supports networks with RNN and transformer as the backbone. The inputs of frameworks are utterance-level code-switching languages. Different inputs in D_T share the same encoder and decoder. The encoder can be hierarchical or non-hierarchical structures. The framework with a non-hierarchical encoder is just like the seq2seq architecture (Sutskever et al., 2014) which consists of an encoder RNN and a decoder RNN. The framework with a hierarchical encoder is just like HRED (Serban et al., 2016) which consists of a hierarchical encoder and a decoder.

Encoders can be hierarchical or non-hierarchical. The framework with a non-hierarchical encoder is just like the seq2seq architecture (Sutskever et al., 2014) which consists of an encoder and a decoder. The framework with a hierarchical encoder is just




Figure 2: The framework of MulZDG.

like HRED (Serban et al., 2016) which consists of a hierarchical encoder and a decoder. The structure of encoder can be RNN or transformer structure. Next, we briefly introduce both hierarchical and non-hierarchical frameworks.

3.3 Non-hierarchical MulZDG

The non-hierarchical MulZDG is a simple seq2seq structure, which has a shared encoder and a decoder module. The encoder is responsible for encoding the dialogue context and the decoder is responsible for generating the response for the dialogue context. Encoder-Decoder structure based on RNN (Sutskever et al., 2014) and Transformer (Vaswani et al., 2017) are the most classic representative models.

RNN Encoder-Decoder In this paper, we employ GRU (Cho et al., 2014) as the concrete implementation for RNN. We concatenate code-switching language utterances in dialogue context into a consecutive tokens sequence, and add a special start symbol [SOS] and end symbol [EOS] to each tokens sequence. The last hidden state of encoder is denoted as h_ℓ , which is considered as the dialogue context summary. ℓ represents the length of sequence. Finally, we employ another GRU to decode the probability distribution of response.

$$P_\theta(y|h_\ell) = \prod_{j=2}^m P_\theta(y_j|y_1, \dots, y_{j-1}, h_\ell)P(y_1) \quad (1)$$

where θ represents the parameters of GRU and y represents the response sequence to be decoded.

Transformer Encoder-Decoder Each layer of transformer (Vaswani et al., 2017) encoder is composed of a multi-head self-attention mechanism and a position-wise fully connected feed-forward network. A residual connection (He et al., 2016) is employed around each layer, followed by layer normalization (Ba et al., 2016). In addition to the two sub-layers in each encoder layer, the decoder layer possesses another multi-head attention calculating the weight distribution over the output of

the encoder based on predicted sequences. Note that in addition to the word embedding information, position encoding information is required in the embedding layer.

3.4 Hierarchical MulZDG

The encoder of hierarchical MulZDG possesses two basic components: utterance encoder and context encoder, which is like the HRED (Serban et al., 2016) architecture. The utterance encoder is responsible for capturing the features of each utterance and the context encoder is in charge of distilling the dependencies between different utterances. The framework MulZDG supports the implementation of RNNs and transformers structure. In this paper, we employ GRU as the implementation of RNNs.

Hierarchical Transformer Structure Note that positional encoding is required for the implementation of the transformer. The utterance encoder and decoder layer share the same positional encoding. The outputs of utterance encoder based on transformer can be denoted as $u_i = \{e_{sos}, e_1, e_2, \dots, e_m, e_{eos}\}$ for i -th utterance, where m represents the length of utterance. We employ an average pooling operation to get a fixed-dimensional representation for every utterance. We add positional encoding to h_i and the context encoder based on transformer is responsible for capturing the global dialogue context information $\hat{H} = \{\hat{h}_1, \hat{h}_2, \dots, \hat{h}_n\}$. Then the decoder layer decodes the probability distribution of response over \hat{H} .

$$h_i = \frac{1}{m} \sum_{j=0}^m e_j \quad (2)$$

4 Experiments

4.1 Datasets

In this paper, we select English datasets DailyDialog (Li et al., 2017) and DSTC7 (Galley et al., 2018) as the source languages and generate code-switching training examples based on source train-

ing datasets through Algorithm 1. We directly translate the test datasets into the corresponding target languages. Note that we employ different translation systems (described in Appendix A.1).

DailyDialog is a multi-turn dialogue dataset about our daily life, which consists of 11,118 context-response pairs for training, 1,000 pairs for validation, and 1,000 pairs for testing. The proportion of non-English utterances in code-switching dataset is De-30.186% in $D_{en_{de}}$, Es-30.134% in $D_{en_{es}}$, Fr-30.096% in $D_{en_{fr}}$, It-30.293% in $D_{en_{it}}$, Ru-30.199% in $D_{en_{ru}}$, Zh-30.109% in $D_{en_{zh}}$. In the experiment we abbreviate it as Daily.

DSTC7 is a multi-turn dialogue dataset from social media data, which consists of 76,590 context-response pairs for training, 17,870 pairs for validation, and 1,710 pairs for testing. The proportion of non-English utterances in code-switching dataset is De-27.661% in $D_{en_{de}}$, Es-27.545% in $D_{en_{es}}$, Fr-27.639% in $D_{en_{fr}}$, It-27.611% in $D_{en_{it}}$, Ru-27.786% in $D_{en_{ru}}$, Zh-27.565% in $D_{en_{zh}}$.

Models	Datasets	Types	PPL	BL-1/2	RL	Dist-1/2	Embed A/E/G
HRED	Daily	En	127.7	29.87/24.05	35.54	12.56/44.55	80.55/82.17/64.22
		Aug	122.4	34.47/28.31	39.11	13.33/45.67	82.66/82.88/65.76
		Multi	125.9	23.77/20.33	34.31	15.34/48.89	78.03/86.54/59.97
	DSTC7	En	116.9	26.73/17.38	29.03	5.34/24.52	78.98/84.78/61.66
		Aug	116.4	27.92/18.77	29.47	7.55/25.16	80.02/84.86/59.66
		Multi	119.7	23.85/12.87	23.77	7.66/33.67	77.37/87.57/60.02
VHRED	Daily	En	123.3	34.69/25.77	40.77	13.77/45.56	84.74/86.17/69.77
		Aug	123.1	35.93/27.35	41.88	14.57/46.16	86.88/87.94/71.23
		Multi	124.6	25.87/20.67	33.56	15.63/51.32	77.19/87.63/58.41
	DSTC7	En	127.7	25.54/14.44	25.47	7.49/32.93	77.77/85.68/57.98
		Aug	123.5	27.05/16.92	26.52	8.03/33.74	79.39/86.24/58.17
		Multi	123.4	20.04/11.34	23.56	6.89/36.52	76.88/87.12/57.96
Trans	Daily	En	143.3	22.86/14.77	28.55	10.36/33.63	79.96/80.06/63.15
		Aug	141.2	23.89/16.17	30.35	11.79/35.64	81.23/81.22/65.45
		Multi	146.7	18.67/11.89	22.65	8.98/33.63	74.53/77.98/59.67
	DSTC7	En	163.4	22.77/19.74	21.57	6.77/34.56	78.32/82.56/56.89
		Aug	158.9	24.47/23.44	23.67	7.98/35.02	80.19/84.47/56.88
		Multi	156.8	18.77/10.23	20.87	4.88/30.87	76.54/85.55/55.43
HTrans	Daily	En	146.7	23.76/15.61	27.3	9.96/35.79	80.26/79.44/62.62
		Aug	133.5	24.57/17.03	28.94	11.12/36.98	82.33/82.16/63.76
		Multi	146.7	18.67/11.89	22.65	8.98/33.63	74.53/77.98/59.67
	DSTC7	En	162.5	23.54/18.68	23.35	7.32/35.66	80.02/82.14/64.33
		Aug	153.3	25.78/20.37	25.76	8.69/37.84	82.43/84.34/65.54
		Multi	161.5	18.78/11.42	21.77	5.33/32.19	75.47/86.33/56.44

Table 1: Performance of models based on data augmentation using multilingual code-switching of monolingual source. Eng represents that models is only trained on monolingual source language. Aug represents that models is trained on mixed languages including source and multilingual code-switching based on MulZDG. BL stands for BLEU and RL represents Rouge-L. All values are multiplied by 100.

4.2 Baselines

MulZDG is a general multilingual learning framework that can be applied to various dialogue generation models. We select several representative models in this paper.

HRED (Serban et al., 2016) is a hierarchical encoder-decoder structure with a hierarchical encoder (including utterance encoder and context encoder) and a decoder. Hred employs shared en-

Models	Datasets	Types	PPL	BL-1/2	RL	Dist-1/2	Embed A/E/G
HRED	Daily	De	125.4	25.89/20.17	35.72	15.63/49.55	78.23/86.86/62.42
		Multi	125.9	23.77/20.33	34.31	15.34/48.89	78.03/86.54/59.97
		De	124.6	21.68/11.89	21.71	7.35/35.23	77.19/87.63/58.41
	DSTC7	Multi	119.7	23.85/12.87	23.77	7.66/33.67	77.37/87.57/60.02
		De	121.2	27.14/20.44	34.77	16.53/51.94	77.56/87.26/62.09
		Multi	124.6	25.87/20.67	33.56	15.63/51.32	77.04/87.56/61.42
VHRED	Daily	De	121.2	27.14/20.44	34.77	16.53/51.94	77.56/87.26/62.09
		Multi	124.6	25.87/20.67	33.56	15.63/51.32	77.04/87.56/61.42
		De	125.3	22.74/12.07	23.69	7.68/36.29	78.34/87.44/58.62
	DSTC7	Multi	123.4	20.04/11.34	23.56	6.89/36.52	76.88/87.12/57.96
		De	150.2	20.06/12.38	24.96	9.35/34.56	74.63/78.88/60.76
		Multi	146.7	18.67/11.89	22.65	8.98/33.63	74.53/77.98/59.67
Trans	Daily	De	150.2	20.06/12.38	24.96	9.35/34.56	74.63/78.88/60.76
		Multi	146.7	18.67/11.89	22.65	8.98/33.63	74.53/77.98/59.67
		De	156.2	20.55/11.37	22.76	5.64/32.19	76.54/85.55/55.43
	DSTC7	Multi	156.8	18.77/10.23	20.87	4.88/30.87	75.87/84.71/55.13
		De	156.7	21.33/11.66	25.22	8.96/33.19	75.61/77.98/61.86
		Multi	157.8	19.65/10.98	24.33	8.87/33.65	74.78/79.13/59.43
HTrans	De	157.7	19.88/11.24	23.45	5.77/33.47	75.96/86.73/56.47	
	Multi	161.5	18.78/11.42	21.77	5.33/32.19	75.47/86.33/56.44	

Table 2: Zero-shot results of models on German. De represents that models is only trained on German training set. Multi represents that models is only trained on code-switching languages based on MulZDG.

Models	Datasets	Types	PPL	BL-1/2	RL	Dist-1/2	Embed A/E/G
HRED	Daily	Es	124.1	25.49/20.75	36.97	17.68/52.65	77.69/84.21/63.44
		Multi	126.7	26.45/20.55	35.98	17.33/50.56	76.53/83.68/63.56
		Es	119.6	25.39/14.47	26.94	7.58/30.13	77.99/87.32/61.24
	DSTC7	Multi	118.4	25.47/15.76	29.23	7.23/30.67	77.68/86.77/62.13
		Es	122.1	29.14/23.04	35.99	18.82/55.37	77.79/85.52/62.28
		Multi	126.7	30.88/22.52	34.76	17.35/54.88	77.23/85.66/62.03
VHRED	Daily	Es	122.1	29.14/23.04	35.99	18.82/55.37	77.79/85.52/62.28
		Multi	126.7	30.88/22.52	34.76	17.35/54.88	77.23/85.66/62.03
		Es	114.5	26.24/14.42	27.82	8.78/32.45	78.68/87.88/59.77
	DSTC7	Multi	123.3	26.45/17.39	31.19	7.49/32.19	78.97/87.57/63.64
		Es	157.7	19.06/3.65	22.06	8.35/30.65	73.61/77.67/58.36
		Multi	153.7	18.76/12.98	22.05	8.14/31.48	73.32/76.88/59.54
Trans	Daily	Es	157.7	19.06/3.65	22.06	8.35/30.65	73.61/77.67/58.36
		Multi	153.7	18.76/12.98	22.05	8.14/31.48	73.32/76.88/59.54
		Es	123.3	24.38/15.52	26.44	7.53/30.62	77.66/86.48/60.12
	DSTC7	Multi	125.7	24.33/15.43	24.55	7.43/30.88	77.42/86.04/62.33
		Es	154.6	18.93/10.57	21.76	8.07/29.33	72.55/75.69/56.38
		Multi	156.3	17.97/9.47	21.62	8.33/27.74	72.76/75.4/56.12
HTrans	Es	127.8	23.87/14.33	26.56	7.44/29.48	77.87/85.46/59.56	
	Multi	131.2	23.19/12.59	24.89	7.95/29.65	76.46/83.12/57.15	

Table 3: Zero-shot results of models on Spanish. Es represents models is trained on monolingual Spanish.

coders to encode each utterance separately.

VHRED (Serban et al., 2017) is a hierarchical encoder-decoder structure with a hierarchical encoder (including utterance encoder and context encoder) and a decoder based on variational mechanism. VHRED can generate long outputs with better use of contextual information via latent variables.

Transformer (Vaswani et al., 2017) is an encoder-decoder structure with multi-head attention mechanism. The inputs of the Transformer is a consecutive word sequence concatenated all utterances. In all experimental tables, we abbreviate it as **Trans**.

HTransformer (Santra et al., 2021) is a hierarchical encoder-decoder structure with a hierarchical encoder (including utterance encoder and context encoder) and a decoder. Htransformer encodes each utterance separately. In all experimental tables, we abbreviate it as **HTrans**.

4.3 Implementation Details

We implement our MulZDG using Tensorflow 2. The word embedding size and hidden size are all set to 512. We employ Adam optimizer (Kingma and Ba, 2015) to train all models. For the models HRED and VHRED we set the learning rate to 0.001. For the Transformer and HTransformer, we set the learning rate to 0.0001. For the models HRED and VHRED, we set the number of encoder and decoder layers to 1. For the Transformer and HTransformer, the number of encoder and decoder layers is 3. And the number HRED for Transformer and HTransformer is 8. We employ the word segmentation of BERT (Devlin et al., 2019) and the vocabulary of multilingual BERT as the unified vocabulary. The batch size is 128 for HRED and VHRED, and we set it to 512 for Transformer and HTransformer. The maximum epochs are set to 200. We employ GloVe to train a unified multilingual embedding vectors representation for embedding-based metrics based on multilingual corpora. We do not remove unknown tokens when computing embedding-based metrics, and the vectors of all unknown tokens are initialized to zero vector.

Models	Datasets	Types	PPL	BL-1/2	RL	Dist-1/2	Embed A/E/G
HRED	Daily	Fr	122.3	25.36/19.89	35.15	13.59/43.68	80.44/87.12/64.43
		Multi	124.6	25.12/18.78	35.04	13.35/42.45	79.31/87.09/62.21
	DSTC7	Fr	111.3	26.42/16.82	27.18	4.7/21.18	80.84/88.36/62.59
		Multi	116.8	26.54/15.96	25.47	5.43/24.33	80.45/88.31/60.61
VHRED	Daily	Fr	132.2	25.64/19.49	34.97	15.42/45.22	79.86/87.77/63.83
		Multi	135.4	24.96/18.87	32.43	13.88/43.88	79.89/87.57/65.13
	DSTC7	Fr	107.6	28.88/19.36	29.24	5.85/26.22	81.18/88.35/63.8
		Multi	112.4	26.93/18.47	27.56	5.77/26.6	80.39/88.26/61.24
Trans	Daily	Fr	163.7	16.66/12.06	25.3	7.47/29.34	75.66/77.14/59.78
		Multi	166.5	15.76/11.56	24.54	7.23/29.87	76.32/77.65/57.62
	DSTC7	Fr	122.3	25.64/16.47	28.04	5.12/25.63	79.94/87.57/61.25
		Multi	124.2	23.65/14.67	27.33	5.34/24.77	79.54/86.32/60.43
HTrans	Daily	Fr	164.4	16.61/9.49	22.82	7.57/31.98	75.12/78.06/60.08
		Multi	165.4	15.44/8.54	21.65	6.77/31.33	75.54/78.67/60.36
	DSTC7	Fr	125.6	24.87/17.77	26.89	4.77/22.34	79.56/88.45/60.56
		Multi	127.3	24.18/16.28	24.86	4.53/22.54	79.89/87.23/62.65

Table 4: Zero-shot results of models on French. Fr represents models is trained on monolingual French.

4.4 Evaluation metrics

To compare different models, we employ both automatic metrics and human evaluations. **Automatic Metrics:** We employ perplexity (PPL) and distinct 1/2 (Dist.1/2) following previous studies (Zhang et al., 2018; Zheng et al., 2020; Song et al., 2021). Lower perplexity means more reliable model. Distinct 1/2 (Li et al., 2016) are the ratio of distinct uni-grams / bi-grams. Higher distinct means better diversity of responses generated by the model. We also employ BLEU (Papineni et al.,




Figure 3: The impact of the number of multilingual code-switching languages on models performance for German. The '1' in abscissa represents that models are trained on monolingual German. Number of languages is greater than '1' represents models is trained on multilingual code-switching languages based on MulZDG.

Models	Datasets	Types	PPL	BL-1/2	RL	Dist-1/2	Embed A/E/G
HRED	Daily	It	126.7	25.51/20.01	35.84	18.07/53.16	76.34/84.54/61.98
		Multi	126.7	25.01/19.23	33.98	18.33/53.25	74.78/84.13/60.3
	DSTC7	It	108.5	24.26/16.11	27.26	7.56/34.53	75.69/87.07/58.73
		Multi	111.2	22.65/14.52	25.54	7.13/32.15	73.85/87.04/56.96
VHRED	Daily	It	123.7	26.99/20.82	34.69	19.64/57.47	76.56/85.38/60.77
		Multi	124.4	25.11/19.14	32.68	17.72/55.89	74.39/84.33/59.31
	DSTC7	It	114.6	28.66/19.04	29.42	8.57/35.12	80.99/88.31/63.96
		Multi	125.4	26.87/18.44	28.49	7.54/35.12	78.54/87.19/63.56
Trans	Daily	It	156.5	18.11/15.72	27.15	8.75/32.34	75.37/79.67/62.08
		Multi	160.5	16.65/14.36	27.42	7.87/31.33	74.36/78.23/61.32
	DSTC7	It	123.3	25.55/17.57	26.44	6.54/32.12	75.09/86.88/57.97
		Multi	124.3	23.55/16.55	24.87	6.12/30.35	75.01/85.32/57.89
HTrans	Daily	It	153.5	19.43/17.56	29.3	9.05/30.34	76.22/80.89/63.28
		Multi	154.7	17.87/18.04	28.88	9.87/30.54	76.86/80.23/62.67
	DSTC7	It	124.5	26.76/18.97	25.67	7.56/34.56	76.11/85.12/57.44
		Multi	123.6	24.88/18.95	24.77	7.45/32.17	76.59/85.07/56.21

Table 5: Zero-shot results of models on Italian. It represents models is trained on monolingual Italian.

2002) and ROUGE-L (Lin, 2004) (abbreviated as RL) for evaluating response generation. BLEU and ROUGE-L metrics evaluate the response based on o-occurrence properties of tokens. Embedding-based metrics (Average, Exterma and Greedy) (Liu et al., 2016; Xu et al., 2018; Sedoc et al., 2019) can reflect the quality of the generated responses at the semantic level. **Human Evaluation:** We further conduct human evaluations to assess the proposed learning framework. We select Chinese and English dialogue systems for human evaluation on DailyDialog and DSTC7. We ask three crowd-sourced graduate students to evaluate the quality of generated responses for 100 randomly sampled input contexts. We request annotators to choose a preferred response, or vote a tie, considering the following aspects of response quality: fluency, informativeness, coherence, and engagingness.

4.5 Effectiveness of Data Augmentation

In particular, models based on transformer do not employ pre-trained language model as the initial checkpoint and train from scratch. In addition,

Models	Datasets	Types	PPL	BL-1/2	RL	Dist-1/2	Embed A/E/G
HRED	Daily	Ru	123.8	28.43/22.16	37.51	21.36/53.56	78.07/85.83/64.34
		Multi	127.6	27.57/21.57	36.65	20.54/52.15	76.32/84.84/64.37
	DSTC7	Ru	119.5	28.21/14.25	29.95	10.22/35.21	80.68/86.61/64.17
		Multi	116.5	27.99/18.19	28.93	9.32/35.12	81.38/88.68/63.51
VHRED	Daily	Ru	134.3	27.96/21.88	35.66	21.46/55.88	78.66/85.63/63.22
		Multi	133.2	25.43/20.47	33.23	20.13/53.17	76.98/85.65/63.22
	DSTC7	Ru	103.6	29.49/17.02	34.25	11.15/36.61	79.96/86.13/66.41
		Multi	107.7	27.77/16.87	34.77	10.86/34.65	80.03/86.88/65.74
Trans	Daily	Ru	144.6	21.53/13.77	27.68	9.57/34.93	78.37/81.55/64.5
		Multi	147.9	20.54/13.28	27.43	8.76/33.98	78.54/80.13/62.19
	DSTC7	Ru	123.3	25.66/13.27	27.84	9.46/32.67	78.88/84.55/65.14
		Multi	125.4	24.65/12.09	25.48	8.91/30.54	77.99/84.33/64.87
HTrans	Daily	Ru	143.1	20.77/14.65	28.49	9.68/35.20	78.75/81.33/63.05
		Multi	147.6	18.44/13.76	26.35	9.02/33.89	78.96/79.57/63.06
	DSTC7	Ru	127.8	24.87/14.77	26.46	9.13/31.66	77.88/83.67/65.03
		Multi	128.6	22.76/13.56	24.32	8.25/29.78	77.54/81.98/65.23

Table 6: Zero-shot results of models on Russian. Ru represents models is trained on monolingual Russian.

the performance of models based on transformer perform worse than RNN in experiments due to the limited training datasets.

Table 1 reports the results of models on DailyDialog and DSTC7 using monolingual English corpus and data augmentation based on multilingual code-switching languages. We can observe that the performances of models are greatly improved when using data augmentation based on multilingual code-switching. Specifically, the performances of models using data augmentation with multilingual code-switching is 0.2% to 13.2% on PPL, 0.81% to 4.38% higher on BLEU-1, 1.4% to 3.7% higher on BLEU-2, 0.59% to 2.41% higher on Rouge-L, 0.54% to 1.43% higher on dist-1, 0.46% to 2.64% higher on dist-2, and 1.27% to 2.41% higher on average embedding compared with models using monolingual English corpus. The data augmentation approaches with multilingual code-switching can enhance the representation ability of models and improve the quality of the responses through learning common features between different languages.

4.6 Zero-shot Dialogue Generation

Different from Table 1, Table 2 to Table 7 report the results of zero-shot generation using MulZDG based on multilingual code-switching languages. The performances of models training on multilingual code-switching languages can achieve competitive results under zero-shot case compared with on corresponding monolingual language. On German DailyDialog and DSTC7, the performances of models under zero-shot case is 0.1% higher on PPL, 1.23% lower on BLEU-1, 0.93% on Rouge-L, 0.71% on dist-1 and 0.51% on average embedding compared with models training on monolingual




Figure 4: Semantic alignment visualization. The left presents the visualization of utterance vectors for models trained on monolingual language. The right demonstrates the visualization of utterance vectors for models trained on multilingual code-switching languages based on MulZDG. The label $lan-N_1-N_2$ represents the number of the utterance, where lan stands for language, N_1 stands for the number of data sample and N_2 indicates the utterance number of utterances in dialogue history.

corpus according to Table 2. On French DailyDialog and DSTC7, the performances of models under zero-shot case is 2.9% lower on PPL, 0.93% lower on BLEU-1, 1.34% on Rouge-L, 0.27% on dist-1 and 0.16% on average embedding compared with models training on monolingual corpus according to Table 4. On Chinese datasets, the performances of models under zero-shot case is 2.1% lower on PPL, 0.91% lower on BLEU-1, 1.57% on Rouge-L, 0.44% on dist-1 and 0.62% on average embedding compared with models training on monolingual corpus according to Table 7.

We can observe the similar results on other languages. MulZDG adopts a multi-task approach to generate responses in different languages. On the one hand, sharing the structure between multiple tasks is beneficial for models to exploit the common features between different languages. On the other hand, sharing task mechanism between multilingual code-switching languages is beneficial to enhance the semantic alignment ability of models between different languages.

4.7 Impact of Multilingualization

To explore the effect of multilingual code-switching languages, we conduct further experiments. Figure 3 demonstrates the effect of the number of languages on models performance. We

Models	Datasets	Types	PPL	BL-1/2	RL	Dist-1/2	Embed A/E/G
HRED	Daily	Zh	127.4	23.52/19.52	30.83	9.5/43.37	83.05/83.77/68.42
		Multi	124.3	21.34/18.11	28.33	9.05/42.07	83.56/82.75/66.88
	DSTC7	Zh	108.1	18.07/12.68	26.78	4.06/25.24	85.32/86.27/73.63
		Multi	116.7	17.91/11.55	24.83	4.04/23.81	85.8/86.34/72.29
VHRED	Daily	Zh	125.6	24.54/20.03	31.28	11.22/46.08	83.17/84.43/67.77
		Multi	127.3	24.57/19.09	29.88	9.97/44.13	82.18/84.32/66.49
	DSTC7	Zh	110.4	19.92/13.32	27.61	4.56/26.57	85.79/86.54/72.01
		Multi	116.5	17.98/12.65	26.17	4.36/24.79	84.15/85.32/72.4
Trans	Daily	Zh	165.7	15.55/11.54	24.38	7.89/33.47	79.32/80.46/66.21
		Multi	167.4	15.13/10.33	22.99	6.54/31.44	76.98/78.54/66.21
	DSTC7	Zh	123.4	18.77/12.45	26.58	4.15/24.46	83.56/85.67/71.77
		Multi	123.3	18.04/11.87	25.37	4.54/23.87	84.13/83.51/70.7
HTrans	Daily	Zh	166.8	16.92/11.83	25.66	8.61/34.21	79.92/81.51/66.54
		Multi	167.7	15.66/11.09	24.76	7.96/33.2	78.99/80.23/66.46
	DSTC7	Zh	134.5	19.04/12.44	25.67	4.32/25.67	84.39/85.19/70.65
		Multi	135.4	18.45/11.32	23.87	4.32/25.33	83.79/83.99/69.69

Table 7: Zero-shot results of models on Chinese. Zh represents models is trained on monolingual Chinese.

Models	Languages	Datasets					
		Daily (%)			DSTC7 (%)		
		Win	Tie	Loss	Win	Tie	Loss
HRED	En	30	44	26	33	36	31
	Fr	23	56	21	23	54	23
	Zh	31	35	34	32	33	35
VHRED	En	38	32	30	30	45	25
	Fr	16	63	21	11	82	7
	Zh	36	29	35	30	37	33

Table 8: Human evaluation on DailyDialog and DSTC7 (multilingual VS monolingual). On English corpus, we compare the the performances of models training using data augmentation of multilingual code-switching with monolingual English corpus. On other languages, we compare the performances of models under zero-shot using multilingual code-switching languages with corresponding monolingual corpus.

select German as the target language (other languages are available), HRED and VHRED as the tested models. The performances of bilingual code-switching languages on HRED and VHRED are dramatically lower than models trained on the corresponding monolingual training set. However, the performances of models are gradually improved with the number of languages increases. We can only add up to seven languages due to the limitations of our constructed corpus. We can conclude that MulZDG fails to work well in zero-shot case when the number of languages is small according to 3. More constructive conclusions require further experimental evaluation in the case of more languages in the future, such as hundreds of languages.

4.8 Multilingual Mechanism Analysis

We conduct extensive experiments to explore how the multilingual mechanism works. We select 1,000 multilingual parallel examples from DailyDialog, about 4,536 utterances in total and vi-

sualize the representations of these examples in HRED and VHRED based on MulZDG trained on different monolingual languages and multilingual code-switching languages, respectively. Figure 4 presents the results of the utterances representation visualization on HRED and VHRED. The representations of utterances based on different monolingual languages are clustered into different language categories while representations of utterances on multilingual code-switching languages are clustered together according to semantics. Utterances in different languages expressing same semantics will be clustered together, which demonstrates that MulZDG will do semantic alignment between different languages. This phenomenon presents that MulZDG pays attention to the common features between different languages.

4.9 Human Evaluation

Although automatic evaluation metrics have been shown to be reliable, we still conduct human evaluations to confirm the validity of the MulZDG. We compare the performance of models training on multilingual code-switching languages and on corresponding monolingual language. Table 8 reports the results of human evaluation of HRED and VHRED on three languages (i.e., English, French and Chinese). We can observe that the performances of models using data augmentation with multilingual code-switching is on average 6.0% higher on DailyDialog and 3.5% higher on DSTC7 than using monolingual English corpus. Besides, the performance of models under zero-shot is on average 5% lower on DailyDialog and 2% lower on DSTC7 than using corresponding monolingual corpus. These results demonstrate that multilingual code-switching framework can not only be considered as a data augmentation method but also be employed to zero-shot dialogue generation.

5 Conclusion and Future Work

In this paper, we propose a simple but effective multilingual framework: MulZDG, which can not only be used as an approach of data augmentation but also be used to zero-shot dialogue generation. Besides, we release the multilingual versions of DailyDialog and DSTC7 datasets. In the future, we will explore the working mechanism and effect of large-scale multilingual code-switching languages (e.g., hundreds of languages) in the problem of zero-shot dialogue generation.

6 Acknowledgement

We would like to thank the reviewers for their constructive comments. The project is supported by the National Natural Science Foundation of China (61872074, 62172086, 62106039, 62272092).

References

- Mikel Artetxe, Gorka Labaka, and Eneko Agirre. 2018. Unsupervised statistical machine translation. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3632–3642.
- Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. 2016. Layer normalization. *arXiv preprint arXiv:1607.06450*.
- Suman Banerjee, Nikita Moghe, Siddhartha Arora, and Mitesh M Khapra. 2018. A dataset for building code-mixed goal oriented conversation systems. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 3766–3780.
- Siqi Bao, Huang He, Fan Wang, Hua Wu, and Haifeng Wang. 2020. Plato: Pre-trained dialogue generation model with discrete latent variable. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 85–96.
- Anshul Bawa, Pranav Khadpe, Pratik Joshi, Kalika Bali, and Monojit Choudhury. 2020. Do multilingual users prefer chat-bots that code-mix? let’s nudge and find out! *Proceedings of the ACM on Human-Computer Interaction*, 4(CSCW1):1–23.
- Piotr Bojanowski, Édouard Grave, Armand Joulin, and Tomáš Mikolov. 2017. Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, 5:135–146.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Emile Chapuis, Pierre Colombo, Matthieu Labeau, and Chloe Clavel. 2021. Code-switched inspired losses for generic spoken dialog representations. *arXiv preprint arXiv:2108.12465*.
- Yong Cheng. 2019. Joint training for pivot-based neural machine translation. In *Joint Training for Neural Machine Translation*, pages 41–54. Springer.
- Kyunghyun Cho, Bart Van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. 2014. Learning phrase representations using rnn encoder–decoder for statistical machine translation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1724–1734.
- Alexis Conneau, Guillaume Lample, Marc’Aurelio Ranzato, Ludovic Denoyer, and Hervé Jégou. 2017. Word translation without parallel data. *International Conference on Learning Representations (ICLR)*.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *NAACL-HLT (1)*.
- A Seza Doğruöz, Sunayana Sitaram, Barbara Bullock, and Almeida Jacqueline Toribio. 2021. A survey of code-switching: Linguistic and social perspectives for language technologies. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1654–1666.
- Abteen Ebrahimi and Katharina Kann. 2021. How to adapt your pretrained multilingual model to 1600 languages. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 4555–4567.
- Luciano Floridi and Massimo Chiriatti. 2020. Gpt-3: Its nature, scope, limits, and consequences. *Minds and Machines*, 30(4):681–694.
- Michel Galley, Chris Brockett, Xiang Gao, Bill Dolan, and Jianfeng Gao. 2018. End-to-end conversation modeling: Moving beyond chitchat.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778.
- Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2019. The curious case of neural text de-generation. In *International Conference on Learning Representations*.
- Minlie Huang, Xiaoyan Zhu, and Jianfeng Gao. 2020. Challenges in building intelligent open-domain dialog systems. *ACM Transactions on Information Systems (TOIS)*, 38(3):1–32.
- Melvin Johnson, Mike Schuster, Quoc V Le, Maxim Krikun, Yonghui Wu, Zhifeng Chen, Nikhil Thorat, Fernanda Viégas, Martin Wattenberg, Greg Corrado, et al. 2017. Google’s multilingual neural machine translation system: Enabling zero-shot translation. *Transactions of the Association for Computational Linguistics*, 5:339–351.
- Pei Ke, Jian Guan, Minlie Huang, and Xiaoyan Zhu. 2018. Generating informative responses with controlled sentence function. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1499–1508.

- San Kim, Jin Yea Jang, Minyoung Jung, and Saim Shin. 2021. A model of cross-lingual knowledge-grounded response generation for open-domain dialogue systems. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 352–365.
- Diederik P Kingma and Jimmy Ba. 2015. Adam: A method for stochastic optimization.
- Guillaume Lample, Alexis Conneau, Ludovic Denoyer, and Marc’Aurelio Ranzato. Unsupervised machine translation using monolingual corpora only. In *International Conference on Learning Representations (ICLR)*, publisher = *OpenReview.net*, year = 2018,.
- Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. 2020. Bart: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7871–7880.
- Chunyuan Li, Xiang Gao, Yuan Li, Baolin Peng, Xiujuan Li, Yizhe Zhang, and Jianfeng Gao. 2020. Optimus: Organizing sentences via pre-trained modeling of a latent space. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4678–4699.
- Jiwei Li, Michel Galley, Chris Brockett, Jianfeng Gao, and William B Dolan. 2016. A diversity-promoting objective function for neural conversation models. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 110–119.
- Yanran Li, Hui Su, Xiaoyu Shen, Wenjie Li, Ziqiang Cao, and Shuzi Niu. 2017. Dailydialog: A manually labelled multi-turn dialogue dataset. In *Proceedings of the Eighth International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 986–995.
- Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81.
- Yanxiang Ling, Fei Cai, Xuejun Hu, Jun Liu, Wanyu Chen, and Honghui Chen. 2021. Context-controlled topic-aware neural response generation for open-domain dialog systems. *Information Processing & Management*, 58(1):102392.
- Chia-Wei Liu, Ryan Lowe, Iulian V Serban, Michael Noseworthy, Laurent Charlin, and Joelle Pineau. 2016. How not to evaluate your dialogue system: An empirical study of unsupervised evaluation metrics for dialogue response generation. *arXiv preprint arXiv:1603.08023*.
- Yinhan Liu, Jiatao Gu, Naman Goyal, Xian Li, Sergey Edunov, Marjan Ghazvininejad, Mike Lewis, and Luke Zettlemoyer. 2020a. Multilingual denoising pre-training for neural machine translation. *Transactions of the Association for Computational Linguistics*, 8:726–742.
- Zihan Liu, Genta Indra Winata, Zhaojiang Lin, Peng Xu, and Pascale Fung. 2020b. Attention-informed mixed-language training for zero-shot cross-lingual task-oriented dialogue systems. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 8433–8440.
- Chuan Meng, Pengjie Ren, Zhumin Chen, Zhaochun Ren, Tengxiao Xi, and Maarten de Rijke. 2021. Initiative-aware self-supervised learning for knowledge-grounded conversations. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 522–532.
- Chuan Meng, Pengjie Ren, Zhumin Chen, Weiwei Sun, Zhaochun Ren, Zhaopeng Tu, and Maarten de Rijke. 2020. Dukenet: A dual knowledge interaction network for knowledge-grounded conversation. In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 1151–1160.
- Xiao Pan, Mingxuan Wang, Liwei Wu, and Lei Li. 2021. Contrastive learning for many-to-many multilingual neural machine translation. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 244–258.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pages 311–318.
- Jeffrey Pennington, Richard Socher, and Christopher D Manning. 2014. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543.
- Libo Qin, Minheng Ni, Yue Zhang, and Wanxiang Che. 2021. Cosda-ml: Multi-lingual code-switching data augmentation for zero-shot cross-lingual nlp. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence*.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21:1–67.
- Bishal Santra, Potnuru Anusha, and Pawan Goyal. 2021. Hierarchical transformer for task oriented dialog systems. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5649–5658.

- Joao Sedoc, Daphne Ippolito, Arun Kirubarajan, Jai Thirani, Lyle Ungar, and Chris Callison-Burch. 2019. Chateval: A tool for chatbot evaluation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (Demonstrations)*, pages 60–65.
- Iulian Serban, Alessandro Sordoni, Yoshua Bengio, Aaron Courville, and Joelle Pineau. 2016. Building end-to-end dialogue systems using generative hierarchical neural network models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30.
- Iulian Serban, Alessandro Sordoni, Ryan Lowe, Laurent Charlin, Joelle Pineau, Aaron Courville, and Yoshua Bengio. 2017. A hierarchical latent variable encoder-decoder model for generating dialogues. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31.
- Haoyu Song, Yan Wang, Kaiyan Zhang, Weinan Zhang, and Ting Liu. 2021. Bob: Bert over bert for training persona-based dialogue models from limited personalized data. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 167–177.
- Alessandro Sordoni, Yoshua Bengio, Hossein Vahabi, Christina Lioma, Jakob Grue Simonsen, and Jian-Yun Nie. 2015. A hierarchical recurrent encoder-decoder for generative context-aware query suggestion. In *proceedings of the 24th ACM international on conference on information and knowledge management*, pages 553–562.
- Ilya Sutskever, Oriol Vinyals, and Quoc V Le. 2014. Sequence to sequence learning with neural networks. In *Advances in neural information processing systems*, pages 3104–3112.
- Zhiliang Tian, Wei Bi, Dongkyu Lee, Lanqing Xue, Yiping Song, Xiaojiang Liu, and Nevin L Zhang. 2020. Response-anticipated memory for on-demand knowledge integration in response generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 650–659.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.
- Yiru Wang, Pengda Si, Zeyang Lei, and Yujiu Yang. 2020. Topic enhanced controllable cvae for dialogue generation (student abstract). In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 13955–13956.
- Chien-Sheng Wu, Richard Socher, and Caiming Xiong. 2018. Global-to-local memory pointer networks for task-oriented dialogue. In *International Conference on Learning Representations*.
- Xinnuo Xu, Ondřej Dušek, Ioannis Konstas, and Verena Rieser. 2018. Better conversations by modeling, filtering, and optimizing for coherence and diversity. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3981–3991.
- Bowen Zhang, Xiaofei Xu, Xutao Li, Yunming Ye, Xiaojun Chen, and Zhongjie Wang. 2020a. A memory network based end-to-end personalized task-oriented dialogue generation. *Knowledge-Based Systems*, 207:106398.
- Hainan Zhang, Yanyan Lan, Liang Pang, Hongshen Chen, Zhuoye Ding, and Dawei Yin. 2021. Modeling topical relevance for multi-turn dialogue generation. In *Proceedings of the Twenty-Ninth International Conference on International Joint Conferences on Artificial Intelligence*, pages 3737–3743.
- Hainan Zhang, Yanyan Lan, Liang Pang, Jiafeng Guo, and Xueqi Cheng. 2019. Recosa: Detecting the relevant contexts with self-attention for multi-turn dialogue generation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3721–3730.
- Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. 2018. Personalizing dialogue agents: I have a dog, do you have pets too? In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2204–2213.
- Yizhe Zhang, Siqi Sun, Michel Galley, Yen-Chun Chen, Chris Brockett, Xiang Gao, Jianfeng Gao, Jingjing Liu, and Bill Dolan. 2020b. Dialogpt: Large-scale generative pre-training for conversational response generation. In *ACL (demo)*.
- Hao Zheng, Yong Cheng, and Yang Liu. 2017. Maximum expected likelihood estimation for zero-resource neural machine translation. In *International Joint Conference on Artificial Intelligence*.
- Yinhe Zheng, Rongsheng Zhang, Minlie Huang, and Xiaoxi Mao. 2020. A pre-training based personalized dialogue generation model with persona-sparse data. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 9693–9700.

A Appendix

A.1 NMT Systems

We simulate distribution differences between training and test datasets through using different translation systems. The NMT systems employed for the training set are *Helsinki-NLP/opus-mt-en-tar*². ‘tar’ represents the target languages, which includes Chinese, German, Russian, Spanish, French and Italian. And we employ T5-base³ to translate the test

²<https://huggingface.co/Helsinki-NLP/>

³<https://huggingface.co/t5-base>

Models	Types	Responses
HRED	En	I like travelling. like my experience and i have a good idea.
	Aug	I like travelling. I travel frequently.
VHRED	En	i like sports. I like travelling.
	Aug	I like travelling. I'll do it next time.
Gold Response		Yes, I like travelling. I am young, and unmarried. It's no problem for me to travel frequently.

Table 9: Case study for data augmentation on Daily dataset. The English context is "What are your personal weaknesses? I'm afraid I'm a poor talker. I'm not comfortable talking with the people whom I have just met for the first time. That is not very good for business, so I have been studying public speaking. Are you more of a leader or a follower? I don't try to lead people. I'd rather cooperate with everybody, and get the job done by working together. Do you think you can make yourself easily understood in English? Yes, in most circumstances. Are you available for travel?"

datasets into German and French. For Russian, Chinese, Spanish and Italian we employ WMT19-en-ru⁴, WMT-en-zh⁵, mbart-en-es⁶ and Google NMT system, respectively.

A.2 Dictionaries

(Lample et al.) employs FastText (Bojanowski et al., 2017) methods on the source and target monolingual corpora to train word embeddings and then applies the unsupervised method (Conneau et al., 2017) to infer a bilingual dictionary. (Lample et al.) provides 110 bilingual dictionaries which can be used for word-by-word translation. According to statistics, there are 101,997 De-En word pairs, 112,583 Es-En word pairs, 113,324 Fr-En word pairs, 103,613 It-En word pairs, 48,714 Ru-En word pairs and 21,597 Zh-En word pairs.

A.3 Case Study

An case study is provided in Table 9 to demonstrate the values of augmented data. We can observe that the responses of HRED and VHRD contain context-independent information without using data augmentation. Specifically, "like my experience and i have a good idea" in HRED and "i like sports" in VHRED are context independent. The responses generated by HRED and VHRED are more informative and more coherent when using data augmentation. Models can utilize cross linguistic knowledge to generate more informative and coherent responses by multilingual data augmentation.

⁴<https://huggingface.co/facebook/wmt19-en-ru>

⁵<https://huggingface.co/liam168/trans-opus-mt-en-zh>

⁶<https://huggingface.co/mrm8488/mbart-large-finetuned-opus-en-es-translation>