

# GAIA Search: Hugging Face and Pyserini Interoperability for NLP Training Data Exploration

Aleksandra Piktus<sup>1,2</sup> Odunayo Ogundepo<sup>3</sup> Christopher Akiki<sup>4,5</sup> Akintunde Oladipo<sup>3</sup>  
Xinyu Zhang<sup>3</sup> Hailey Schoelkopf<sup>6</sup> Stella Biderman<sup>6,7</sup> Martin Potthast<sup>4,5</sup> Jimmy Lin<sup>3</sup>

<sup>1</sup>Hugging Face <sup>2</sup>Sapienza University <sup>3</sup>University of Waterloo  
<sup>4</sup>Leipzig University <sup>5</sup>ScaDS.AI <sup>6</sup>EleutherAI  
<sup>7</sup>Booz Allen Hamilton  
piktus@huggingface.co

## Abstract

Noticing the urgent need to provide tools for fast and user-friendly qualitative analysis of large-scale textual corpora of the modern NLP, we propose to turn to the mature and well-tested methods from the domain of Information Retrieval (IR)—a research field with a long history of tackling TB-scale document collections. We discuss how Pyserini—a widely used toolkit for reproducible IR research can be integrated with the Hugging Face ecosystem of open-source AI libraries and artifacts. We leverage the existing functionalities of both platforms while proposing novel features further facilitating their integration. Our goal is to give NLP researchers tools that will allow them to develop retrieval-based instrumentation for their data analytics needs with ease and agility. We include a Jupyter Notebook-based walk through the core interoperability features, available [on GitHub](#). We then demonstrate how the ideas we present can be operationalized to create a powerful tool for qualitative data analysis in NLP. We present GAIA Search—a search engine built following previously laid out principles, giving access to four popular large-scale text collections. GAIA serves a dual purpose of illustrating the potential of methodologies we discuss but also as a standalone qualitative analysis tool that can be leveraged by NLP researchers aiming to understand datasets prior to using them in training. GAIA is hosted live on [Hugging Face Spaces](#).

## 1 Introduction

Training large language models, or LLMs (Brown et al., 2020; Lieber et al., 2021; Rae et al., 2021; Smith et al., 2022; Le Scao et al., 2022; Chowdhery et al., 2022; Touvron et al., 2023), established itself as the central task of the modern Natural Language Processing (NLP) research. The attempts to understand the scaling laws of LLMs led researchers to believe that simply increasing the number of parameters may not bring the desired improvements without a simultaneous increase in the size of the

LLM training data (Kaplan et al., 2020; Hoffmann et al., 2022). These observations only increased an already pressing need for massive textual datasets, fueling the proliferation of Web-based corpora of TB-scale created with varying levels of curation and quality control.

Rather than investing in scraping the Web on their own, dataset creators typically turn to Common Crawl<sup>1</sup> as the main source of text to include in their corpora. A repository of Web snapshots dating back to 2011, Common Crawl contains various types of low-quality text (Luccioni and Viviano, 2021). Pre-processing steps commonly introduced by dataset creators aiming to filter out undesired content include removing any documents with words matching a pre-defined, static blacklist, like in the case of C4 (Raffel et al., 2020), perplexity-based filtering like in CCNet and ROOTS (Wenzek et al., 2019; Laurençon et al., 2022), removing malformed text via simple text statistics like in the case of OSCAR (Abadji et al., 2022) or through deduplication, studied extensively by Lee et al. (2022). However, the generated artifacts still tend to contain a multitude of worrying phenomena, such as synthetic data (Dodge et al., 2021), private and copyrighted data (Huang et al., 2022) or incorrect language codes and translations (Kreutzer et al., 2022). A lack of representation of diversity and socio-cultural and socio-economic biases constitute another big challenge of Common Crawl and datasets derived from it (Bender et al.; Blodgett et al., 2020; Field et al., 2021; Stanczak and Augenstein, 2021; Beaulieu and Leonelli, 2021).

Aware of the mounting problems with training data for modern LLMs, and appreciating the value of data exploration for better modeling in general, we focus our current work on building tools that can facilitate the qualitative analysis of NLP datasets. We propose to leverage the extensive experience of the Information Retrieval community in build-

<sup>1</sup><https://commoncrawl.org/>




Figure 1: The user interface of GAIA Search.

ing relevance-based search indices for large-scale document collections and put it into practice in the context of NLP data exploration work. We follow with a demonstration of ways in which the interoperability between Pyserini (Lin et al., 2021), a leading toolkit for reproducible IR research on one side, and Hugging Face<sup>2</sup>, a platform for open AI research on the other, can be leveraged to build tools for easy and effective analysis of textual data. To facilitate the adoption of the proposed methods we provide a collection of Jupyter Notebooks with step-by-step explanations of explored functionalities available at [github.com/huggingface/gaia/tree/main/notebooks](https://github.com/huggingface/gaia/tree/main/notebooks).

Finally, we release GAIA—a simple, yet powerful search engine giving relevance-based interface to four popular, large-scale, textual datasets, namely C4 (Raffel et al., 2020), the Pile (Gao et al., 2021; Biderman et al., 2022), ROOTS (Laurençon et al., 2022) and captions from LAION-2B-en (Schuhmann et al., 2022). All considered datasets rely to a big extent on data mined from Common Crawl. GAIA benefits from the interoperability between Pyserini and Hugging Face that

<sup>2</sup><https://huggingface.co/>

we discuss in the first part of the paper, while also constituting a standalone contribution which can benefit the NLP research community by making it easy to study leading corpora qualitatively. GAIA is available online at [hf.co/spaces/spacerini/gaia](https://hf.co/spaces/spacerini/gaia).

## 2 Background

The ability to analyze large collections of textual data is core in multiple research and engineering disciplines. While the industrial standard is to rely on robust, scalable database and data analytics infrastructure, in the research environment, we typically resort to more local, granular and flexible, if ad-hoc, solutions which leverage toolkits such as NumPy (Harris et al., 2020), Pandas (pandas development team, 2020; Wes McKinney, 2010), SciPy (Virtanen et al., 2020) and others. A common research approach to data analytics involves using one of the aforementioned packages in combination with Jupyter Notebooks<sup>3</sup>. Notebooks make it easy to deploy and share analyses, however, typically they remain essentially non-interactive, requiring

<sup>3</sup><https://jupyter.org/>

Dataset	Reference	Hugging Face Hub link	# docs	# snippets	Data Size	Index Size
C4	Raffel et al. (2020)	c4	365M	1,587M	829GB	1.3TB
The Pile	Gao et al. (2021)	the_pile_deduplicated	134M	673M	825GB	1.2TB
ROOTS	Laurençon et al. (2022)	bigscience-data	598M	2,171M	1.6TB	2.6TB
LAION	Schuhmann et al. (2022)	laion2B-en	2,322M	1,351M	503GB	446GB
Total			3,419M	5,782M	3.76 TB	5.55TB

Table 1: Datasets included in the GAIA Search tool. All numbers refer to the size of the train split of the data.

at least a basic understanding of programming to be able to work with them efficiently. With the commodification of AI, and NLP in particular, and the expansion of NLP technologies into research areas beyond AI (Yang et al., 2022; Smith et al., 2015; Bhardwaj et al., 2017; Niezni et al., 2022), the need for easy to use, no-code tools for understanding AI artifacts arises. This need is partly addressed by Python packages such as Streamlit<sup>4</sup> and Gradio<sup>5</sup>, designed to facilitate the creation of interactive Machine Learning (ML) demos. As the authors of the Gradio white paper (Abid et al., 2019) point out, the accessibility and ease of use of the analysis tools is critical if we want to build an understanding of AI and trust in it. The Hugging Face Spaces platform, providing free hosting of both Streamlit, Gradio, and Docker-based applications, serves this exact purpose. However, it puts emphasis on demonstrating the capabilities of models while paying less attention to the datasets used to train them.

Even more so than in NLP, the evaluation of IR systems is heavily dependent on the implementation details of the retrieval systems serving the search indices being evaluated. The lack of standardisation of IR evaluation was the main motivator behind creating Anserini (Yang et al., 2017), a Lucene<sup>6</sup>-based toolkit for reproducible IR research, and the follow-up Pyserini (Lin et al., 2021)—a convenient Python API to the underlying Java-based implementation of Anserini. While it is relatively easy to build and serve search indices backed by Pyserini and Lucene, the task of building and deploying interactive user interfaces generally comes with a higher engineering barrier of entry.

Relevance-based search interfaces have been previously explored in the context of NLP—e.g. in the C4 (Raffel et al., 2020) analysis (Dodge et al., 2021), in COVID-related datasets (Zhang et al., 2020) or in news quotes (Vuković et al., 2022).

<sup>4</sup><https://streamlit.io/>

<sup>5</sup><https://gradio.app/>

<sup>6</sup><https://lucene.apache.org/>

Rather than focusing only on providing finished artifacts, however, we intend our current work to serve as a reference and inspiration for NLP researchers looking to develop and deploy similar applications by themselves.

We attempt to bring together the power of Pyserini-backed retrieval and the agility of ML demo development within the Hugging Face ecosystem to serve the goal of building intuitive data exploration tools. We believe that resulting applications will make a great difference for NLP researchers trying to study their data qualitatively, as well as to non-technical researchers looking for tools allowing them to perform dataset analysis in a no-code fashion. We propose our search engine GAIA as a compelling case in point.

### 3 Pyserini and Hugging Face: From Data to Search

In the current section we discuss core components which need to be considered when building a search application for textual datasets. We focus on how each step can be facilitated by the use of Pyserini, Hugging Face, or a combination of the two. We also provide hands-on tutorials covering basic concepts and search engine building blocks such as [data loading and indexing](#), [tokenization](#), [search](#), and [index analysis](#). We further release the [pre-processing](#), [backend](#) and [frontend code](#) that allowed us to index 3.5 billion documents—chunked into 5.8 billion snippets—and serve 5.55TB worth of BM25 indexes.

#### 3.1 Data Access

The Hugging Face hub is the repository of over 20,000 datasets from across AI domains. This includes the most popular large-scale text corpora in NLP—for example all the datasets we consider in GAIA (see Table 1 for details), but also other popular large scale text datasets such as OS-CAR (Abadji et al., 2022) and The Stack (Kocetkov et al., 2022) among many others. Each dataset

hosted on the Hub can be accessed locally using the datasets (Lhoest et al., 2021) library which provides convenient and parallelizable APIs for downloading and processing the data. Memory-mapping is supported by default and uses the efficient an Apache Arrow format,<sup>7</sup> making it possible to seamlessly handle datasets surpassing the RAM constraints of a given machine. Datasets also provide a streaming functionality which dispenses of downloading data to disk, making it possible to work with larger-than-disk datasets.

### 3.2 Tokenization

Tokenization is a crucial pre-processing step in NLP in general, and Information Retrieval in particular. In the context of IR, this process typically includes removing stop words, stemming, lemmatization, and removing non-alphanumeric characters. By default, Pyserini uses Lucene analyzers—heuristics-based algorithms designed for various languages and use cases, to tokenize text. The drawback of this approach is that only some languages have dedicated analyzers, while others have to resort to simply breaking on whitespace, which inadvertently leads to suboptimal performance.

An alternative to whitespace tokenization that has shown promise in Information Retrieval and is a mainstay in NLP is subword tokenization (Mielke et al., 2021), a process which splits words into smaller units based on their frequency in the corpus. Hugging Face provides a range of tokenizers that are specifically designed to work with its pre-trained transformer language models, as well as the means to train such tokenizers (MOI et al., 2022).

As of recently, Pyserini can leverage Hugging Face pre-trained subword tokenizers to improve indexing and searching for multiple languages. Pre-trained tokenizers from Hugging Face can serve as drop-in replacements for Lucene Analyzers, improving retrieval effectiveness, particularly in low-resource languages (Ogundepo et al., 2022). This interoperability between Hugging Face and Pyserini makes it easy for researchers to incorporate deep learning-based language models into their information retrieval workflows and opens up new avenues for research in the field.

### 3.3 Building the Index

Indexing constitutes the core functionality of Pyserini. The library enables experiments with bag-of-

<sup>7</sup><https://arrow.apache.org/>

words sparse retrieval using Lucene, and dense vector retrieval using Faiss (Johnson et al., 2019), as well as hybrid retrieval combining the two. Though this project focuses solely on sparse retrieval using BM25 indexes, Pyserini’s dense encoding and retrieval API would make it very easy to adapt all examples and demos to this paradigm.

**Offline Indexing.** Arrow-backed Hugging Face datasets readily lend themselves to being indexed by Pyserini’s standard Lucene indexer. In principle, one can build an index of a Hugging Face dataset simply by downloading it locally and then passing the file path to the Pyserini indexer via a command line argument. The scenario where a pre-processing step is required in between the data download and the indexing step—as with document segmentation which we discuss later in Section 4—can be realised straightforwardly for smaller datasets, which fit both on disk and into RAM. The larger-than-RAM datasets which fit on disk, can be easily sharded into any of the disk text formats supported by Pyserini (those include CSV, TSV, JSON, and JSONL) and processed concurrently within RAM limits to be then passed to the indexer.

**Datasets Streaming.** As of recently, it is also possible to index datasets which don’t fit on disk.<sup>8</sup> This new addition to Pyserini—one that resulted out of our current collaboration—allows users to stream text into the index directly—in other words, build an index on the fly from a text stream rather than from a static file saved on disk. As a result, larger-than-disk collections can be streamed from the Hugging Face Hub directly into the local indexing process. Data streaming can also improve experimental agility for smaller datasets, by removing the data downloads step from the Hugging Face dataset—Pyserini index pipeline.

### 3.4 Backend: Custom Pyserini Server

Once the data index is ready we need a way to host it and serve the search functionality to the clients. We propose a simple Python-based, Pyserini server implementation for GAIA, which can be easily generalized to other use-cases. The server code can be accessed [on GitHub](#).

<sup>8</sup>Note however, that the resulting index does have to fit on disk. As a result, we envision this functionality to be particularly convenient for scenarios where either the dataset or the index may be able to fit on disk, but both do not—a common scenario when dealing with TB-scale artefacts.

### 3.5 Frontend: Interactive Demos

Providing interactive demos which enable the exploration of AI artifacts is crucial in order to be able to collaborate across research disciplines and share results with colleagues without imposing the burden of setting up their own engineering stack on them. By offering the hosting of Gradio and Streamlit applications Hugging Face Spaces meet this need perfectly. We encourage readers to follow the implementations of GAIA for an example of how to build a simple UI for a search tool.

## 4 Case Study: GAIA Search

Relevance-based search tools have the potential of the largest impact on massive-scale datasets, common in modern NLP. Unlike with smaller data collections, where simpler investigation strategies, e.g. via a combination of Pandas and Jupyter Notebooks, may be feasible, huge datasets are generally too cumbersome to process this way. A big benefit of search engines in the form that we propose is also the fact that after being set up, they require no engineering skills or extensive computing resources to operate, expanding the community of potential users. We demonstrate this with GAIA search, available online at [hf.co/spaces/spacerini/gaia](https://hf.co/spaces/spacerini/gaia).

### 4.1 Included Datasets

GAIA proposes a simple interface to four large-scale textual datasets—C4, The Pile, ROOTS, and captions from LAION-2B-en. The reader may consult Table 1 for details on respective datasets. All of the datasets included in GAIA are sourced at least partly from Common Crawl. The users of the tool are therefore bound by the Common Crawl terms of use<sup>9</sup> in respect of the content contained in the datasets. Additionally, in order to respect the data subjects’ rights (Jernite et al., 2022) we refrain from presenting full documents in the tool, and instead include snippets of at most 256 words. We redact the personally identifiable information (PII) on all search results on the backend side, using the PII redaction script open-sourced alongside the BigScience<sup>10</sup> language model BLOOM (Le Scao et al., 2022). Below we discuss details of the respective datasets’ pre-processing.

<sup>9</sup><https://commoncrawl.org/terms-of-use/>

<sup>10</sup>[bigscience.huggingface.co](https://bigscience.huggingface.co)

**C4.** This is a dataset fully sourced from Common Crawl. We index the variant of the English split of the dataset [available on the Hugging Face hub](#). C4 has been used to train T5 (Raffel et al., 2020), a major seq-2-seq model with a plethora of downstream applications, parts of it have also contributed to the training of other LLMs, e.g. LaMDA (Thoppilan et al., 2022) and Chinchilla (Hoffmann et al., 2022), which makes it a compelling dataset to study.

**The Pile.** This corpus has been a standard dataset for many English LLM releases from various organizations (Biderman et al., 2023; Black et al., 2021; Wang and Komatsuzaki, 2021; Black et al., 2022; Smith et al., 2022; Tang, 2021; Zhang et al., 2022; Lieber et al., 2021), so we believe that it is important to expose its contents to public view. The Pile is an English-only corpus containing multiple sub-corpora from various sources (Biderman et al., 2022). We use a variant of The Pile which has been deduplicated with MinhashLSH and a threshold of 0.87, following the advice of Lee et al. (2022). Notably, this variant of the Pile has also been used to train an LLMs (Biderman et al., 2023). We hope that providing the search interface will allow further investigation of the subjective differences between deduplicated and unprocessed corpora. Both [the canonical variant of The Pile](#) and its [deduplicated counterpart](#) are available on the Hugging Face Hub.

**ROOTS.** Developed for the purpose of training BLOOM (Le Scao et al., 2022), this is the only multilingual dataset available in GAIA. We therefore, create independent indices for each language or language group provided in the corpus, resulting in 13 separate indices—Arabic, Catalan, Code (comprising all programming languages included in the corpus), English, Spanish, Basque, French, Indonesian, Indic and Niger-Congo (language groups), Portuguese, Vietnamese and Chinese. We return results for each index when issuing queries in the tool.

**LAION-2B-en** LAION is a dataset of [image caption, image URL] pairs scraped from the Web. It has been used to train Stable Diffusion (Rombach et al., 2021), a textual-prompt-based image generation model, constituting an open-source counterpart to OpenAI’s DALL·E 2 (Ramesh et al., 2022). We use LAION-2B-en, the subset of the original dataset with captions in English, as the starting point for further pre-processing. We start by dedu-

plicating captions, which yields clusters of image URLs with identical captions (deduplication code is available on [GitHub](#)). We then index unique captions. For textual queries to our tool, we return results consisting of the relevant captions. Alongside each result, we include the list of associated image URLs.

## 4.2 Implementation and Functionality

The implementation of GAIA makes use of a variety of interoperability features we've discussed in Section 3. As detailed in Table 1, all of the considered datasets are available on the Hugging Face Hub. We download and segment them locally. Such segmented datasets are then provided as input to a Pyserini indexer. We leverage Streamlit to build the user interface for our tool and host it on Hugging Face Spaces. On the backend side, the indices are served from Hugging Face provisioned machines. We open-source helper functions for segmenting long documents and the backend server code at [github.com/huggingface/gaia](https://github.com/huggingface/gaia).

## 5 Limitations and Future Plans

A major area for consideration when developing data access tools is that of data governance, privacy and data ownership (Jernite et al., 2022; Carlini et al., 2020). In our current work we focus on the technical aspects of giving access to large data collections, however, we urge users to consider data governance principles when designing their own tools. In terms of the infrastructure, the cost and complexity of hosting the retrieval index falls on the creator of the tool, which can be easy to manage for small datasets but becomes more problematic when entering the realm of TB-scale corpora. We are currently investigating a parallel workstream that could address this limitation at least partly.

## 6 Conclusions

We showcase interoperability between Hugging Face and Pyserini and provide value to the NLP community by demonstrating easy ways to perform high-quality, large-scale retrieval with open-source tools. We also introduce GAIA - a search engine for retrieval-based exploration of four major textual datasets. We wish to encourage NLP and IR practitioners to follow our examples and build their own tools to explore both large and smaller-scale textual datasets.

## 7 Acknowledgements

Authors would like to thank Carlos Muñoz Ferlandis, Daniel van Strien, Katie Link and Quentin Lhoest for valuable tips and suggestions. This research was also supported in part by the Natural Sciences and Engineering Research Council (NSERC) of Canada.

## 8 Impact Statement

As mentioned in Section 5, accessing large-scale, web-scraped textual corpora comes with a variety of ethical considerations, pertaining to the protection of rights of the data owners and people whose privacy or copyright might be infringed upon. We introduce guardrails, namely the PII redaction and the segmentation of documents into short snippets, preventing the ability to reconstruct full documents or full corpora, into the GAIA Search design. We strongly encourage researchers aiming to build similar tools to do the same. Overall, a lot of these problems seem to occur because we're proposing the tool only after the datasets have been created and models trained on them. The workflow we envision for future research projects would involve building data exploration tools prior to the release of the datasets, so that core problems can be observed, studied and addressed before datasets reach an external audience.

## References

- Julien Abadji, Pedro Ortiz Suarez, Laurent Romary, and Benoît Sagot. 2022. [Towards a cleaner document-oriented multilingual crawled corpus](#). In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 4344–4355, Marseille, France. European Language Resources Association.
- Abubakar Abid, Ali Abdalla, Ali Abid, Dawood Khan, Abdulrahman Alfozan, and James Zou. 2019. [Gradio: Hassle-free sharing and testing of ml models in the wild](#).
- Anne Beaulieu and Sabina Leonelli. 2021. *Data and Society: A Critical Introduction*. Sage.
- Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. On the dangers of stochastic parrots: Can language models be too big?, year = 2021, isbn = 9781450383097, publisher = Association for Computing Machinery, address = New York, NY, USA, url = <https://doi.org/10.1145/3442188.3445922>, doi = 10.1145/3442188.3445922, abstract = The past 3 years of work in NLP have been characterized by the development and deployment of ever larger language

- models, especially for English. BERT, its variants, GPT-2/3, and others, most recently Switch-C, have pushed the boundaries of the possible both through architectural innovations and through sheer size. Using these pretrained models and the methodology of fine-tuning them for specific tasks, researchers have extended the state of the art on a wide array of tasks as measured by leaderboards on specific benchmarks for English. In this paper, we take a step back and ask: How big is too big? What are the possible risks associated with this technology and what paths are available for mitigating those risks? We provide recommendations including weighing the environmental and financial costs first, investing resources into curating and carefully documenting datasets rather than ingesting everything on the web, carrying out pre-development exercises evaluating how the planned approach fits into research and development goals and supports stakeholder values, and encouraging research directions beyond ever larger language models., booktitle = Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency, pages = 610–623, numpages = 14, location = Virtual Event, Canada, series = FAccT '21.
- Rohan Bhardwaj, Ankita R. Nambiar, and Debojyoti Dutta. 2017. [A study of machine learning in health-care](#). In *2017 IEEE 41st Annual Computer Software and Applications Conference (COMPSAC)*, volume 2, pages 236–241.
- Stella Biderman, Kieran Bicheno, and Leo Gao. 2022. [Datasheet for the pile](#). *CoRR*, abs/2201.07311.
- Stella Biderman, Hailey Schoelkopf, Quentin Anthony, Herbie Bradley, Kyle O’Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Aviya Skowron, Lintang Sutawika, and Oskar van der Wal. 2023. [Pythia: a scaling suite for language model interpretability research](#). *Computing Research Repository*. Version 1.
- Sid Black, Leo Gao, Phil Wang, Connor Leahy, and Stella Biderman. 2021. [GPT-Neo: Large scale autoregressive language modeling with Mesh-TensorFlow](#). *GitHub*.
- Sidney Black, Stella Biderman, Eric Hallahan, Quentin Anthony, Leo Gao, Laurence Golding, Horace He, Connor Leahy, Kyle McDonell, Jason Phang, et al. 2022. GPT-NeoX-20B: An open-source autoregressive language model. In *Proceedings of BigScience Episode #5–Workshop on Challenges & Perspectives in Creating Large Language Models*, pages 95–136.
- Su Lin Blodgett, Solon Barocas, Hal Daumé III, and Hanna Wallach. 2020. [Language \(Technology\) is Power: A Critical Survey of “Bias” in NLP](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5454–5476, Online. Association for Computational Linguistics.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners](#). In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.
- Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, Alina Oprea, and Colin Raffel. 2020. [Extracting Training Data from Large Language Models](#). *arXiv:2012.07805 [cs]*.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayanan Pilla, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. 2022. [Palm: Scaling language modeling with pathways](#).
- Jesse Dodge, Maarten Sap, Ana Marasović, William Agnew, Gabriel Ilharco, Dirk Groeneveld, Margaret Mitchell, and Matt Gardner. 2021. [Documenting Large Webtext Corpora: A Case Study on the Colossal Clean Crawled Corpus](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 1286–1305, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Anjalie Field, Su Lin Blodgett, Zeerak Waseem, and Yulia Tsvetkov. 2021. [A Survey of Race, Racism, and Anti-Racism in NLP](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1905–1925, Online. Association for Computational Linguistics.
- Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang,

- Horace He, Anish Thite, Noa Nabeshima, Shawn Presser, and Connor Leahy. 2021. [The pile: An 800gb dataset of diverse text for language modeling](#).
- Charles R. Harris, K. Jarrod Millman, Stéfan J. van der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J. Smith, Robert Kern, Matti Picus, Stephan Hoyer, Marten H. van Kerkwijk, Matthew Brett, Allan Haldane, Jaime Fernández del Río, Mark Wiebe, Pearu Peterson, Pierre Gérard-Marchant, Kevin Sheppard, Tyler Reddy, Warren Weckesser, Hameer Abbasi, Christoph Gohlke, and Travis E. Oliphant. 2020. [Array programming with NumPy](#). *Nature*, 585(7825):357–362.
- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals, and Laurent Sifre. 2022. [Training compute-optimal large language models](#).
- Jie Huang, Hanyin Shao, and Kevin Chen-Chuan Chang. 2022. [Are Large Pre-Trained Language Models Leaking Your Personal Information?](#)
- Yacine Jernite, Huu Nguyen, Stella Biderman, Anna Rogers, Maraim Masoud, Valentin Danchev, Samson Tan, Alexandra Sasha Luccioni, Nishant Subramani, Isaac Johnson, Gerard Dupont, Jesse Dodge, Kyle Lo, Zeerak Talat, Dragomir Radev, Aaron Gokaslan, Somaieh Nikpoor, Peter Henderson, Rishi Bommasani, and Margaret Mitchell. 2022. [Data governance in the age of large-scale data-driven language technology](#). In *2022 ACM Conference on Fairness, Accountability, and Transparency, FAccT '22*, page 2206–2222, New York, NY, USA. Association for Computing Machinery.
- Jeff Johnson, Matthijs Douze, and Hervé Jégou. 2019. Billion-scale similarity search with GPUs. *IEEE Transactions on Big Data*, 7(3):535–547.
- Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. [Scaling laws for neural language models](#).
- Denis Kocetkov, Raymond Li, Loubna Ben Allal, Jia Li, Chenghao Mou, Carlos Muñoz Ferrandis, Yacine Jernite, Margaret Mitchell, Sean Hughes, Thomas Wolf, Dzmitry Bahdanau, Leandro von Werra, and Harm de Vries. 2022. [The stack: 3 tb of permissively licensed source code](#).
- Julia Kreutzer, Isaac Caswell, Lisa Wang, Ahsan Wahab, Daan van Esch, Nasanbayar Ulzii-Orshikh, Allahsera Tapo, Nishant Subramani, Artem Sokolov, Claytone Sikasote, Monang Setyawan, Supheakmungkol Sarin, Sokhar Samb, Benoît Sagot, Clara Rivera, Annette Rios, Isabel Papadimitriou, Salomey Osei, Pedro Ortiz Suarez, Iroko Orife, Kelechi Ogueji, Andre Niyongabo Rubungo, Toan Q. Nguyen, Mathias Müller, André Müller, Shamsuddeen Hassan Muhammad, Nanda Muhammad, Ayanda Mnyakeni, Jamshidbek Mirzakhlov, Tapiwanashe Matangira, Colin Leong, Nze Lawson, Sneha Kudugunta, Yacine Jernite, Mathias Jenny, Orhan Firat, Bonaventure F. P. Dossou, Sakhile Dlamini, Nisansa de Silva, Sakine Çabuk Ballı, Stella Biderman, Alessia Battisti, Ahmed Baruwa, Ankur Bapna, Pallavi Baljekar, Israel Abebe Azime, Ayodele Awokoya, Duygu Ataman, Orevaoghene Ahia, Oghenefego Ahia, Sweta Agrawal, and Mofetoluwa Adeyemi. 2022. [Quality at a Glance: An Audit of Web-Crawled Multilingual Datasets](#). *Transactions of the Association for Computational Linguistics*, 10:50–72.
- Hugo Laurençon, Lucile Saulnier, Thomas Wang, Christopher Akiki, Albert Villanova del Moral, Teven Le Scao, Leandro Von Werra, Chenghao Mou, Eduardo González Ponferrada, Huu Nguyen, Jörg Froberg, Mario Šaško, Quentin Lhoest, Angelina McMillan-Major, Gérard Dupont, Stella Biderman, Anna Rogers, Loubna Ben allal, Francesco De Toni, Giada Pistilli, Olivier Nguyen, Somaieh Nikpoor, Maraim Masoud, Pierre Colombo, Javier de la Rosa, Paulo Villegas, Tristan Thrush, Shayne Longpre, Sebastian Nagel, Leon Weber, Manuel Romero Muñoz, Jian Zhu, Daniel Van Strien, Zaid Alyafeai, Khalid Almubarak, Vu Minh Chien, Itziar Gonzalez-Dios, Aitor Soroa, Kyle Lo, Manan Dey, Pedro Ortiz Suarez, Aaron Gokaslan, Shamik Bose, David Ifeoluwa Adelani, Long Phan, Hieu Tran, Ian Yu, Suhas Pai, Jenny Chim, Violette Lepercq, Suzana Ilic, Margaret Mitchell, Sasha Luccioni, and Yacine Jernite. 2022. [The bigscience ROOTS corpus: A 1.6TB composite multilingual dataset](#). In *Thirty-sixth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.
- Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, Matthias Gallé, Jonathan Tow, Alexander M. Rush, Stella Biderman, Albert Webson, Pawan Sasanka Ammanamanchi, Thomas Wang, Benoît Sagot, Niklas Muennighoff, Albert Villanova del Moral, Olatunji Ruwase, Rachel Bawden, Stas Bekman, Angelina McMillan-Major, Iz Beltagy, Huu Nguyen, Lucile Saulnier, Samson Tan, Pedro Ortiz Suarez, Victor Sanh, Hugo Laurençon, Yacine Jernite, Julien Launay, Margaret Mitchell, Colin Raffel, Aaron Gokaslan, Adi Simhi, Aitor Soroa, Alham Fikri Aji, Amit Alfassy, Anna Rogers, Ariel Kreisberg Nitzav, Canwen Xu, Chenghao Mou, Chris Emezue, Christopher Klamm, Colin Leong, Daniel van Strien, David Ifeoluwa Adelani, Dragomir Radev, Eduardo González Ponferrada, Efrat Levkovich, Ethan Kim, Eyal Bar Natan, Francesco De Toni, Gérard Dupont, Germán Kruszewski, Giada Pistilli, Hady Elsahar, Hamza Benyamina, Hieu Tran, Ian Yu, Idris Abdulmumin, Isaac Johnson, Itziar Gonzalez-Dios,



Javier de la Rosa, Jenny Chim, Jesse Dodge, Jian Zhu, Jonathan Chang, Jörg Froberg, Joseph Tobing, Joydeep Bhattacharjee, Khalid Almubarak, Kimbo Chen, Kyle Lo, Leandro Von Werra, Leon Weber, Long Phan, Loubna Ben allal, Ludovic Tanguy, Manan Dey, Manuel Romero Muñoz, Maraim Masoud, María Grandury, Mario Šaško, Max Huang, Maximin Coavoux, Mayank Singh, Mike Tian-Jian Jiang, Minh Chien Vu, Mohammad A. Jauhar, Mustafa Ghaleb, Nishant Subramani, Nora Kassner, Nuru-laqilla Khamis, Olivier Nguyen, Omar Espejel, Ona de Gibert, Paulo Villegas, Peter Henderson, Pierre Colombo, Priscilla Amuok, Quentin Lhoest, Rheza Harliman, Rishi Bommasani, Roberto Luis López, Rui Ribeiro, Salomey Osei, Sampo Pyysalo, Sebastian Nagel, Shamik Bose, Shamsuddeen Hassan Muhammad, Shanya Sharma, Shayne Longpre, So-maieh Nikpoor, Stanislav Silberberg, Suhas Pai, Sydney Zink, Tiago Timponi Torrent, Timo Schick, Tristan Thrush, Valentin Danchev, Vassilina Nikoulina, Veronika Laippala, Violette Lepercq, Vrinda Prabhu, Zaid Alyafeai, Zeerak Talat, Arun Raja, Benjamin Heinzerling, Chenglei Si, Davut Emre Taşar, Elizabeth Salesky, Sabrina J. Mielke, Wilson Y. Lee, Abheesht Sharma, Andrea Santilli, Antoine Chaffin, Arnaud Stiegler, Debajyoti Datta, Eliza Szczechla, Gunjan Chhablani, Han Wang, Harshit Pandey, Hendrik Strobelt, Jason Alan Fries, Jos Rozen, Leo Gao, Lintang Sutawika, M. Saiful Bari, Maged S. Al-shaibani, Matteo Manica, Nihal Nayak, Ryan Teehan, Samuel Albanie, Sheng Shen, Srulik Ben-David, Stephen H. Bach, Taewoon Kim, Tali Bers, Thibault Fevry, Trishala Neeraj, Urmish Thakker, Vikas Raunak, Xiangru Tang, Zheng-Xin Yong, Zhiqing Sun, Shaked Brody, Yallow Uri, Hadar Tojarieh, Adam Roberts, Hyung Won Chung, Jaesung Tae, Jason Phang, Ofir Press, Conglong Li, Deepak Narayanan, Hatim Bourfoune, Jared Casper, Jeff Rasley, Max Ryabinin, Mayank Mishra, Minjia Zhang, Mohammad Shoeybi, Myriam Peyrounette, Nicolas Patry, Nouamane Tazi, Omar Sanseviero, Patrick von Platen, Pierre Cornette, Pierre François Lavallée, Rémi Lacroix, Samyam Rajbhandari, Sanjit Gandhi, Shaden Smith, Stéphane Requery, Suraj Patil, Tim Dettmers, Ahmed Baruwa, Amanpreet Singh, Anastasia Cheveleva, Anne-Laure Ligozat, Arjun Subramonian, Aurélie Névél, Charles Lovering, Dan Garrette, Deepak Tunuguntla, Ehud Reiter, Ekaterina Taktasheva, Ekaterina Voloshina, Eli Bogdanov, Genta Indra Winata, Hailey Schoelkopf, Jan-Christoph Kalo, Jekaterina Novikova, Jessica Zosa Forde, Jordan Clive, Jungo Kasai, Ken Kawamura, Liam Hazan, Marine Carpuat, Miruna Clinciu, Nadjoung Kim, Newton Cheng, Oleg Serikov, Omer Antverg, Oskar van der Wal, Rui Zhang, Ruo Chen Zhang, Sebastian Gehrmann, Shachar Mirkin, Shani Pais, Tatiana Shavrina, Thomas Scialom, Tian Yun, Tomasz Limisiewicz, Verena Rieser, Vitaly Protasov, Vladislav Mikhailov, Yada Pruksachatkun, Yonatan Belinkov, Zachary Bamberger, Zdeněk Kasner, Alice Rueda, Amanda Pestana, Amir Feizpour, Ammar Khan, Amy Faranak, Ana Santos, Anthony Hevia, Antigona Unldreaj, Arash Aghagol, Are-

zoo Abdollahi, Aycha Tammour, Azadeh HajiHosseini, Bahareh Behroozi, Benjamin Ajibade, Bharat Saxena, Carlos Muñoz Ferrandis, Danish Contractor, David Lansky, Davis David, Douwe Kiela, Duong A. Nguyen, Edward Tan, Emi Baylor, Ezinwanne Ozoani, Fatima Mirza, Frankline Onon-iwu, Habib Rezanejad, Hessie Jones, Indrani Bhat-tacharya, Irene Solaiman, Irina Sedenko, Isar Ne-jadgholi, Jesse Passmore, Josh Seltzer, Julio Bonis Sanz, Livia Dutra, Mairon Samagaio, Maraim El-badri, Margot Mieskes, Marissa Gerchick, Martha Akinlolu, Michael McKenna, Mike Qiu, Muhammed Ghauri, Mykola Burynok, Nafis Abrar, Nazneen Ra-jani, Nour Elkott, Nour Fahmy, Olanrewaju Samuel, Ran An, Rasmus Kromann, Ryan Hao, Samira Al-izadeh, Sarmad Shubber, Silas Wang, Sourav Roy, Sylvain Viguier, Thanh Le, Tobi Oyebade, Trieu Le, Yoyo Yang, Zach Nguyen, Abhinav Ramesh Kashyap, Alfredo Palasciano, Alison Callahan, Anima Shukla, Antonio Miranda-Escalada, Ayush Singh, Benjamin Beilharz, Bo Wang, Caio Brito, Chenxi Zhou, Chirag Jain, Chuxin Xu, Clémentine Fourrier, Daniel León Periñán, Daniel Molano, Dian Yu, Enrique Manjavacas, Fabio Barth, Florian Fuhrmann, Gabriel Altay, Giyaseddin Bayrak, Gully Burns, Helena U. Vrabec, Imane Bello, Ishani Dash, Jihyun Kang, John Giorgi, Jonas Golde, Jose David Posada, Karthik Rangasai Sivaraman, Lokesh Bulchandani, Lu Liu, Luisa Shinzato, Madeleine Hahn de Bykhovetz, Maiko Takeuchi, Marc Pàmies, Maria A. Castillo, Mari-anna Nezhurina, Mario Sängner, Matthias Samwald, Michael Cullan, Michael Weinberg, Michiel De Wolf, Mina Mihaljcic, Minna Liu, Moritz Freidank, Myung-sun Kang, Natasha Seelam, Nathan Dahlberg, Nicholas Michio Broad, Nikolaus Muellner, Pascale Fung, Patrick Haller, Ramya Chandrasekhar, Renata Eisenberg, Robert Martin, Rodrigo Canalli, Rosaline Su, Ruisi Su, Samuel Cahyawijaya, Samuele Garda, Shlok S. Deshmukh, Shubhanshu Mishra, Sid Ki-blawi, Simon Ott, Sinee Sang-aoonsiri, Srishti Ku-mar, Stefan Schweter, Sushil Bharati, Tanmay Laud, Théo Gigant, Tomoya Kainuma, Wojciech Kusa, Yanis Labrak, Yash Shailesh Bajaj, Yash Venkatraman, Yifan Xu, Yingxin Xu, Yu Xu, Zhe Tan, Zhongli Xie, Zifan Ye, Mathilde Bras, Younes Belkada, and Thomas Wolf. 2022. [BLOOM: A 176B-Parameter Open-Access Multilingual Language Model](#). In *Thirty-Sixth Conference on Neural Information Processing Systems*, New Orleans, Louisiana. arXiv.

Katherine Lee, Daphne Ippolito, Andrew Nystrom, Chiyuan Zhang, Douglas Eck, Chris Callison-Burch, and Nicholas Carlini. 2022. [Deduplicating training data makes language models better](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8424–8445, Dublin, Ireland. Association for Computational Linguistics.

Quentin Lhoest, Albert Villanova del Moral, Yacine Jernite, Abhishek Thakur, Patrick von Platen, Suraj Patil, Julien Chaumond, Mariama Drame, Julien Plu, Lewis Tunstall, Joe Davison, Mario Šaško, Gunjan Chhablani, Bhavitvya Malik, Simon Brandeis,

- Teven Le Scao, Victor Sanh, Canwen Xu, Nicolas Patry, Angelina McMillan-Major, Philipp Schmid, Sylvain Gugger, Clément Delangue, Théo Matussière, Lysandre Debut, Stas Bekman, Pierric Cistac, Thibault Goehringer, Victor Mustar, François Lagunas, Alexander Rush, and Thomas Wolf. 2021. [Datasets: A community library for natural language processing](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 175–184, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Opher Lieber, Or Sharir, Barak Lenz, and Yoav Shoham. 2021. Jurassic-1: Technical details and evaluation. Technical report, AI21 Labs.
- Jimmy Lin, Xueguang Ma, Sheng-Chieh Lin, Jheng-Hong Yang, Ronak Pradeep, and Rodrigo Nogueira. 2021. Pyserini: A Python toolkit for reproducible information retrieval research with sparse and dense representations. In *Proceedings of the 44th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR 2021)*, pages 2356–2362.
- Alexandra Luccioni and Joseph Viviano. 2021. [What’s in the box? an analysis of undesirable content in the Common Crawl corpus](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pages 182–189, Online. Association for Computational Linguistics.
- Sabrina J. Mielke, Zaid Alyafeai, Elizabeth Salesky, Colin Raffel, Manan Dey, Matthias Gallé, Arun Raja, Chenglei Si, Wilson Y. Lee, Benoît Sagot, and Samson Tan. 2021. Between words and characters: A brief history of open-vocabulary modeling and tokenization in nlp. *ArXiv*, abs/2112.10508.
- Anthony MOI, Nicolas Patry, Pierric Cistac, Pete, Fun-towicz Morgan, Sebastian Pütz, Mishig, Bjarte Johansen, Thomas Wolf, Sylvain Gugger, Clement, Julien Chaumond, Lysandre Debut, François Garillot, Luc Georges, dcelus, JC Louis, MarcusGrass, Taufiqzaman Peyash, 0xflotus, Alan deLevie, Alexander Mamaev, Arthur, Cameron, Colin Clement, Dagmawi Moges, David Hewitt, Denis Zolotukhin, and Geoffrey Thomas. 2022. [huggingface/tokenizers: Rust 0.13.2](#).
- Danna Niezni, Hillel Taub-Tabib, Yuval Harris, Hagit Sason-Bauer, Yakir Amrusi, Dana Azagury, Maytal Avrashami, Shaked Launer-Wachs, Jon Borchardt, M Kusold, Aryeh Tiktinsky, Tom Hope, Yoav Goldberg, and Yosi Shamay. 2022. [Extending the boundaries of cancer therapeutic complexity with literature data mining](#). *bioRxiv*.
- Odunayo Ogundepo, Xinyu Zhang, and Jimmy Lin. 2022. [Better than whitespace: Information retrieval for languages without custom tokenizers](#).
- The pandas development team. 2020. [pandas-dev/pandas: Pandas](#).
- Jack W. Rae, Sebastian Borgeaud, Trevor Cai, Katie Millican, Jordan Hoffmann, Francis Song, John Aslanides, Sarah Henderson, Roman Ring, Susannah Young, Eliza Rutherford, Tom Hennigan, Jacob Menick, Albin Cassirer, Richard Powell, George van den Driessche, Lisa Anne Hendricks, Mari-beth Rauh, Po-Sen Huang, Amelia Glaese, Johannes Welbl, Sumanth Dathathri, Saffron Huang, Jonathan Uesato, John F. J. Mellor, Irina Higgins, Antonia Creswell, Nathan McAleese, Amy Wu, Erich Elsen, Siddhant M. Jayakumar, Elena Buchatskaya, David Budden, Esme Sutherland, Karen Simonyan, Michela Paganini, L. Sifre, Lena Martens, Xiang Lorraine Li, Adhiguna Kuncoro, Aida Nematzadeh, Elena Gribovskaya, Domenic Donato, Angeliki Lazaridou, Arthur Mensch, Jean-Baptiste Lespiau, Maria Tsim-poukelli, N. K. Grigorev, Doug Fritz, Thibault Sottiaux, Mantas Pajarskas, Tobias Pohlen, Zhitao Gong, Daniel Toyama, Cyprien de Masson d’Autume, Yujia Li, Tayfun Terzi, Vladimir Mikulik, Igor Babuschkin, Aidan Clark, Diego de Las Casas, Aurelia Guy, Chris Jones, James Bradbury, Matthew G. Johnson, Blake A. Hechtman, Laura Weidinger, Iason Gabriel, William S. Isaac, Edward Lockhart, Simon Osindero, Laura Rimell, Chris Dyer, Oriol Vinyals, Kareem W. Ayoub, Jeff Stanway, L. L. Bennett, Demis Hassabis, Koray Kavukcuoglu, and Geoffrey Irving. 2021. Scaling language models: Methods, analysis & insights from training gopher. *ArXiv*, abs/2112.11446.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(1).
- Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. 2022. [Hierarchical text-conditional image generation with clip latents](#).
- Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. 2021. [High-resolution image synthesis with latent diffusion models](#).
- Christoph Schuhmann, Romain Beaumont, Richard Vencu, Cade Gordon, Ross Wightman, Mehdi Cherti, Theo Coombes, Aarush Katta, Clayton Mullis, Mitchell Wortsman, Patrick Schramowski, Srivatsa Kundurthy, Katherine Crowson, Ludwig Schmidt, Robert Kaczmarczyk, and Jenia Jitsev. 2022. [Laion-5b: An open large-scale dataset for training next generation image-text models](#).
- David A. Smith, Ryan Cordell, and Abby Mullen. 2015. [Computational Methods for Uncovering Reprinted Texts in Antebellum Newspapers](#). *American Literary History*, 27(3):E1–E15.
- Shaden Smith, Mostofa Patwary, Brandon Norick, Patrick LeGresley, Samyam Rajbhandari, Jared Casper, Zhun Liu, Shrimai Prabhumoye, George

- Zerveas, Vijay Korthikanti, Elton Zhang, Rewon Child, Reza Yazdani Aminabadi, Julie Bernauer, Xia Song, Mohammad Shoeybi, Yuxiong He, Michael Houston, Saurabh Tiwary, and Bryan Catanzaro. 2022. [Using deepspeed and megatron to train megatron-turing nlq 530b, a large-scale generative language model.](#)
- Karolina Stanczak and Isabelle Augenstein. 2021. [A Survey on Gender Bias in Natural Language Processing.](#)
- Jie Tang. 2021. WuDao: Pretrain the world. Keynote address at the European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases.
- Romal Thoppilan, Daniel De Freitas, Jamie Hall, Noam Shazeer, Apoorv Kulshreshtha, Heng-Tze Cheng, Alicia Jin, Taylor Bos, Leslie Baker, Yu Du, YaGuang Li, Hongrae Lee, Huaixiu Steven Zheng, Amin Ghafouri, Marcelo Menegali, Yanping Huang, Maxim Krikun, Dmitry Lepikhin, James Qin, Dehao Chen, Yuanzhong Xu, Zhifeng Chen, Adam Roberts, Maarten Bosma, Vincent Zhao, Yanqi Zhou, Chung-Ching Chang, Igor Krivokon, Will Rusch, Marc Pickett, Pranesh Srinivasan, Laichee Man, Kathleen Meier-Hellstern, Meredith Ringel Morris, Tulsee Doshi, Renelito Delos Santos, Toju Duke, Johnny Soraker, Ben Zevenbergen, Vinodkumar Prabhakaran, Mark Diaz, Ben Hutchinson, Kristen Olson, Alejandra Molina, Erin Hoffman-John, Josh Lee, Lora Aroyo, Ravi Rajakumar, Alena Butryna, Matthew Lamm, Viktoriya Kuzmina, Joe Fenton, Aaron Cohen, Rachel Bernstein, Ray Kurzweil, Blaise Aguerre-Arcas, Claire Cui, Marian Croak, Ed Chi, and Quoc Le. 2022. [Lamda: Language models for dialog applications.](#)
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. [Llama: Open and efficient foundation language models.](#)
- Pauli Virtanen, Ralf Gommers, Travis E. Oliphant, Matt Haberland, Tyler Reddy, David Cournapeau, Evgeni Burovski, Pearu Peterson, Warren Weckesser, Jonathan Bright, Stéfan J. van der Walt, Matthew Brett, Joshua Wilson, K. Jarrod Millman, Nikolay Mayorov, Andrew R. J. Nelson, Eric Jones, Robert Kern, Eric Larson, C J Carey, İlhan Polat, Yu Feng, Eric W. Moore, Jake VanderPlas, Denis Laxalde, Josef Perktold, Robert Cimrman, Ian Henriksen, E. A. Quintero, Charles R. Harris, Anne M. Archibald, Antônio H. Ribeiro, Fabian Pedregosa, Paul van Mulbregt, and SciPy 1.0 Contributors. 2020. [SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python.](#) *Nature Methods*, 17:261–272.
- Vuk Vuković, Akhil Arora, Huan-Cheng Chang, Andreas Spitz, and Robert West. 2022. [Quote erat demonstrandum: A web interface for exploring the quotebank corpus.](#) In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval.* ACM.
- Ben Wang and Aran Komatsuzaki. 2021. GPT-J-6B: A 6 billion parameter autoregressive language model.
- Guillaume Wenzek, Marie-Anne Lachaux, Alexis Conneau, Vishrav Chaudhary, Francisco Guzmán, Armand Joulin, and Edouard Grave. 2019. [Ccnnet: Extracting high quality monolingual datasets from web crawl data.](#)
- Wes McKinney. 2010. [Data Structures for Statistical Computing in Python.](#) In *Proceedings of the 9th Python in Science Conference*, pages 56 – 61.
- Peilin Yang, Hui Fang, and Jimmy Lin. 2017. [Anserini: Enabling the use of lucene for information retrieval research.](#) In *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR '17*, page 1253–1256, New York, NY, USA. Association for Computing Machinery.
- Xi Yang, Aokun Chen, Nima PourNejatian, Hoo Chang Shin, Kaleb E Smith, Christopher Parisien, Colin Compas, Cheryl Martin, Mona G Flores, Ying Zhang, Tanja Magoc, Christopher A Harle, Gloria Lipori, Duane A Mitchell, William R Hogan, Elizabeth A Shenkman, Jiang Bian, and Yonghui Wu. 2022. [Gatortron: A large clinical language model to unlock patient information from unstructured electronic health records.](#)
- Edwin Zhang, Nikhil Gupta, Raphael Tang, Xiao Han, Ronak Pradeep, Kuang Lu, Yue Zhang, Rodrigo Nogueira, Kyunghyun Cho, Hui Fang, and Jimmy Lin. 2020. [Covidex: Neural ranking models and keyword search infrastructure for the COVID-19 open research dataset.](#) In *Proceedings of the First Workshop on Scholarly Document Processing*, pages 31–41, Online. Association for Computational Linguistics.
- Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, Todor Mihaylov, Myle Ott, Sam Shleifer, Kurt Shuster, Daniel Simig, Punit Singh Koura, Anjali Sridhar, Tianlu Wang, and Luke Zettlemoyer. 2022. [Opt: Open pre-trained transformer language models.](#)