# HealthCards: Exploring Text-to-Image Generation as Visual Aids for Healthcare Knowledge Democratizing and Education

Qian Wu<sup>1</sup> Zheyao Gao<sup>1</sup> Longfei Gou<sup>2</sup> Yifan Hou<sup>3</sup> Ann Sin Nga Lau<sup>1</sup> Qi Dou<sup>1\*</sup>

<sup>1</sup>The Chinese University of Hong Kong, Hong Kong SAR, China <sup>2</sup> Southern Medical University, China <sup>3</sup> ETH Zürich

gianwu@link.cuhk.edu.hk, gidou@cuhk.edu.hk

#### **Abstract**

The evolution of text-to-image (T2I) generation techniques has introduced new capabilities for information visualization, with the potential to advance knowledge democratization and education. In this paper, we investigate how T2I models can be adapted to generate educational health knowledge contents, exploring their potential to make healthcare information more visually accessible and engaging. We explore methods to harness recent T2I models for generating health knowledge flashcards—visual educational aids that present healthcare information through appealing and concise imagery. To support this goal, we curated a diverse, highquality healthcare knowledge flashcard dataset containing 2,034 samples sourced from credible medical resources. We further validate the effectiveness of fine-tuning open-source models with our dataset, demonstrating their promise as specialized health flashcard generators. Our code and dataset are available at: https://github.com/med-air/HealthCards.

### 1 Introduction

Text-to-image (T2I) generation advancements, such as Stable Diffusion (Rombach et al., 2022), Flux (Labs, 2024), and GPT-40 (Hurst et al., 2024), have empowered users to create content with unprecedented aesthetic expression while offering fine-grained control and personalization. This great advancement also fosters valuable applications in various domains, such as design ideation (Paananen et al., 2024; Hu et al., 2023), K12 Education (Ali et al., 2024), math tutoring (Wang et al., 2025a; Choudhury et al., 2025) and Medicine (Mai et al., 2024).

Notably, the recent model from OpenAI, *GPT-4o-Image* (OpenAI, 2025), which was first released in late March 2025, has sparked widespread global discussion and adoption for its unprecedented capability to generate highly coherent and contextually

relevant visual content from natural language instructions with remarkable detail fidelity and compositional accuracy (Yan et al., 2025; Cao et al., 2025). Among its global popularity, an eventful and interesting application is "Ghibli-style images", a style inspired by the works of Studio Ghibli, characterized by hand-drawn aesthetics, vibrant natural landscapes, and emotionally rich characters. Users simply provide text prompts describing scenes, people, or concepts they want to visualize, and the model generates images that faithfully capture the distinctive Ghibli aesthetic—transforming ordinary descriptions into dreamlike illustrations that evoke the studio's signature warmth and fantastical elements. Social media platforms like X and Instagram have been flooded with Ghibli-style images, across personal photos transformed into this aesthetic, creative memes, reimagined movie stills, and entirely new fictional scenarios, highlighting its viral appeal (Di Placido, 2025).

This global phenomenon could reveal a profound public fascination with visually appealing, customizable content that effectively carries both information and emotion. The widespread adoption motivates us to explore more substantive applications: (1) Can we harness text-to-image generation technology to create knowledge disseminators with more educational value? And (2) How effectively can privacy-friendly open-source models perform in these educational contexts?

For these questions, in this work, we try to start approaching it in the field of public health education (Wu et al., 2025b; Zhang et al., 2023). As healthcare knowledge could sometimes remain inaccessible due to its technical complexity, especially for undereducated populations in less developed regions and people with reading disabilities all around the world (Shahid et al., 2022; Gréaux et al., 2023). We expect this kind of new technique could help popularize health knowledge and promote health education.

<sup>\*</sup> Corresponding author




Figure 1: Samples of our *HealthCards* dataset illustrating diverse health topics with anime-style visualizations. The cards feature structured layouts with clear topics, knowledge point headings, and corresponding visual illustrations that effectively represent key health concepts in an accessible format. Below, a simplified data creation pipeline demonstrates how credible health knowledge is extracted, converted into pictorial illustrations, and composed into visually engaging educational content via a text-to-image generation model. These tiny cards carry our vision that such automatic generation of educational flashcard-like knowledge presentations could serve as a new potential for health knowledge democratization (offering more accessible and personalized health information for the public with diverse backgrounds), education (stimulating learners to actively recall knowledge and make conceptual connections), and beyond.

Following this line of thinking, which kind of visual media with what designs are desired for this research and could be valuable for the community? After investigation, a classic learning tool, *Flash-Cards (Wikipedia contributors, 2025; Logopsycom, 2020)* come to our vision. Flashcards are efficient learning tools that organize information in a way that prompts active recall and memorization. They present concise, focused content that can usually combine text with visual elements such as images and diagrams for better comprehension and retention.

Long recognized as an effective educational approach, flashcard-based learning facilitates independent study and reinforces understanding of key concepts. This versatility makes flashcards widely adopted by educators, students, and parents across various disciplines (Santika et al., 2023; Tirtayani et al., 2017). For instance, flashcards are particularly effective in vocabulary learning, as demon-

strated by educational tools like *Duolingo*(Teske, 2017) and 4-pics-1-word(Fithriani, 2023), which incorporate relevant or deliberately confusing images to aid topic retention (Loewen et al., 2019). In healthcare education, flashcards are similarly valuable. Tools like ANKI (Anki, 2025) are widely used by medical students to create personalized flashcards summarizing complex health knowledge points, such as drug recommendations and precautions of disease. Studies show that these tools enhance learning outcomes and knowledge retention (Lu et al., 2021; Harris et al., 2022). Building on this foundation, we envision that automating the design of flashcards using text-to-image generation could further facilitate this process and democratize healthcare knowledge for a wider audience, such as underserved communities and individuals with reading disabilities or attention limitations.

In this work, our contributions could be summarized as follows:

- (1) To the best of our knowledge, we are the first to systematically explore the potential of text-to-image generation models for creating educational health flashcards. We devise problem formulations and design customized pipelines, together with detailed evaluation methodologies for this task. This research is timely given the recent surge in interest around GPT-4o's image generation capabilities and the viral spread of Ghibli-style imagery, demonstrating both the technical feasibility and public enthusiasm for engaging visual knowledge representation that could make complex healthcare knowledge more accessible.
- (2) We curated *HealthCards*, a high-quality health knowledge flashcard dataset comprising 2,034 samples, each carefully selected and verified by medical experts. This dataset encompasses diverse health topics sourced from credible health-care resources and features varied knowledge types, with differing numbers of knowledge points per sample. This diversity makes it a valuable resource for developing AI systems capable of generating accurate visual health education content.
- (3) Our extensive experiments reveal that opensource text-to-image models can be effectively finetuned with our dataset to generate high-quality health education flashcards. The performance is validated by detailed automatic metrics and human evaluation. Importantly, we identify an *evenness bias* among existing T2I models, where they preferentially generate an even number of subfigures for symmetrical visual aesthetics. Models fine-tuned with our dataset demonstrate significant mitigation of this bias and achieve precise subfigure generation that accurately follows the content requirement.

#### 2 Related Works

#### 2.1 Text-to-image Generation

Text-to-image (T2I) generation techniques have achieved unprecedented progress in recent years through pioneering works like *Stable Diffusion*(Rombach et al., 2022) series, *FLUX*(Labs, 2024) series, DALLE (Ramesh et al., 2021), Midjourney and the more recent GPT-4o-Image (Hurst et al., 2024). Research efforts have focused on enhancing and evaluating T2I models across multiple dimensions, including visual-textual alignment (Huang et al., 2025), variability (Tang et al., 2024), generalizability (Cao et al., 2024), and specialized capabilities such as text rendering (Zhao

et al., 2025) and scientific knowledge alignment (Li et al., 2025a). These advancements have enabled valuable healthcare applications, from visualizing anatomical structures (Noel, 2024) and generating realistic surgical images (Nwoye et al., 2025) to creating visual aids that bridge communication gaps and enhance patient understanding of medical conditions (Goparaju, 2024).

#### 2.2 Visual aids for Health Education

Visual aids are critical in health education, enhancing understanding and retention, particularly for individuals with low literacy. Studies show that visual aids improve health literacy, medication adherence, and comprehension (Mbanda et al., 2021; Wang et al., 2025b). The AHRQ (Agency for Healthcare Research and Quality, 2020) recommends visuals to simplify complex information, such as using graphics to clarify portion sizes or numerical data. A review (Lee and Nathan-Roberts, 2021) confirms that visual aids positively impact adherence, comprehension, and recall when supplementing written or spoken medical instructions. Additionally, visuals benefit diverse demographics by enhancing accessibility, with WebMD Ignite (Ignite, 2022) highlighting how they promote health equity through inclusive information.

Flashcards are widely used in medical education for active recall and spaced repetition. Platforms like Anki and Brainscape offer extensive medical flashcard collections (Anki, n.d.; Brainscape, n.d.). Research demonstrates their effectiveness, with studies showing improved engagement and knowledge retention (Sun et al., 2021).

#### 3 Problem Formulation

Drawing from real-world flashcard design principles (31Memorize, 2024) and multimedia learning (Mayer, 2005), we try to formalize our task of HealthCards as a specialized text-to-image generation problem. Specifically, we model a <u>health flashcard</u> HC as a structure with four components:

$$HC = (\tau, K, \Phi, I) \tag{1}$$

where  $\tau \in \mathcal{T}$  denotes the topic of the flashcard as text (e.g., "Prevention of Hypertension").  $K = \{k_i\}_{i=1}^m \subset \mathcal{K}$  represents a knowledge set where each element  $k_i = (h_i, c_i, p_i) \in \mathcal{H} \times \mathcal{C} \times \mathcal{P}$  consists of a concise heading  $h_i \in \mathcal{H}$ , a knowledge content  $c_i \in \mathcal{C}$ , and a pictorial illustration description  $p_i \in \mathcal{P}$  for the knowledge point.  $\Phi = \phi(\tau, K)$  constitutes a synthesized generation prompt that guides

a text-to-image generation model  $g:\Phi\to\mathcal{I}$  in producing a healthcard image  $I=g(\Phi)\in\mathcal{I}$ . The symbolic representation described above is illustrated in Figure 2(A).

The generated health card image I is expected to satisfy the following properties:

**Property 1** (Text Rendering). Let  $T : \mathcal{I} \to 2^{\mathcal{V}}$  be a function that extracts all text elements from an image, where  $\mathcal{V}$  is the set of all possible text strings. For any valid health card image I:

$$\mathsf{T}(I) = \{\tau\} \cup \{h_i \mid i \in \{1, \dots, m\}\}$$
 (2)

That is, the rendered text must precisely consist of the topic  $\tau$  and all knowledge headings  $\{h_i\}_{i=1}^m$ .

**Property 2** (Subfigure Counting). Let |S(I)| denote the number of subfigures in image I, and |K| denote the number of knowledge points. A valid health card image must satisfy:

$$|\mathcal{S}(I)| = |K| = m \tag{3}$$

ensuring the number of generated subfigures exactly matches the number of knowledge points required.

**Property 3** (Subfigure Content Alignment). For a health card image I with m identified subfigures  $S(I) = \{s_1, s_2, \ldots, s_m\}$  and knowledge set  $K = \{k_i = (h_i, c_i, p_i)\}_{i=1}^m$ , there should exist a correspondence between subfigures and knowledge points such that each subfigure visually represents the content described in its corresponding pictorial description. This visual-semantic alignment is necessary for effective knowledge presentation through the health flashcard.

#### 4 Healthcards Dataset

# 4.1 Construction Pipeline

We sourced public health knowledge from the *MedlinePlus* website<sup>1</sup>, a public platform supported by the NIH that provides health information across various categories including Body Location, Disorders, Conditions, Diagnosis, Therapy, and Demographic Groups. It serves as a credible health knowledge resource for the public. As of our data collection on April 5th, 2025, the platform contained 1,017 health topics. The website provides packed resources for research purposes and free public access.

Our construction pipeline can be formalized as a sequence of transformations:

$$E \xrightarrow{f(prompt1;E)} (\tau, K) \xrightarrow[compose]{\phi(\tau,K)} \Phi \xrightarrow[generate]{g(\Phi)} I$$

where E represents the raw essay from Medline-Plus, f is our knowledge extraction function implemented using GPT-4o (Hurst et al., 2024) with fewshot examples that produces the topic  $\tau$  and knowledge set K (the prompt1 is presented in Appendix Table 2). After that,  $\phi(\tau,K)$  synthesizes these elements into a generation prompt  $\Phi$ , a demonstration of this process is shown below:

# Prompt Composition: $\phi(\tau, K) \to \Phi$

Design a clean, 1:1 aspect-ratio health flashcard with anime-style illustrations for  $\{m\}$  knowledge points. Use a  $\{layout\ type\}$  layout  $(\{description\})$ . Each sub-figure must contain a concise title and an illustration cue, focusing on clarity, readability, and an approachable style. Flashcard topic: " $\{\tau\}$ ".

```
For each k_i \in K (i=1,\ldots,m): Subfigure \{i\} (\{\textbf{position}\}): "\{k_i.h\}" - Illustration: \{k_i.p\}.
```

The elements in  $\{*\}$  denote the contents in knowledge set K that is extracted by the previous step. m is the number of knowledge points in the set. Those in  $\{*\}$  represent layout type (e.g. two-layer grid layout), layout description (e.g. two above, two below) and subfigure position (e.g. bottom left). We provide some examples in Appendix Table 3.

Finally, g represents the text-to-image model (specifically GPT-4o-Image) that leverages the composed prompt  $\Phi$  to generate a healthcard image I. Through this process, we generated 2,693 images for our initial dataset, reserving 861 prompts for testing purposes.

#### 4.2 Experts Verification

Even though *GPT-4o-Image* has achieved unprecedented text-to-image generation capability and could be the most powerful model at the time of this manuscript submission, we observe that its performance in generating HealthCards remains unstable. We categorize some common shortcomings: incorrect layouts, inappropriate visual presentations, and inaccurate medical knowledge. Examples of these issues are provided in Appendix Figure 6. Therefore, conducting meticulous quality reviews is crucial to ensure high-quality data collection, which can subsequently serve as a valuable fine-tuning resource for local models.

<sup>1</sup>https://medlineplus.gov/




Figure 2: The Construction Procedure and Statistics of our HealthCards Dataset.

According to our problem formulation in Section 3, we need to manually review whether three properties (text rendering, Subfigure Counting, and Subfigure Content Alignment) are satisfied. For this purpose, two medical postgraduate students manually verified the generated images and provided next-action labels (Accept, Regenerate, Discard, Prompt Modification, CheckNeeded) for each image. After that, all the results were again reviewed by a senior doctor with PhD degree. All the annotation procedures were performed on our specially developed platform, as shown in Appendix Figure 7. We provide more detailed description such as instructions and usage of the platform in Appendix A. During this phase, a final number of 2034 images has been verified which constitute our HealthCards dataset.

#### 4.3 Data Statistics

Our HealthCards dataset demonstrates considerable diversity across multiple dimensions. Figure 2 (b1) illustrates the distribution of medical specialties, encompassing 22 distinct categories, which collectively span most healthcare domains. Figure 2 (b2) depicts the corresponding knowledge types (such as Treatment and Diagnosis) represented within the dataset.

In Figure 2 (b3), we present the distribution of knowledge points per sample, which ranges from 1 to 6 points. This range represents a deliberate tradeoff aimed at ensuring effective knowledge representation given the spatial limitations of a single

1024x1024-pixel image. Samples containing more knowledge points were strategically segmented to ensure all entries fall within this optimal range. Figure 2 (b4) displays the token length distribution of pictorial illustrations per knowledge point, with a maximum constraint of 77 tokens to maintain compatibility with standard text encoders (e.g., CLIP (Radford et al., 2021)).

The distribution of composed text-to-image prompts is shown in Figure 2 (b6), with lengths carefully controlled to remain under 512 tokens, ensuring compatibility with some text encoders such as T5 (Raffel et al., 2020). Finally, we present the character count distribution for each sample's rendered text in (b5), calculated as the combined length of the topic and all associated headings, which provides insight into the textual density of our HealthCards.

# 5 Finetuning and Inference

Flow matching models based on diffusion transformer (DiT), such as Stable Diffusion 3.5 (Rombach et al., 2022) and Flux (Labs, 2024), have significantly outperformed traditional diffusion models in terms of prompt adherence, visual quality and sampling speed. Based on these advantages, we select this class of conditional Flow matching models as a base model and describe its fine-tuning and inference strategies<sup>2</sup>.

<sup>&</sup>lt;sup>2</sup>For these concepts, we provide a more comprehensive recapitulation in the Appendix B.

**Training objective.** We adopt conditional flow-matching (CFM) (Lipman et al., 2022, 2024). For  $t \sim \mathcal{U}[0,1]$ , prompt y, and samples  $x_0 \sim p(\cdot \mid y)$ ,  $x_1 \sim q(\cdot \mid y)$ , the loss can be expressed as:

$$\mathcal{L}_{\text{CFM}}(\theta) = \mathbb{E}_{t,x_0,x_1} \Big[ \| v_{\theta}^{t}(x_t \mid y) - (x_1 - x_0) \|_2^2 \Big]$$

where  $x_t = (1 - t) x_0 + t x_1$  and  $v_{\theta}^t$  is a neural velocity field with trainable parameters  $\theta$ .

Inference with classifier-free guidance (CFG). Following Zheng et al. (2023); Ho and Salimans (2022), during inference phase, conditional and unconditional velocities are linearly mixed:

$$\widehat{v}_{\theta}^{t}(x \mid y) = (1 - \omega) v_{\theta}^{t}(x \mid \varnothing) + \omega v_{\theta}^{t}(x \mid y), \omega \ge 1,$$
(4)

where  $\omega$  is the guidance scale ( $\omega=1$ : no guidance;  $\omega>1$ : stronger adherence to y).

# 6 Experiments

# **6.1** Experiment and Evaluation Settings

Aligned with our problem formulation in Section 3, the experiments were designed to evaluate each HealthCard image generated by a T2I model from the following aspects:

- (1) Text Rendering Score. We harness an OCR model (PaddleOCR V4 (Contributors, 2025)) to extract all identifiable words and characters. Then, all words are first grouped according to their layout positions, and in each group, they are reordered with human reading sequence (from left to right, from up to down). After that, we obtain all processed detected strings. They are compared with the expected detected string, which is a set of Flashcard topic  $\tau$  plus all subheadings h. Then, following the common practice of NLP, we compute the Word Error Rate (WER) and Character Error Rate (CER) for each paired detected string and ground truth string. We provide a more detailed explanation of this score in Appendix C.1.
- (2) Subfigure Counting Score. we measure whether the number of generated subfigures in a generated image aligns with the number of knowledge points for that case. For this purpose, we harness a powerful vision language model, *Qwen2.5-VL-32B* (Bai et al., 2025). It has an innate layout detection capability which is capable of this task without further training, and this helps reduce the risk of overfitting to a certain layout which could

be unfair for some models. We compute the absolute subfigure count gap (Gap) and subfigure count error rate for this score. More details are illustrated in Appendix C.2.

(3) Subfigure Alignment Score. We evaluate the semantic alignment between each subfigure and its corresponding pictorial illustration description. This provides fine-grained assessment of content representation quality. For this dimension, we employ CLIPScore (Hessel et al., 2021) and VQAScore (Lin et al., 2024) as measurement tools. Comprehensive evaluation procedures are detailed in Appendix C.3.

**General Scores:** Beyond the three dimensions directly addressing our problem formulation, we also assess general image quality and aesthetic properties using *Q-align* (Wu et al., 2024). We also computed the global image and T2I prompt alignment score with the VQAScore. (As token lengths of our T2I prompts exceed 77, as reflected in Figure 2 (b6), metrics like CLIPScore are not feasible here).

# **6.2** Implementation Details

All open-source models were trained and tested on a server equipped with 2 H100 GPUs. The code and annotation platform are available via link for further details. Our experiments employed multiple state-of-the-art models: Stable Diffusion 3.5 Medium & Large (Rombach et al., 2022), FLUX.1-dev (Labs, 2024), Lumina (Oin et al., 2025), and HiDream-I1-Full (HiDream-ai, 2025). All fine-tuning was performed using LoRA (Hu et al., 2022) with rank 128 unless otherwise specified, trained for 10,000 steps with a batch size of 4. Classifier-free Guidance scale was set to 5 during inference by default. Commercial models including Flux.1 [Pro] (Black Forest Labs, 2025), DALLE3 (Ramesh et al., 2021), and GPT4o-Image (OpenAI, 2025) were accessed through their official APIs.

# 6.3 Results

We present the quantitative results in Table 1 and qualitative comparisons in Figure 5. GPT4o-Image demonstrates superior performance in *text rendering* and *Subfigure Alignment*, yet exhibits a significant limitation in accurately generating the requested number of subfigures (approximately 14% of total cases). As shown in Figure 5 (a-5), the generated healthcard fails to match the expected

Table 1: Quantitative results on test prompts.	*indicates models fine-tuned with our HeathCards dataset. I	Bold
indicates the best performance, and underlined	I the second-best.	

Text Re	ndering	Subfig	ure Counting	Subfigure Ali	gnment	General				
		ı — —		====						
WER↓	CER↓	Gap↓	Error Rate↓	CLIPScore <sub>s</sub> $\uparrow$	$VQA_s\uparrow$	Aesthetic↑	Quality↑	VQA↑		
0.827	0.603	0.552	0.387	0.236	0.705	3.520	4.568	0.786		
1.044	0.794	0.626	0.474	0.221	0.696	3.103	3.966	0.761		
0.694	0.485	0.585	0.407	0.221	0.630	<u>3.547</u>	4.525	0.791		
1.309	1.029	0.569	0.425	0.209	0.699	3.144	4.150	0.674		
ream-I1 0.429 0.342 0.681 0.499		0.499	0.237	0.647	3.383	<u>4.671</u>	0.821			
0.640	0.529	0.352	0.348	0.251	0.758	3.533	4.674	0.785		
0.833	0.665	0.626	0.479	0.249	0.753	3.654	4.669	0.774		
0.067	0.052	0.143	0.141	0.270	0.903	3.357	4.527	0.838		
0.853	-0.545	0.172	0.170	0.227	0.731	3.376	4.399	0.808		
0.387	0.222	0.033	0.027	0.241	0.760	3.441	4.565	0.832		
1.140	0.915	0.511	0.442	0.211	0.741	3.395	4.444	0.590		
0.378	0.288	0.121	0.100	0.229	0.672	3.469	4.631	0.821		
<u>0.118</u>	<u>0.064</u>	0.010	0.008	<u>0.265</u>	<u>0.861</u>	3.429	4.636	0.838		
	WER↓  0.827 1.044 0.694 1.309 0.429 0.640 0.833  0.067 - 0.853 0.387 1.140 0.378	0.827 0.603 1.044 0.794 0.694 0.485 1.309 1.029 0.429 0.342 0.640 0.529 0.833 0.665 <b>0.067 0.052</b> 	WER↓ CER↓ Gap↓  0.827  0.603  0.552  1.044  0.794  0.626  0.694  0.485  0.585  1.309  1.029  0.569  0.429  0.342  0.681  0.640  0.529  0.352  0.833  0.665  0.626  0.067  0.052  0.143  0.853  0.545  0.172  0.387  0.222  0.033  1.140  0.915  0.511  0.378  0.288  0.121	WER↓         CER↓         Gap↓         Error Rate↓           0.827         0.603         0.552         0.387           1.044         0.794         0.626         0.474           0.694         0.485         0.585         0.407           1.309         1.029         0.569         0.425           0.429         0.342         0.681         0.499           0.640         0.529         0.352         0.348           0.833         0.665         0.626         0.479           0.067         0.052         0.143         0.141           0.853         0.545         0.172         0.170           0.387         0.222         0.033         0.027           1.140         0.915         0.511         0.442           0.378         0.288         0.121         0.100	WER↓         CER↓         Gap↓         Error Rate↓         CLIPScore <sub>s</sub> ↑           0.827         0.603         0.552         0.387         0.236           1.044         0.794         0.626         0.474         0.221           0.694         0.485         0.585         0.407         0.221           1.309         1.029         0.569         0.425         0.209           0.429         0.342         0.681         0.499         0.237           0.640         0.529         0.352         0.348         0.251           0.833         0.665         0.626         0.479         0.249           0.067         0.052         0.143         0.141         0.270 $\overline{0}.853$ $\overline{0}.545$ $\overline{0}.172$ $\overline{0}.170$ $\overline{0}.227$ 0.387         0.222 $\overline{0}.033$ $\overline{0}.027$ 0.241           1.140         0.915         0.511         0.442         0.211           0.378         0.288         0.121         0.100         0.229	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	WER↓         CER↓         Gap↓         Error Rate↓         CLIPScore $_s$ ↑         VQA $_s$ ↑         Aesthetic↑         Quality↑           0.827         0.603         0.552         0.387         0.236         0.705         3.520         4.568           1.044         0.794         0.626         0.474         0.221         0.696         3.103         3.966           0.694         0.485         0.585         0.407         0.221         0.630         3.547         4.525           1.309         1.029         0.569         0.425         0.209         0.699         3.144         4.150           0.429         0.342         0.681         0.499         0.237         0.647         3.383         4.671           0.640         0.529         0.352         0.348         0.251         0.758         3.533         4.674           0.833         0.665         0.626         0.479         0.249         0.753         3.654         4.669           0.067         0.052         0.143         0.141         0.270         0.903         3.357         4.527 $\overline{0.853}$ $\overline{0.545}$ 0.172         0.170         0.227         0.731         3.376         4		

5 knowledge points. Further investigation reveals an "Evenness Bias" in GPT4o-Image. The confusion matrix in Figure 3 illustrates that subfigure counting errors predominantly occur in healthcard generation tasks with odd numbers of subfigures (e.g., 3 and 5), with results often defaulting to even numbers (4 and 6). This suggests an inappropriate preference for visual symmetry at the expense of content accuracy. While this bias is also observed in the raw Flux.1[Dev] model (Figure 5 (c3 and c5)), our fine-tuned version significantly mitigates this issue. This could indicate the potential value of our dataset for improving healthcare educational materials, where accurate representation of medical knowledge points is critical for effective learning and education.




Figure 3: Confusion Matrices Comparing Expected and Actual Number of Generated Subfigures. (a) Confusion matrix for GPT-4o-Image, with red dotted boxes highlighting the *evenness bias*, where the model tends to preferentially generate an even number of subfigures. (b) Confusion matrix for Flux.1[Dev], fine-tuned on our *HealthCards* dataset, demonstrating a significant reduction in confusion compared to GPT-4o-Image.




Figure 4: The results of Human Evaluation Study

While all fine-tuned models significantly outperform their raw counterparts, Flux.1[Dev] emerges as the most promising among all open-source models evaluated. However, it still falls short in text rendering and subfigure alignment, as shown in Table 1. To better understand human preferences regarding these shortcomings and to assess the validity of our evaluation methods, we conducted a human evaluation study.

#### **6.4** Human Evaluation Results

To validate our automatic evaluation metrics and gain deeper insights into model performance, we conducted a comprehensive human evaluation study with four participants who have backgrounds in healthcare education. Each evaluator independently assessed 90 images (30 distinct image pairs from Flux.1[Dev], our fine-tuned Flux.1[Dev], and GPT-4o-Image respectively). Participants rated each image on a 5-point Likert scale (1=poor, 5=ex-




Figure 5: Qualitative Demonstration of Our Models. The Healthcards shown are expected to include knowledge points covering a range from 1 to 6, arranged sequentially from left to right. Results from three selected models are presented: **GPT-4o-Image** (top row), **fine-tuned Flux.1[Dev]** using our dataset (middle row), and **baseline Flux.1[Dev]** (bottom row). T2I prompts for these cases are provided in the Appendix Table 3.

cellent) across four dimensions: Text Readability, Layout Organization, Text-Subfigure Alignment, and Overall Quality. Details are provided in Appendix D. The results are shown in Figure 4.

GPT-4o-Image achieves better performance in Text Readability, Alignment, and Overall Quality, while fine-tuned Flux.1[Dev] shows significantly better results in Layout Organization. This aligns with our automatic evaluation outcomes in Table 1. Notably, our fine-tuned model achieves an average overall score of 4 (good), while its raw counterpart receives a negative overall score, demonstrating the value and effectiveness of fine-tuning on our dataset for real-world applications.

We also examined how human evaluation correlates with our automatic metrics. The Spearman correlation between Text Readability and Word Accuracy and Character Accuracy are 0.526 and 0.530 respectively (p<0.05). The Layout Organization score correlates with the accuracy of subfigure counting at 0.796 (p<0.001). The Text-Subfigure Alignment score correlates with  $CLIPScore_s$  at 0.315 and with  $VQA_s$  at 0.368 . The Overall Assessment correlates with VQA at 0.337, with accuracy of subfigure count at 0.567 (p<0.01), and with word accuracy at 0.505 (p<0.01). These correlations reveal that subfigure counting accuracy and word accuracy most strongly influence evaluators' overall impressions, highlighting the critical

importance of accurate text rendering and layout generation in health educational materials. This aligns with intuitive human review patterns for knowledge cards—when evaluators notice incorrect knowledge point counts or inaccurate titles, they tend to assign lower scores without needing to examine the image content in detail. This finding underscores the fundamental importance of structural and textual accuracy as gatekeeping criteria in the evaluation of educational health materials.

# 6.5 More experimental Explorations.

We provide more experimental explorations such as different LoRA ranks, data ratios, guidance scales, and T2I prompt designs in Appendix E.

# 7 Conclusion

We introduced HealthCards, the first comprehensive exploration of text-to-image models for healthcare knowledge visualization through educational flashcards. Our contributions include a high-quality dataset of expert-verified healthcare flashcards sourced from credible medical knowledge resources. We identified an "evenness bias" in current models like GPT-4o-Image, where they could prioritize visual symmetry over content accuracy, and demonstrated that fine-tuning with our dataset effectively mitigates this issue while significantly improving overall quality.

#### Limitations

- (1) Our current models still face challenges in highly specialized medical contexts, which is a limitation inherent to the foundational knowledge of the underlying models—a constraint that affects even GPT-4o-Image. These knowledge limitations led us to focus our initial application on public health education rather than specialized medical training. The models perform well in conveying general health concepts but may struggle with nuanced medical terminology or highly technical concepts that require expert-level domain knowledge.
- (2) While our fine-tuned models successfully mitigate the evenness bias and demonstrate significant improvements, they still fall short of GPT-4o-Image in text rendering and content alignment. At the time of this submission, the architecture, parameters, and methodologies behind GPT-4o-Image remain undisclosed, creating uncertainty for our alignment efforts. GPT-4o-Image may employ fundamentally different approaches such as autoregressive generation (Tian et al., 2024; Wu et al., 2025a) or agent-based systems (Li et al., 2025b), which could explain the performance gap and present challenges for future improvements using purely opensource methods.
- (3) As pioneers in this emerging research area, we were unable to conduct long-term educational effectiveness studies within our project timeline. While our human evaluations with healthcare educators provide valuable initial validation, more extensive studies on knowledge retention and learning outcomes with diverse learner populations would strengthen claims about educational benefits.

# Acknowledgements

The authors gratefully acknowledge the anonymous reviewers for their helpful comments and suggestions. This work makes use of materials courtesy of MedlinePlus from the National Library of Medicine. This research project was supported in part by the National Natural Science Foundation of China Project No. 62322318 and Project No. 62201485, in part by National Key R&D Program of China Project No. 2022ZD0161100, and in part by a grant from the Research Grants Council of the Hong Kong Special Administrative Region, China, Project No. T45-401/22-N.

### References

- 31Memorize. 2024. Guiding principles of effective flashcard creation. Accessed: 2025-05-18.
- Agency for Healthcare Research and Quality. 2020. Topic: Use of visual aids. Accessed: 2025-05-18.
- Safinah Ali, Prerna Ravi, Katherine Moore, Hal Abelson, and Cynthia Breazeal. 2024. A picture is worth a thousand words: Co-designing text-to-image generation learning materials for k-12 with educators. Proceedings of the AAAI Conference on Artificial Intelligence, 38(21):23260–23267.
- Anki. 2025. Anki powerful, intelligent flashcards.
- Anki. n.d. Anki for first year. Accessed: 2025-05-18.
- Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, and 1 others. 2025. Qwen2. 5-vl technical report. arXiv preprint arXiv:2502.13923.
- Asma Ben Abacha and Dina Demner-Fushman. 2019. A question-entailment approach to question answering. BMC Bioinform., 20(1):511:1–511:23.
- Black Forest Labs. 2025. FLUX1.1 Pro: Best in class image generation.
- Brainscape. n.d. The best flashcards for medical and nursing students. Accessed: 2025-05-18.
- Jingtao Cao, Zhang Zheng, Hongru Wang, and Kam-Fai Wong. 2024. Vleu: a method for automatic evaluation for generalizability of text-to-image models. In Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, pages 11034–11049.
- Pu Cao, Feng Zhou, Junyi Ji, Qingye Kong, Zhixiang Lv, Mingjian Zhang, Xuekun Zhao, Siqi Wu, Yinghui Lin, Qing Song, and 1 others. 2025. Preliminary explorations with gpt-40 (mni) native image generation. arXiv preprint arXiv:2505.05501.
- Monjoy Narayan Choudhury, Junling Wang, Yifan Hou, and Mrinmaya Sachan. 2025. Can vision-language models solve visual math equations? <u>Preprint</u>, arXiv:2509.09013.
- PaddlePaddle Contributors. 2025. Paddleocr: Awesome multilingual ocr toolkits based on paddlepaddle. https://github.com/PaddlePaddle/PaddleOCR. Accessed: 2025-05-18.
- Dani Di Placido. 2025. The AI-generated Studio Ghibli trend, explained.
- Weichen Fan, Amber Yijia Zheng, Raymond A Yeh, and Ziwei Liu. 2025. Cfg-zero\*: Improved classifier-free guidance for flow matching models. <a href="arXiv:2503.18886"><u>arXiv:2503.18886</u></a>.
- Rahmah Fithriani. 2023. Gamified efl learning: Utilizing 4 pics 1 word application in vocabulary class. Journal of English Language Studies, 8(1):1–18.

- Niharika Goparaju. 2024. Picture this: Text-to-image models transforming pediatric emergency medicine. Annals of Emergency Medicine, 84(6):651–657.
- Mélanie Gréaux, Maria Francesca Moro, Kaloyan Kamenov, Amy M Russell, Darryl Barrett, and Alarcos Cieza. 2023. Health equity for persons with disabilities: a global scoping review on barriers and interventions in healthcare services. <a href="International Journal">International Journal</a> for Equity in Health, 22(1):236.
- David M Harris, Michael Chiang, and MIchael Chiang. 2022. An analysis of anki usage and strategy of first-year medical students in a structure and function course. Cureus, 14(3).
- Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. 2021. Clipscore: A referencefree evaluation metric for image captioning. <u>arXiv</u> preprint arXiv:2104.08718.
- HiDream-ai. 2025. Hidream-i1: A new open-source image generative model. https://github.com/ HiDream-ai/HiDream-I1.
- Jonathan Ho and Tim Salimans. 2022. Classifier-free diffusion guidance. <u>arXiv preprint</u> arXiv:2207.12598.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, and 1 others. 2022. Lora: Low-rank adaptation of large language models. ICLR, 1(2):3.
- Wentao Hu, Wengyu Zhang, Yiyang Jiang, Chen Jason Zhang, Xiaoyong Wei, and Li Qing. 2025. Removal of hallucination on hallucination: Debate-augmented RAG. In Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 15839–15853, Vienna, Austria. Association for Computational Linguistics.
- Wentao Hu, Jia Zheng, Zixin Zhang, Xiaojun Yuan, Jian Yin, and Zihan Zhou. 2023. Plankassembly: Robust 3d reconstruction from three orthographic views with learnt shape programs. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), pages 18495–18505.
- Kaiyi Huang, Chengqi Duan, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. 2025. T2i-compbench++: An enhanced and comprehensive benchmark for compositional text-to-image generation. IEEE Transactions on Pattern Analysis and Machine Intelligence.
- Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, and 1 others. 2024. Gpt-4o system card. <a href="mailto:arXiv:2410.21276"><u>arXiv:2410.21276</u></a>.
- WebMD Ignite. 2022. Visuals in health education. Accessed: 2025-05-18.

- Black Forest Labs. 2024. Flux. https://github.com/black-forest-labs/flux.
- Katherine Lee and Dan Nathan-Roberts. 2021. Using visual aids to supplement medical instructions, health education, and medical device instructions.

  Proceedings of the International Symposium on Human Factors and Ergonomics in Health Care, 10(1):257–262.
- Jialuo Li, Wenhao Chai, Xingyu Fu, Haiyang Xu, and Saining Xie. 2025a. Science-t2i: Addressing scientific illusions in image synthesis. Preprint, arXiv:2504.13129.
- Mingcheng Li, Xiaolu Hou, Ziyang Liu, Dingkang Yang, Ziyun Qian, Jiawei Chen, Jinjie Wei, Yue Jiang, Qingyao Xu, and Lihua Zhang. 2025b. Mccd: Multiagent collaboration-based compositional diffusion for complex text-to-image generation. In <a href="Proceedings of the Computer Vision and Pattern Recognition Conference">Proceedings Recognition Conference</a>, pages 13263–13272.
- Zhiqiu Lin, Deepak Pathak, Baiqi Li, Jiayao Li, Xide Xia, Graham Neubig, Pengchuan Zhang, and Deva Ramanan. 2024. Evaluating text-to-visual generation with image-to-text generation. In <a href="European Conference on Computer Vision"><u>European Conference on Computer Vision</u></a>, pages 366–384. Springer.
- Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. 2022. Flow matching for generative modeling. <a href="arXiv:2210.02747">arXiv:2210.02747</a>.
- Yaron Lipman, Marton Havasi, Peter Holderrieth, Neta Shaul, Matt Le, Brian Karrer, Ricky TQ Chen, David Lopez-Paz, Heli Ben-Hamu, and Itai Gat. 2024. Flow matching guide and code. arXiv preprint arXiv:2412.06264.
- Shawn Loewen, Dustin Crowther, Daniel R Isbell, Kathy Minhye Kim, Jeffrey Maloney, Zachary F Miller, and Hima Rawal. 2019. Mobile-assisted language learning: A duolingo case study. ReCALL, 31(3):293–311.
- Logopsycom. 2020. Flashcards: A tool to facilitate learning. Accessed: 2025-05-02.
- Matthew Lu, John H Farhat, and Gary L Beck Dallaghan. 2021. Enhanced learning and retention of medical knowledge using the mobile flash card application anki. Medical science educator, 31(6):1975–1981.
- Michelle Mai, Fatima N Mirza, and Christopher Di-Marco. 2024. Application of text-to-image translation algorithms in medicine: a systematic review. JAAD Reviews.
- Richard E Mayer. 2005. <u>The Cambridge handbook of</u> multimedia learning. Cambridge university press.
- Njabulo Mbanda, Shakila Dada, Kirsty Bastable, Gimbler-Berglund Ingalill, and 1 others. 2021. A scoping review of the use of visual aids in health education materials for persons with low-literacy levels. Patient education and counseling, 104(5):998–1017.

- Geoffroy PJC Noel. 2024. Evaluating ai-powered text-to-image generators for anatomical illustration: A comparative study. <u>Anatomical sciences education</u>, 17(5):979–983.
- Chinedu Innocent Nwoye, Rupak Bose, Kareem Elgohary, Lorenzo Arboit, Giorgio Carlino, Joël L Lavanchy, Pietro Mascagni, and Nicolas Padoy. 2025. Surgical text-to-image generation. Pattern Recognition Letters.
- OpenAI. 2025. Introducing 40 image generation.
- Ville Paananen, Jonas Oppenlaender, and Aku Visuri. 2024. Using text-to-image generation for architectural design ideation. <u>International Journal of Architectural Computing</u>, 22(3):458–474.
- Qi Qin, Le Zhuo, Yi Xin, Ruoyi Du, Zhen Li, Bin Fu, Yiting Lu, Xinyue Li, Dongyang Liu, Xiangyang Zhu, Will Beddow, Erwann Millon, Wenhai Wang Victor Perez, Yu Qiao, Bo Zhang, Xiaohong Liu, Hongsheng Li, Chang Xu, and Peng Gao. 2025. Luminaimage 2.0: A unified and efficient image generative framework. Preprint, arXiv:2503.21758.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, and 1 others. 2021. Learning transferable visual models from natural language supervision. In <a href="International conference on machine learning">International conference on machine learning</a>, pages 8748–8763. PmLR.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. Journal of machine learning research, 21(140):1–67.
- Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. 2021. Zero-shot text-to-image generation. In International conference on machine learning, pages 8821–8831. Pmlr.
- Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. 2022. High-resolution image synthesis with latent diffusion models. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 10684–10695.
- Rani Santika, Rafi Farizki, and Hanif Nurcholish Adiantika. 2023. English language learning with flash-card media and educational posters to improve language education. <u>Journal of Social Science</u>, 4(3):706–711.
- Rabia Shahid, Muhammad Shoker, Luan Manh Chu, Ryan Frehlick, Heather Ward, and Punam Pahwa. 2022. Impact of low health literacy on patients' health outcomes: a multicenter cohort study. <u>BMC</u> health services research, 22(1):1148.

- Streamlit. 2025. Streamlit: A faster way to build and share data apps. https://github.com/streamlit/streamlit.
- Michael Sun, Shelun Tsai, Deborah L Engle, and Shelley Holmer. 2021. Spaced repetition flashcards for teaching medical students psychiatry. Medical science educator, 31:1125–1131.
- Raphael Tang, Xinyu Zhang, Lixinyu Xu, Yao Lu, Wenyan Li, Pontus Stenetorp, Jimmy Lin, and Ferhan Ture. 2024. Words worth a thousand pictures: Measuring and understanding perceptual variability in text-to-image generation. <a href="mailto:arXiv:2406.08482">arXiv:2406.08482</a>.
- Kaitlyn Teske. 2017. Duolingo. <u>Calico Journal</u>, 34(3):393–401.
- Keyu Tian, Yi Jiang, Zehuan Yuan, Bingyue Peng, and Liwei Wang. 2024. Visual autoregressive modeling:
   Scalable image generation via next-scale prediction.
   Advances in neural information processing systems,
   37:84839–84865.
- Luh Ayu Tirtayani, Mutiara Magta, and Ni Gusti Ayu Made Yeni Lestari. 2017. Teacher friendly e-flashcard: a development of bilingual learning media for young learners. <u>Journal of Education</u> Technology, 1(1):18–29.
- Junling Wang, Anna Rutkiewicz, April Wang, and Mrinmaya Sachan. 2025a. Generating pedagogically meaningful visuals for math word problems: A new benchmark and analysis of text-to-image models. In Findings of the Association for Computational Linguistics: ACL 2025, pages 11229–11257, Vienna, Austria. Association for Computational Linguistics.
- Rongsheng Wang, Junying Chen, Ke Ji, Zhenyang Cai, Shunian Chen, Yunjin Yang, and Benyou Wang. 2025b. Medgen: Unlocking medical video generation by scaling granularly-annotated medical videos. Preprint, arXiv:2507.05675.
- Wikipedia contributors. 2025. Flashcard Wikipedia, the free encyclopedia. [Online; accessed 2-May-2025].
- Chengyue Wu, Xiaokang Chen, Zhiyu Wu, Yiyang Ma, Xingchao Liu, Zizheng Pan, Wen Liu, Zhenda Xie, Xingkai Yu, Chong Ruan, and 1 others. 2025a. Janus: Decoupling visual encoding for unified multimodal understanding and generation. In <a href="Proceedings of the Computer Vision and Pattern Recognition Conference">Proceedings Recognition Conference</a>, pages 12966–12977.
- Haoning Wu, Zicheng Zhang, Weixia Zhang, Chaofeng Chen, Liang Liao, Chunyi Li, Yixuan Gao, Annan Wang, Erli Zhang, Wenxiu Sun, and 1 others. 2024.
  Q-align: Teaching lmms for visual scoring via discrete text-defined levels. In <u>International Conference on Machine Learning</u>, pages 54015–54029. PMLR.

Qian Wu, Zheyao Gao, Longfei Gou, and Qi Dou. 2025b. DDxTutor: Clinical reasoning tutoring system with differential diagnosis-based structured reasoning. In Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 30934–30957, Vienna, Austria. Association for Computational Linguistics.

Zhiyuan Yan, Junyan Ye, Weijia Li, Zilong Huang, Shenghai Yuan, Xiangyang He, Kaiqing Lin, Jun He, Conghui He, and Li Yuan. 2025. Gpt-imgeval: A comprehensive benchmark for diagnosing gpt40 in image generation. arXiv preprint arXiv:2504.02782.

Zihao Zhang, Zonghai Yao, Huixue Zhou, Feiyun ouyang, and Hong Yu. 2023. Ehrtutor: Enhancing patient understanding of discharge instructions. Preprint, arXiv:2310.19212.

Shitian Zhao, Qilong Wu, Xinyue Li, Bo Zhang, Ming Li, Qi Qin, Dongyang Liu, Kaipeng Zhang, Hongsheng Li, Yu Qiao, and 1 others. 2025. Lex-art: Rethinking text generation via scalable high-quality data synthesis. arXiv preprint arXiv:2503.21749.

Qinqing Zheng, Matt Le, Neta Shaul, Yaron Lipman, Aditya Grover, and Ricky TQ Chen. 2023. Guided flows for generative modeling and decision making. arXiv preprint arXiv:2311.13443.

# A Dataset Construction and Annotation Process

In this section, we provide more details about our dataset construction and annotation Process. We present prompt 1 in box 2, which guides the LLM f to perform knowledge extraction from essays, as described in Section 4.1.

# **Prompt 1 (for Knowledge Extraction)**

You are a helpful health education assistant. Your task is to extract ALL knowledge points from the provided context and organize them into appropriate health flashcards. For each knowledge point: 1. Extract the original content from the text. 2. Assign a concise but descriptive title. 3. Create a brief description for an illustration that would help visualize the concept.

Focus on extracting knowledge related to: -Symptoms - Causes - Treatments - Prevention methods - Diagnostic procedures - Risk factors - Complications - Any other health relevant information

Guidelines: - Extract ALL knowledge points present in the text, being comprehensive - Group related knowledge points under appropriate topics - The content should be directly from the original text - do not infer or add information - If the context lacks useful information (e.g., only contains external links), you may return an empty list - Make titles concise but informative, including key information - For each knowledge point, include an illustration description that would help visualize the concept

Here's an example of the expected format: {example1} {example2}

Now, extract ALL knowledge points from the following context and organize them into appropriate Health FlashCards:

Table 2: *Prompt 1* used for extracting knowledge from healthcare essays.

After structured knowledge points being extracted, we assemble them into text-to-image generation prompts. This composing process has been defined as  $\phi$  in Section 4.1. Here we provide some complete examples in Table 3. Note that the maximum length is controlled below 512 tokens.

After all the T2I prompts have been prepared, we fed them into GPT-40-Image for healthcard im-

age generation. Following which we performed a dataset review with experts on our specialized developed platform. A screenshot of the platform is presented in Figure 7. It is built on Streamlit and could be easily deployed for shared annotation (Streamlit, 2025).




Figure 6: Some examples of discarded samples or ones need to regenerate. (Best Viewed when zoomed in)

#### **A.1** The Annotation Platform

When using this platform, as shown in Figure 7, the interface displays generated images alongside the original material (the source essay from which knowledge points are extracted, shown on the left) and the structured knowledge point (shown on the right). Experts follow a systematic verification procedure: (1) They first assess whether the Health Card on the right appropriately extracts information from the original material on the left. If not, the item is labeled "Need Prompt Modification." (2) If the extraction is valid, experts proceed to evaluate the image content by verifying the correct number of subfigures, identifying expected text elements (healthcare topic and subfigure headings), and examining whether each subfigure's content aligns with its pictorial illustration. Images that pass all verification criteria are accepted into the dataset;

otherwise, they require regeneration or additional review (Hu et al., 2025). We have released this platform in our github repository.

# B Recapitulation for Flow Matching and Classifier-free Guidance

Following the explanations as in previous works (Lipman et al., 2022, 2024; Fan et al., 2025), we provide a revisit of basic concepts of *Flow Matching* and *Classifier-free Guidance* techniques. Our notation follows the conditional setting, yet the ideas hold for the unconditional case as well.

# **B.1** Conditional Flow Matching (CFM)

Let the source density be  $p(x \mid y)$  and the target density be  $q(x \mid y)$ , where y is an external conditioning signal (e.g. a class label). CFM introduces a continuum of intermediate distributions  $\{p_t(x \mid y)\}_{t \in [0,1]}$  that smoothly morph the source into the target, satisfying  $p_0(x \mid y) = p(x \mid y)$  and  $p_1(x \mid y) = q(x \mid y)$ . A convenient choice is the linear interpolation

$$p_t(x \mid y) := (1 - t) p(x \mid y) + t q(x \mid y), \quad (5)$$

implying that a sample drawn at time t can be written as  $x_t = (1 - t) x_0 + t x_1$  with  $x_0 \sim p(x \mid y)$  and  $x_1 \sim q(x \mid y)$ .

To describe the evolution of  $x_t$ , we fit a time-dependent velocity field  $\dot{x}_t = v_t^{\theta}(x \mid y)$ , where  $v_t^{\theta}$  is a neural network parameterized by  $\theta$ . The parameters are optimized through the mean-squared error objective

$$\mathcal{L}_{CFM}(\theta) = \mathbb{E}_{t,x_0,x_1} \left\| v_t^{\theta}(x_t \mid y) - (x_1 - x_0) \right\|_2^2.$$
(6)

After training, new samples from  $q(\cdot \mid y)$  are obtained by numerically integrating the learned ODE with a solver.

### **B.2** Classifier-Free Guidance (CFG)

Classifier-free guidance (Ho and Salimans, 2022) enhances conditional generation by biasing the trajectory toward the conditioning signal without a separate classifier. During training, the same neural field  $v_t^{\theta}$  is asked to produce both conditional and unconditional velocities by occasionally replacing y with the null token  $\varnothing$ . At inference time, the guided field is obtained by the linear blend

$$\hat{v}_t^{\theta}(x \mid y) := (1 - \omega)v_t^{\theta}(x \mid y = \varnothing) + \omega v_t^{\theta}(x \mid y), \tag{7}$$

#### PROMPT FOR FIGURE 5 (1)

Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for the given knowledge point. The subfigure should include a clear title and illustration, emphasizing clarity, readability, and an approachable style. Topic (title) of Flashcard: 'Symptoms of atypical mycobacterial infections'. Subfigure: 'Weight loss' - Illustration: An anime character noticing their loose-fitting clothes and appearing perplexed.

#### PROMPT FOR FIGURE 5 (2)

Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for two knowledge points. Each subfigure should include a clear title and illustration, emphasizing clarity, readability, and an approachable style. Topic (title) of Flashcard: 'How to improve mental health'. Subfigure 1 (left): 'Staying positive' - Illustration: An anime character standing in a bright park with flowers nearby, smiling gently. They hold a glowing phone showing positivity while a small cloud drifts away in the background, symbolizing negative information being set aside. Subfigure 2 (right): 'Practicing gratitude' - Illustration: An anime character sitting at a simple desk, happily writing in a journal with small glowing icons of a family portrait, a meal, and a sunset floating around them.

#### PROMPT FOR FIGURE 5 (3)

Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for three knowledge points. Use a two-layer grid layout (two above, one below). Each subfigure should include a clear title and illustration, emphasizing clarity, readability, and an approachable style. Topic (title) of FlashCard: 'Warning Signs of Behavior Disorders'. Subfigure 1 (top left): 'Lying or stealing' - Illustration: An anime character holding a small object behind their back, with a nervous or guilty expression to represent dishonest behavior. Subfigure 2 (top right): 'School-related issues' - Illustration: An anime classroom setting with a character slouched on a desk, looking discouraged with scattered papers around to suggest poor academic performance. Subfigure 3 (bottom): 'Early substance use' - Illustration: An anime teenager holding a cigarette or small bottle, with a worried expression representing unhealthy habits.

#### PROMPT FOR FIGURE 5 (4)

Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for four knowledge points. Use a two-layer grid layout (two above, two below). Each subfigure should include a clear title and illustration, emphasizing clarity, readability, and an approachable style. Topic (title) of FlashCard: 'Risk factors for stroke'. Subfigure 1 (top left): 'Smoking' - Illustration: An anime character holding a cigarette with a worried expression. Include a glowing 'no-smoking' symbol in the frame for emphasis. Subfigure 2 (top right): 'Personal or family history' - Illustration: An anime character looking at framed family photos, with a single subtle chart or document visible in the background to highlight family history concerns. Subfigure 3 (bottom left): 'Age' - Illustration: An elderly anime character with a walking stick and glasses, accompanied by simplified icons like a warning sign near a heart or brain diagram. Subfigure 4 (bottom right): 'Race and ethnicity' - Illustration: An anime-style group of diverse characters looking at a stroke prevention poster or booklet held by an African American character.

#### PROMPT FOR FIGURE 5 (5)

Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for five knowledge points. Use a two-layer grid layout (three above, two below). Each subfigure should include a clear title and illustration, emphasizing clarity, readability, and an approachable style. Topic (title) of FlashCard: 'Diagnosis of tremor'. Subfigure 1 (top left): 'Neurological exam' - Illustration: An anime doctor pointing at a straight walking path while a patient walks carefully, with a small additional scene showing the doctor listening to the patient speak. Subfigure 2 (top middle): 'Blood or urine tests' - Illustration: An anime scientist handling a test tube in a laboratory setting, visually focused on analyzing the sample. Subfigure 3 (top right): 'Imaging tests' - Illustration: An anime patient inside an MRI machine with a technician observing the process through a glass control room window. Subfigure 4 (bottom left): 'Daily task tests' - Illustration: An anime patient carefully holding a cup while a doctor takes notes, demonstrating focused observation. Subfigure 5 (bottom right): 'Electromyogram' - Illustration: An anime scene showing electrodes attached to a patient's arm, connected to a monitor displaying live results.

#### PROMPT FOR FIGURE 5 (6)

Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for six knowledge points. Use a two-layer grid layout (three above, three below). Each subfigure should include a clear title and illustration, emphasizing clarity, readability, and an approachable style. Topic (title) of FlashCard: 'Steps toward healthy living'. Subfigure 1 (top left): 'Be physically active' - Illustration: An anime character jogging forward with visible energy lines and a park environment suggested by minimal tree icons. Subfigure 2 (top middle): 'Control blood pressure and cholesterol' - Illustration: An anime doctor using a blood pressure cuff with a simplified chart icon showing healthy cholesterol levels in the background. Subfigure 3 (top right): 'Don't smoke' - Illustration: An anime character throwing a cigarette into a trash bin with a smoke-free icon in the background. Subfigure 4 (bottom left): 'Protect yourself from too much sun' - Illustration: An anime character wearing a hat and sunglasses under a simplified sun icon, applying sunscreen with a beach umbrella behind. Subfigure 5 (bottom middle): 'Drink alcohol in moderation' - Illustration: An anime character holding a glass of water beside a wine glass with a moderation symbol. Subfigure 6 (bottom right): 'Get enough sleep' - Illustration: An anime character peacefully sleeping in bed with a blanket and a nearby clock showing nighttime hours.

Table 3: Examples of our Text-to-Image generation prompts.




Figure 7: Screenshot of our developed platform for *HealthCards* dataset annotation.

where  $\omega \ge 0$  controls the guidance strength. Setting  $\omega = 1$  recovers the purely conditional sampler, while  $\omega > 1$  amplifies the influence of y.

# C More Detailed Explanation of Evaluation Setting

# **C.1** Text Rendering Score

To evaluate the quality of text rendering in generated images, we develop a pipeline that assesses how accurately the text elements are rendered and can be detected by OCR systems. We harness PaddleOCR (Contributors, 2025) to extract all identifiable words from the images.

As shown in Figure 8, while word-level identification and localization is achieved, these words require further processing to be reorganized into readable sentences that match the intended text layout of the flash cards.

Our text rendering evaluation pipeline consists of the following key steps:

# **C.1.1** Text Grouping and Ordering

We first perform an iterative grouping process to cluster detected text elements that belong together. This is accomplished through a two-step approach:



Figure 8: Examples of OCR text detection results showing word-level identification.

We merge overlapping bounding boxes to handle cases where OCR detects parts of the same text element as separate entities.

We iteratively group text elements whose distances are below a predefined threshold (20 pixels

in our implementation), continuing until no further merging occurs.

# **C.1.2** Reading Order Determination

After grouping, we determine the proper reading order of text elements within each group to reconstruct coherent text. Our approach follows natural human reading patterns (left-to-right, top-to-bottom):

We first identify line breaks within each text group by clustering the vertical (y-coordinate) positions of text elements. Text elements with vertical positions differing by less than one-third of the average text height are considered to be on the same line.

For each line, we sort text elements by their horizontal (x-coordinate) position to establish left-to-right reading order.

Finally, lines are arranged in top-to-bottom order to produce the complete reading sequence for each text group. A demo of this grouping and ordering process is visualized in Figure 9, where each group is enclosed by a dashed outline and numbers indicate the determined reading sequence.




Figure 9: Visualization of text grouping and reading order determination. Each colored rectangle represents an individual text box detected by OCR. Text boxes are grouped (indicated by dashed outlines) based on proximity and overlap. Numbers within each box indicate the reading order sequence determined by our algorithm, following natural reading patterns (left-to-right within lines, top-to-bottom across lines).

# **C.1.3** Text Matching and Evaluation

To evaluate text rendering quality, we compare OCR-extracted text against the expected text from the original flash card through the following process: (1) normalizing both text sets using case-

folding and standardization; (2) constructing a cost matrix of Levenshtein distances between extracted and expected text elements; (3) applying the Hungarian algorithm to determine optimal text matching that minimizes overall edit distance; and (4) computing Character Error Rate (CER) and Word Error Rate (WER) metrics between matched pairs. This approach enables objective measurement of text rendering fidelity independent of spatial arrangement variations.

# **C.2** Subfigure Counting Score

To evaluate the structural fidelity of generated flash cards, we implement a subfigure counting mechanism that assesses whether the correct number of visual elements are present. This metric is particularly important for multi-topic flash cards where each knowledge point should be accompanied by a corresponding illustration.

We employ the Qwen2.5-VL-32B model to detect and localize subfigures within the generated images. This multimodal vision-language model is capable of understanding complex visual layouts and identifying distinct visual elements. The model receives a prompt requesting detection of all subtopics or subfigures, and returns bounding box coordinates along with associated labels.



Figure 10: Illustration of subfigure detection using Qwen2.5-VL-32B model. Red bounding boxes indicate detected subfigures across various medical flash cards. The model successfully identifies distinct subtopics within each flash card, enabling accurate counting of knowledge points and their associated visual elements.

The prompt template used for this task is:

This image has several subtopics (subfigures) under the title. Please detect all subtopics (subfigures) in the image and return their locations in the form of coordinates. The bounding box should include the whole subfigure (including the subtitle and corresponding drawing).

As demonstrated in Figure 10, the model effectively localizes individual subfigures across various medical flash cards with different layouts and topics. For each generated flash card, we compare the number of detected subfigures against the expected count from the original flash card specification. We compute two key metrics:

- 1. **Mean Gap**: The absolute difference between the detected subfigure count and the expected count, averaged across all samples.
- Error Rate: The proportion of samples where the detected count does not match the expected count.

We exclude flash cards with only a single knowledge point from this evaluation, as the subfigure counting is primarily meaningful for multi-topic cards. Lower values for both metrics indicate better structural fidelity to the original flash card design.

This evaluation approach objectively quantifies a model's ability to maintain the intended structural organization of educational flash cards, which is crucial for proper information hierarchy and visual organization in educational materials.

# **C.3** Subfigure Alignment Score

After localizing individual subfigures within the healthcards, we evaluate how well each subfigure aligns with its intended knowledge point. This alignment assessment is critical for educational materials, as it measures whether the visual representations accurately convey the corresponding concepts. We employ two complementary metrics to quantify this alignment: CLIP Score and VQA Score.

#### C.3.1 CLIP Score

We utilize the Contrastive Language-Image Pretraining (CLIP) framework (Hessel et al., 2021) to measure the semantic similarity between each subfigure and its corresponding textual description. Specifically, we employ ViT-L-14-336 CLIP model (Radford et al., 2021) to compute cosine similarity between image and text embeddings. This

approach provides a direct measurement of how well the generated visual elements match their intended semantic content.

The CLIP Score ranges from 0 to 1, with higher values indicating stronger alignment between the subfigure and its textual description. This metric effectively captures the general semantic correspondence but may not fully assess more complex relationships or fine-grained details.

### C.3.2 VQA Score

To complement the CLIP Score with a more contextual understanding of image-text alignment, we implement a Visual Question Answering (VQA) approach (Lin et al., 2024) using the CLIP-FlanT5-XXL model. This model evaluates whether the subfigure contains the necessary visual information to answer questions derived from the knowledge point description.

For each subfigure, we treat the knowledge point description as a prompt or implicit question that the image should address. The VQA Score represents the model's confidence (from 0 to 1) that the subfigure adequately illustrates the described concept. This metric provides insight into how well the subfigure serves its educational purpose by visually representing the intended knowledge.

By combining these two alignment metrics, we obtain a comprehensive assessment of how effectively each subfigure communicates its intended educational content. This evaluation is crucial for ensuring that generated flash cards not only maintain correct structure but also convey accurate and clear visual representations of the knowledge points they aim to illustrate.

# **D** Details of Human Evaluation

Here we provide instruction to the human evaluators, in Figure 11.

# E More Experimental Results and Analysis

# **E.1** Different Training and Inference Settings

In this section, we present additional experimental results using Flux.1[Dev], as shown in Table 4. We investigate: (1) Different LoRA ranks, ranging from 1 to 256; (2) Various scales of classifier-free guidance; (3) Fine-tuning with Flux.1[Dev]'s textrendering specialist, *LexFlux* (Zhao et al., 2025); and (4) Different data ratios during training (while

Table 4: More Experimental Study of hyperparameters and settings.

	Text Re	ndering	Subfig	ure Counting	Subfigure Al	ignment	General				
Model	WER↓	CER↓	Gap↓	Error Rate↓	$\overline{\text{ClipScore}_s \uparrow}$	$\overline{\mathrm{VQA}_s}$	Aesthetic↑	Quality↑	VQA↑		
LoRA r1	0.223	0.149	0.115	0.112	0.261	0.828	3.361	4.613	0.830		
LoRA r16	0.152	0.088	0.119	0.115	0.264	0.838	3.396	4.614	0.832		
LoRA r64	0.153	0.092	0.016	0.016	0.265	0.852	3.387	4.606	0.836		
LoRA r256	0.155	0.097	0.055	0.051	0.265	0.859	3.404	<u>4.635</u>	0.835		
CFG guidance3	0.191	0.109	0.014	0.010	0.261	0.850	3.377	4.611	0.830		
CFG guidance7	0.191	0.209	0.004	0.004	0.262	0.844	3.352	4.618	0.835		
CFG guidance10	0.204	0.119	0.012	0.006	0.260	0.841	3.337	4.604	0.831		
LexFlux	0.173	0.109	0.031	0.031	0.265	0.858	3.409	4.632	0.837		
20% Data	0.195	0.133	0.045	0.041	0.265	0.854	3.384	4.601	0.836		
50% Data	0.154	0.096	0.072	0.072	0.266	0.852	3.406	4.628	0.835		
75% Data	0.124	0.065	0.039	0.035	0.266	0.858	3.405	4.634	0.835		
Ours	0.118	0.064	0.010	0.008	0.265	0.861	3.429	4.636	0.838		

Text Readability Definition: This dimension evaluates the clarity, legibility, and accuracy of all text elements in the healthCard.  1. Paper (2). Note that the control of the control of 1.5: 1. Paper (2). Note that illegible sweeper bullering or contains numerous spelling/grammatical errors. Text may be cut off or incomplete. Reading the content requires significant effort.  2. Fair (2). Text is partially legible but contains several errors or incomplete. Reading the content requires significant anilor too large; 5. Some words may be difficult to read.  3. Most term are correctly spelled Fort choices and size are mostly appropriate, though some improvements could be made.  4. Good (4): Text is clarity legible with minimal errors. Front choices and size are appropriate, theaders and body text are well-differentiated. New few reading differentiated for the reverse for the control of the control	Leyout Organization  Ordanization insuration evaluates the structural organization of the  Image, particularly focusing on whether the number of subfigures  matches the requested count and whether each subfigure has clear,  distinct boundaries that make it visually independent.  Rating Scale:  Poor (1): Incorrect number of subfigures (does not match the required  mumber of inowhedge points). Subfigures lack clear boundaries and  sumber of inowhedge points). Subfigures lack clear boundaries and  surface of the subfigures in the subfigures and  Fair (2): Number of subfigures may be slightly off from what was  requested. Some subfigures has when clear boundaries or partially  overlap, reducing visual independence.  Acceptable (3): Correct number of subfigures with generally  recognizable boundaries. Most subfigures appear as distinct visual  visually independent of subfigures with generally  recognizable boundaries. Most subfigures appear as distinct visual  visually independent and properly spaced from  others, creating a well-organized laplus with case visual  boundaries. Subfigures is visually independent and properly spaced from  others, creating a well-organized laplus with case visual  defined boundaries. Each subfigure stands as a compitety  independent visual unit with optimal spacing and clear delineation,  making the organization all structure limendelity's appears  making the organization all structure inmediately appears.
Text-Subfigure Alignment Definition: This dimension evaluates how well each textual element corresponds to its associated visual element, and whether the visual content accurately represents the described concept.  Instructions: Repair either text-availager alignment on a scale of 1-5 instructions scales and the text-availager alignment on a scale of 1-5 instructions scales are the text-availager alignment on a scale of 1-5 idescriptions. Images appear unrelated to the health topic. Significant disconnection between text and visuals.  2.Fair (2): Some visual elements relate to their text but with major inaccuracion misorperesentations, connection between text and visuals is weak.  3.Acceptable (3): Most visual elements align with their text descriptions, though some representations may be generic or partially descriptions, though some representations are appropriate for the health concepts being presented.  5. Excellent (5): All visual elements clearly talling with their text descriptions. Visual accurately and meaningfully represent the health concepts, enhancing understanding beyond what text alone could convey.	Overall Quality  Definition: This dimension evaluates the overall effectiveness of the HealthCard as an educational tool, considering all aspects together, Instructions: Please rate the overall quality on a scale of 1-5: Poor (1): The HealthCard is unsuable for healthcare deucation. Major flaws in multiple dimensions make it potentially misleading or ineffective Would require complete redesign to be useful. Fair (2): The HealthCard has significant shortcomings that limit is, Fair (2): The HealthCard has significant shortcomings that limit is, HealthCard has significant shortcomings that limit is, HealthCard has significant shortcomings that immunity is the HealthCard has significant shortcomings that immunity is the HealthCard flaw of the communications before use in HealthCard (3): The HealthCard could serve as an educational tool with minor areas for improvement. It clearly communicates health information in a pencelly accessible way.  Excellent (3): The HealthCard is an effective educational tool with minor areas for improvement. It clearly communicates health information in a study.  Excellent (3): The HealthCard health information in a study.  Excellent (3): The HealthCard health information in a study.  Excellent (3): The HealthCard health information in a study.

Figure 11: Instructions for human evaluation.

maintaining consistent total iterations). For reference, our primary model was trained with LoRA rank 128, using the complete dataset and CFG guidance of 5.

Results indicate that slightly increasing CFG to 7 enhances subfigure counting performance, though at the expense of text rendering quality. Both excessive and insufficient guidance lead to deterioration across all metrics. Surprisingly, utilizing a text rendering-specialized pretrained model did not yield improvements, possibly because preoptimization introduces biases that impede learning for our specific task.

From the data ratio experiments, we observe that performance metrics generally improve with increased data usage, particularly for text rendering scores. This demonstrates the value of our dataset's scale. Finally, rank 128 demonstrates the best per-

formance, as both higher and lower ranks result in decreased performance.

# **E.2** Different Text-to-Image Prompts Designs

To investigate how prompt design affects image generation quality, we conducted ablation experiments on prompt structures using 120 test samples (20 each for 1–6 subfigures). We constructed several prompt variants based on our original template to evaluate the impact of different prompt components on generation performance. The illustration, examples and results are shown in Table 5.

The original prompt generally yields the best or near-best results across most evaluation metrics, achieving the lowest text rendering errors and highest subfigure alignment scores. While Variant A slightly improves subfigure counting performance, this comes at the cost of text rendering quality. Other variants either reduce layout control, introduce ambiguity, or hurt content alignment, as evidenced by increased error rates and lower semantic alignment scores.

Variant B, which removes the emphasis on clarity, readability, and approachable style, leads to degraded layout organization while achieving the highest aesthetic scores. This suggests that explicit style instructions are important for generating well-structured and informative images, though their removal may paradoxically improve visual aesthetics.

Removing layout descriptions from the prompt (Variant C) results in a clear drop in subfigure counting accuracy, validating the importance of explicitly specifying layout details in prompt design for structural fidelity.

When using raw healthcare knowledge content

instead of pictorial illustration cues (Variant D), we observe a significant decline in text rendering performance. This occurs because GPT-4o-Image tends to render lengthy medical content as raw text in the image, introducing visual noise and lowering text rendering performance. We also notice reduced subfigure alignment for this variant, likely because non-visual medical descriptions are harder for the model to translate into coherent illustrations, resulting in poorer text-image correspondence.

These results help demonstrate that our original prompt template was carefully designed and effectively balances structural control, visual clarity, and content alignment for healthcare flashcard generation.

# E.3 More Evidence of Evenness Bias and the Effects of Finetuning

In this section, we present a more comprehensive quantitative analysis of the evenness bias phenomenon and its mitigation through fine-tuning with our dataset.

Table 6 presents confusion matrices comparing expected versus generated subfigure counts for three open-source models: Stable Diffusion 3.5 Large, HiDream-I1, and Flux.1[Dev], both before and after fine-tuning.

As shown, before fine-tuning, open-source models exhibit a strong evenness bias, often producing incorrect subfigure counts towards even numbers. For example, raw Flux.1[Dev] completely fails to generate 3 subfigures (0% accuracy), always defaulting to 4 subfigures instead. When tasked with 5 subfigures, it achieves only 20.8% accuracy.

After fine-tuning with our dataset, this bias is greatly reduced, with the generated subfigures much more accurately matching the ground-truth number. Fine-tuned Flux.1[Dev] achieves 94.9% accuracy for 3 subfigures and 97.2% for 5 subfigures. Similar improvements are observed across all models, demonstrating that our HealthCards dataset effectively mitigates evenness bias while maintaining generation quality in other dimensions.

Table 5: Prompt ablation study: (a) Prompt variants used in experiments, (b) Quantitative results across evaluation metrics.

				(a) Proi	mpt Variants								
Name	Modif	ication	Exa	ample									
Original			three sub and ing An con anim	Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations three knowledge points. Use a two-layer grid layout (two above, one below). Easubfigure should include a clear title and illustration, emphasizing clarity, readabil and an approachable style. Topic (title) of FlashCard: 'Causes of Nausea and Voning'. Subfigure 1 (top left): 'Medicines including cancer chemotherapy' - Illustration. An anime character receiving IV chemotherapy treatment in a clinic, expressing m concern but resilience. Subfigure 2 (top right): 'GERD and ulcers' - Illustration: anime character grimacing in discomfort near a visual diagram showing acid refl moving up the esophagus. Subfigure 3 (bottom): 'Intestinal obstruction' - Illustration anime-style illustration of a character lying on a hospital bed, clutching the abdomen with a medical diagram of a blocked intestine nearby.									
Variant A	ing in	xplicit cou struction subfigure nents	be- for re- You sho app Sub- anii	Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for three knowledge points. Use a two-layer grid layout (two above, one below). <b>You must generate a flashcard image with exactly 3 subfigures!</b> Each subfigure should include a clear title and illustration, emphasizing clarity, readability, and an approachable style. Topic (title) of FlashCard: 'Causes of Nausea and Vomiting'. Subfigure 1 (top left): 'Medicines including cancer chemotherapy' - Illustration: An anime character receiving IV chemotherapy treatment in a clinic, expressing mild concern but resilience (omitted for brevity)									
Variant B	Remov phasis	ve style o phrase	thre sub <del>and</del> ing An	Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for three knowledge points. Use a two-layer grid layout (two above, one below). Each subfigure should include a clear title and illustration, emphasizing clarity, readability and an approachable style. Topic (title) of FlashCard: 'Causes of Nausea and Voming'. Subfigure 1 (top left): 'Medicines including cancer chemotherapy' - Illustration An anime character receiving IV chemotherapy treatment in a clinic, expressing mit concern but resilience (omitted for brevity)									
Variant C	scription	ve layout ons and po pecification	osi- three ns sub and ing	Design a clean, 1:1 aspect ratio medical flashcard with anime-style illustrations for three knowledge points. Use a two-layer grid layout (two above, one below). Each subfigure should include a clear title and illustration, emphasizing clarity, readability and an approachable style. Topic (title) of FlashCard: 'Causes of Nausea and Vomiting'. Subfigure 1 (top left): 'Medicines including cancer chemotherapy' - Illustration An anime character receiving IV chemotherapy treatment in a clinic, expressing mile concern but resilience (omitted for brevity)									
					receiving IV chen		treatment in a		ustration:				
Variant D	lustrati	ee pictoria ion cues w owledge c	con l il- Des vith thre con- sub and ing Me and	cern but resilience sign a clean, 1:1 see knowledge pointing figure should include an approachable an approachable an approachable but including a clear, and a clear, and a clear and a c	receiving IV chen	cal flashca ayer grid l and illustra e) of Flash es includ chemothe ) and ulce	ard with anime ayout (two about ition, emphasized) are are cancer che crapy. Subfigur	e-style illustra ove, one beloving clarity, re of Nausea ar motherapy' - e 2 (top right)	ustration: sing mild ations for w). Each adability, ad Vomit- Content: : 'GERD				
Variant D	lustrati raw kn	ion cues w	con l il- Des vith thre con- sub and ing Me and	cern but resilience sign a clean, 1:1 are knowledge pointing figure should include an approachable an approachable an approachable and approac	receiving IV chence (omitted for aspect ratio mediants. Use a two-ladude a clear title as style. Topic (title op left): 'Medicing those for cancernt: GERD (reflux	cal flashca ayer grid l and illustra e) of Flash es includ chemothe ) and ulce	ard with anime ayout (two about ition, emphasized) are are cancer che crapy. Subfigur	e-style illustra ove, one beloving clarity, re of Nausea ar motherapy' - e 2 (top right)	ustration: sing mild ations for w). Each adability, ad Vomit- Content: : 'GERD				
Variant D	lustrati raw kn	ion cues w owledge c	con I il- Des vith thre con- sub and ing Me and obs	cern but resilience sign a clean, 1:1 are knowledge pointing figure should include an approachable an approachable an approachable and approac	receiving IV chemes (omitted for aspect ratio mediants. Use a two-ladude a clear title as estyle. Topic (title op left): 'Medicing those for cancernt: GERD (reflux Intestinal obsti	or brevity) cal flashed ayer grid l and illustrate) of Flash hes include chemothed) and ulce ruction.	ard with anime ayout (two about on, emphasize arcard: 'Causes ing cancer che erapy. Subfigure 3	e-style illustra ove, one beloving clarity, re of Nausea ar motherapy' - e 2 (top right)	ustration: sing mild ations for w). Each adability, ad Vomit- Content: : 'GERD				
Variant D  Variants	lustrati raw kn tent	ion cues w owledge c	con I il- Des vith thre con- sub and ing Me and obs	sign a clean, 1:1 are knowledge point an approachable and approachab	receiving IV chence (omitted for aspect ratio mediants. Use a two-lade a clear title astyle. Topic (title op left): 'Medicing those for cancer at: GERD (refluxnt: Intestinal obstitative Results	or brevity) cal flashed ayer grid l and illustrate) of Flash hes include chemothed) and ulce ruction.	ard with anime ayout (two about on, emphasize arcard: 'Causes ing cancer che erapy. Subfigure 3	e-style illustrative, one belowing clarity, refer of Nausea armotherapy' - e 2 (top right) 8 (bottom): 'I	ustration: sing mild ations for w). Each adability, ad Vomit- Content: : 'GERD				
<b>Variants</b> Original	lustrati raw kn tent  Text Rec  WER↓  0.032	ndering CER  0.023	con It il- Des with thre con- sub and ing Me and obs  Subfig  Gap  0.100	cern but resilience sign a clean, 1:1 see knowledge point an approachable? Subfigure 1 (to dicines, including ulcers' - Content (b) Quant ure Counting Error Rate \ 0.100	receiving IV chemes (omitted for aspect ratio mediants. Use a two-ladude a clear title as estyle. Topic (title op left): 'Medicing those for cancernt: GERD (reflux Intestinal obstantiative Results  Subfigure Ali  CLIPScore  0,274	or brevity) cal flashed and illustrate) of Flash desinclude chemothed and ulce ruction.  gnment VQA↑ 0,910	ard with anime ayout (two aboution, emphasize acancer che crapy. Subfigure 3  Aesthetic  3.472	clinic, express e-style illustra ove, one beloving clarity, re of Nausea ar motherapy' - e 2 (top right) 3 (bottom): 'I  General  Quality  4.585	ustration: sing mild ations for w). Each adability, id Vomit- Content: : 'GERD intestinal  VQA↑  0.825				
Variants Original Variant A	Text Rev WER↓  0.032 0.063	ndering CER↓ 0.023	con It il- Des with three con- sub and ing Me and obs  Subfig  Gap  0.100 0.080	cern but resilience sign a clean, 1:1 see knowledge pointing an approachable? Subfigure 1 (to dicines, including ulcers? - Contentruction? - Contentruction? - Contentruction and the counting the count	receiving IV chemics (omitted for aspect ratio mediants. Use a two-lad lude a clear title aspect ratio received in the style. Topic (title op left): 'Medicing those for cancer at: GERD (reflux Intestinal obstants: Intestinal obstants: Subfigure Alic CLIPScore \$\frac{0.274}{0.271}\$	cal flashed ayer grid I and illustrate) of Flash desincted to chemothed and ulce ruction.  gnment  VQA↑  0.910  0.906	ard with anime ayout (two aboution, emphasized ard: 'Causes ing cancer che erapy. Subfigure 3.482	eclinic, express e-style illustra eve, one beloving clarity, re of Nausea ar motherapy' - e 2 (top right) 8 (bottom): 'I  General Quality  4.585 4.573	ustration: sing mild tions for w). Each adability, nd Vomit- Content: : 'GERD intestinal  VQA↑  0.825 0.808				
Variants Original	lustrati raw kn tent  Text Rec  WER↓  0.032	ndering CER  0.023	con It il- Des with thre con- sub and ing Me and obs  Subfig  Gap  0.100	cern but resilience sign a clean, 1:1 see knowledge point an approachable? Subfigure 1 (to dicines, including ulcers' - Content (b) Quant ure Counting Error Rate \ 0.100	receiving IV chemes (omitted for aspect ratio mediants. Use a two-ladude a clear title as estyle. Topic (title op left): 'Medicing those for cancernt: GERD (reflux Intestinal obstantiative Results  Subfigure Ali  CLIPScore  0,274	or brevity) cal flashed and illustrate) of Flash desinclude chemothed and ulce ruction.  gnment VQA↑ 0,910	ard with anime ayout (two aboution, emphasize acancer che crapy. Subfigure 3  Aesthetic  3.472	clinic, express e-style illustra ove, one beloving clarity, re of Nausea ar motherapy' - e 2 (top right) 3 (bottom): 'I  General  Quality  4.585	ustration: sing mild attions for w). Each adability, ad Vomit-Content: 'GERD Intestinal				

Table 6: Confusion matrices comparing expected vs. generated subfigure counts for open-source models before and after fine-tuning. Values represent the ratio of generating each number of subfigures given the ground truth requirement. Bold values highlight correct predictions on the diagonal.

								Before	Fine-tu	ning								
SD3.5 Large HiDream-I1									am-I1	1 Flux.1[Dev]								
GT/Gen	1	2	3	4	5	6	1	2	3	4	5	6	1	2	3	4	5	6
1	1.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.000
2	0.000	0.960	0.006	0.029	0.006	0.000	0.000	0.983	0.006	0.006	0.000	0.006	0.000	0.994	0.000	0.006	0.000	0.000
3	0.000	0.889	0.009	0.103	0.000	0.000	0.000	0.684	0.051	0.214	0.009	0.043	0.000	0.000	0.000	1.000	0.000	0.000
4	0.000	0.068	0.000	0.932	0.000	0.000	0.000	0.046	0.057	0.874	0.000	0.023	0.000	0.000	0.000	1.000	0.000	0.000
5	0.000	0.408	0.014	0.197	0.056	0.324	0.000	0.028	0.056	0.789	0.028	0.099	0.000	0.000	0.000	0.444	0.208	0.347
6	0.000	0.069	0.000	0.086	0.017	0.828	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.000	0.034	0.017	0.949
								After	Fine-tur	ing								
			SD3.5	Large					HiDre	am-I1					Flux.	1[Dev]		
GT/Gen	1	2	3	4	5	6	1	2	3	4	5	6	1	2	3	4	5	6
1	1.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.000
2	0.000	0.994	0.006	0.000	0.000	0.000	0.000	0.994	0.000	0.000	0.000	0.006	0.000	1.000	0.000	0.000	0.000	0.000
3	0.000	0.000	0.915	0.085	0.000	0.000	0.000	0.000	0.897	0.103	0.000	0.000	0.000	0.026	0.949	0.026	0.000	0.000
4	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.011	0.977	0.011	0.000
5	0.000	0.000	0.000	0.000	0.986	0.014	0.000	0.014	0.000	0.014	0.528	0.444	0.000	0.000	0.000	0.028	0.972	0.000
6	0.000	0.000	0.000	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0.018	0.982	0.000	0.000	0.000	0.000	0.000	1.000

#### F Checklist

#### F.1 Potential Risks

Despite improvements through fine-tuning, our models occasionally generate inaccurate or misleading healthcare information, which presents significant concerns in educational contexts. Incorrect visual representations of medical concepts could lead to misunderstanding among learners and potentially influence future healthcare decisions. The visually compelling nature of the generated flashcards might increase the likelihood that incorrect information is trusted and remembered, amplifying the impact of any inaccuracies. We strongly recommend human expert review before deployment in actual educational settings, and future work should explore developing robust verification mechanisms specifically for healthcare content. Addressing these safety concerns will be crucial for responsible implementation of these technologies in health education.

# F.2 Use Or Create Scientific Artifacts

### **F.2.1** Cite Creators Of Artifacts

We sourced credible healthcare resources from the NIH MedlinePlus website. According to the webpage<sup>3</sup>, certain content is in the public domain and not copyrighted. We strictly followed their guidelines to ensure all sourced knowledge was from non-copyrighted sections, including health topic summaries, medical test information, Genetics page summaries, and illustrations with the "U.S. National Library of Medicine" watermark. For citation of creators, we include the acknowledgment "Courtesy of MedlinePlus from the National Library of Medicine" as required by the website. We also utilize GPT-40-Image (OpenAI, 2025) and have properly cited this in our paper.

#### **F.2.2** Discuss The License For Artifacts

As mentioned in the previous subsection, our sourced knowledge information is not copyrighted. This data source was also used by previous work (Ben Abacha and Demner-Fushman, 2019), which shared their dataset under the Creative Commons Attribution 4.0 International License (CC BY).

# F.2.3 Artifact Use Consistent With Intended Use

Yes, our use of artifacts strictly follows the guidelines provided by MedlinePlus. We only utilize content that is explicitly marked as being in the public domain. Our artifacts will be released under the Creative Commons Attribution 4.0 International License (CC BY).

# **F.2.4** Data Contains Personally Identifying Info Or Offensive Content

No. No personally identifying data has been created or included. We have not observed any identifiable personal data in our dataset.

#### F.2.5 Statistics For Data

Please refer to Section 4.3.

# F.3 Computational Experiments

# F.3.1 Model Size And Budget

40 H100 GPU hours are required for training a Flux.1[Dev] (Labs, 2024) which has 12B parameters.

# **F.3.2** Descriptive Statistics

We report results of single runs, due to computational limitations. As aforementioned, it requires 40 H100 GPU hours to finetune a model. Our results are reproducible.

### **F.3.3** Parameters For Packages

Yes, we have included necessary mentions of models used, such as QwenVL (Bai et al., 2025) and PaddleOCR (Contributors, 2025).

# **F.4** Human Subjects Including Annotators

#### **F.4.1** Instructions Given To Participants

Yes, we have provided screenshots of annotation platforms and instructions for annotating in section A.

# F.4.2 Recruitment And Payment

All annotators were recruited as volunteers and paid at rates exceeding local standards.

#### F.4.3 Data Consent

Yes. We have explained the purpose of our work to all annotators. They are aware and have agreed that their opinions, such as ratings and modifications of text-to-image prompts, will be used as public data. Throughout the process, no personally identifiable information was collected.

<sup>3</sup>https://medlineplus.gov/about/using/usingcontent/

# F.4.4 Ethics Review Board Approval

Yes, data collection in this study was conducted in strict accordance with the licensing requirements of all sources, without the use of sensitive data or the conduct of sensitive experiments. This project is determined to be exempt.

# **F.4.5** Characteristics Of Annotators

Yes, we describe this in Section 4.

# F.5 AI Assistants In Research Or Writing

# F.5.1 Information About Use Of Ai Assistants

Yes, we used AI assistants like Claude, Gemini, and GPT40 only for polishing language use.